CTART UNCLA	SSIFIED 003551
Westinghouse	Manual No. WHC-CM- 2-14
Hanford Company Richland, Washington	Date Copy No.
Hanford Operations and Engineering Contractor for the U.S. Department of Energy under Contract DE-AC06-87RL10930	(Reserved for Controlled Documents and Distribution Use Only)
HAZARDOUS MATERIALS PACKAGING & SHIPPING	
Author WHC TRAFFIC GROUP	AUG 2 4, 10:00 pages service of control of the cont

This is a CONTROLLED Manual. The assigned custodian is responsible for this copy and all revisions. If no longer needed, return to: Controlled Documents and Distribution.

crs 22.6.a

Q)

Andreas Carrier

က အ

Responsible Custodian	Payroli No.	, Bldg.	MSIN	Area	Date Assigned
B.S. Sprause	69586	450Hills	H4-51	3000	A)
ł					
				-	
(121316)					
SEP 1989 SE RECEIVED SE EDMC SE RECEIVED SE EDMC SE STATE DE SE ST					
SEP 1989 SA					
EDMC B					
	J U	NCLASSIFIED			BD-6100-151

THIS PAGE INTENTIONALLY LEFT BLANK



WESTINGHOUSE HANFORD COMPANY CONTROLLED MANUAL REVISION RECORD

	CONTROLLE	U MANUA	IT KEAIZION KECOKD	•	
Manual Number: WHC-	см-2-14		Copy Number	C3	
Manual Title: HAZA					
	•				
Revision Release Number/Date	Date Revisions Filed	Revised By (Initial)	Revision Release Number/Date	Date Revisions Filed	Revised By (Initial)
1 / 3-03-89	3-22-89		. That		
2 / 6/26/89	7/12/89, 🕆	r KLB			
· · · · · · · · · · · · · · · · · · ·		\$#1 E		<u> </u>	
			<u> </u>		
					
· · · · · · · · · · · · · · · · · · ·					
	Company Company				
			<u>. </u>		
				-	
					•
<u> </u>	,		'		1
	Power or				
.,					-
			· · · · · · · · · · · · · · · · · · ·		
					· ·
		1		 	

jury.

2. Q.)

(___)

Ne Jan

1. h

(Place behind Unclassified Controlled Coversheet)

THIS PAGE INTENTIONALLY LEFT BLANK

Hazardous Material Packaging and Shipping

Procurement and Materials Management

Date Published July 1988

()



Westinghouse
Hanford Company
Richland, Washington 99352

Hanford Operations and Engineering Contractor for the U.S. Department of Energy under Contract DE-AC06-87RL10930

DIS				-	•
1115	-11	д.	TA S	-	ж

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Printed in the United States of America

HAZARDOUS MATERIAL PACKAGING	Manua l	WHC-CM-2-14
AND SHIPPING	Section	Table of Contents
	Pag e	· 1 of 5
TABLE OF CONTENTS	Effective Date	July 15, 1989

,

		<u>Page</u>	REV	Effective <u>Date</u>
	PART I INTRODUCTION	I-1	0	08/01/88
	1.0 Purpose and Scope	I-1		
	PART II RESPONSIBILITIES AND PROCEDURES FOR ALL HAZARDOUS MATERIALS SHIPMENTS	II-1	1	03/20/89
7.7 3 0 4 9 5	1.0 Responsibilities 1.1 Procurement and Materials Management 1.1.1 Traffic 1.2 Operations Organizations 1.3 Safety 1.4 Packaging and Remote Systems 1.4.1 Packaging Development 1.5 Safeguards and Security 1.6 Packaging and Shipping Subcouncil (PSSC) 1.7 WHC Approval Authority 1.8 Quality Assurance 1.9 Procurement 1.10 Technical Training 1.11 Defense Waste Management 1.12 Site Services	II-1 II-1 II-4 II-4 II-5 II-5 II-6 II-6 II-7 II-7 II-7		
enterna	2.0 Procedures2.1 Delegation, Training and Approval of Shippers	II-8 II-8		
© ©	2.2 Receivers of Hazardous Material Shipments2.3 Non Compliance Procedures and Variance Reports	II-8 II-10		
	2.3.1 Offsite 2.3.2 Onsite 2.4 Packaging Procedures 2.4.1 Tiedown Procedures 2.4.2 Radioactive Shipment Checklist 2.4.3 Onsite Packaging Systems 2.4.4 Offsite Packaging Systems	II-10 II-12 II-12 II-12 II-12 II-16		
	PART III NONRADIOACTIVE HAZARDOUS MATERIALS/ HAZARDOUS WASTE (HM/HW) SHIPMENTS	III-1	0	08/01/88
	<pre>1.0 Introduction 1.1 Offsite HM/HW Shipment 1.2 Onsite HM/HW Shipment</pre>	III-1 III-1 III-2		
)	2.0 Procedure for Making HM/HW Shipments	III-2		

HAZARDOUS MATERIAL PACKAGING AND SHIPPING	Manual Section Page	WHC-CM-2-14 Table of Contents 2 of 5
TABLE OF CONTENTS	Effective Date	July 15, 1989

		<u>Page</u>	REV	Effective <u>Date</u>
3.0	Preparing a Hazardous Material Shipment	III-6		
3.1	Record (HMSR) Shipment Description Section Completed	III-6		
3.2 3.3	by Originator Certification Section Completed by Certifier Offsite Shipment Approval Section Completed by Traffic	III-8 III-8		
4.0	Preparing a Uniform Hazardous Waste Management (UHWM)	B-III	ı	
4.1 4.2	Generator Section Completed by Originator Transportation Section Completed by Transportation	III-8 III-11		
4.3	Facility Section Completed by Treatment Storage, Disposal Facility	III-11		
PART	IV RADIOACTIVE MATERIAL SHIPMENTS	IV-1	0	08/01/88
1.0 1.1 1.2	Onsite Shipping Procedures General Requirements/Responsibilities 1.1.1 Manager of Facility 1.1.2 Authorized Hazardous Materials Shipper 1.1.3 Vehicle Driver Normal Onsite Radioactive Material Shipments, Procedures 1.2.1 Definition of Material 1.2.2 Shipping Container Selection, Preparation and Transport Preparing Onsite Radioactive Shipping Record (RSR) 1.3.1 Shipper Section Completed by Packager/Shipper 1.3.2 Radiation Monitor Selection Completed by RPT 1.3.3 Carrier Section Completed by Packager/Shipper 1.3.4 Certification Section Completed by Certifier Onsite Routine Radioactive Shipments	IV-1 IV-1 IV-1 IV-3 IV-3 IV-4 IV-6 IV-11 IV-11 IV-13 IV-13 IV-14		
1.7	1.4.1 How to obtain an ORRSR 1.4.2 Use of the ORRSR	IV-14 IV-18		
2.0 2.1	Miscellaneous Radioactive Material Shipments Fissile Material and SNM 2.1.1 Fissile Exempt Material Onsite/Offsite Shipment	IV-21 IV-21 IV-21		

1 m

Manual Section Page Effective Date

WHC-CM-2-14 Table of Contents 3 of 5 July 15, 1989

TABLE OF CONTENTS

€3.3°

dia. 14

43, 4

 \bigcirc C>

		<u>Page</u>	<u>REV</u>	Effective Date
	2.1.2 Fissile Material Offsite/Onsite Shipment	IV-22		
	2.1.3 Fissile Classes	IV-22		
	2.1.4 Accountable Material	IV-22		
	2.1.5 Approvals for Offsite Shipments of Radioactive Material	IV-23		
	2.1.6 Categorization and Physical	IV-24		
	Protection for SNM Shipment			
	2.1.7 Security Exceptions for Onsite Shipments of SNM	IV-25		
2.2	Radioactive Mixed Waste	IV-25		
2.3	Controlled Vehicles	IV-26		
3.0	Offsite Shipping Procedures	IV-26		
3.1	Shipper's Responsibilities	IV-26		
3.2	General Procedure for Offsite	IV-28		
	Radioactive Material Shipments	711 00		
	3.2.1 Definition of Material	IV-28		
	3.2.2 Shipping Containers, Packaging and Transport	IV-28		
3.3	Preparing Offsite Radioactive Shipment Record (ORSR)	ĮV-34		
	3.3.1 Shipment Instruction Section Completed by Originator	IV-34		
	3.3.2 Shipment Description Section	IV-34		
	Completed by Originator/Shipper 3.3.3 Area Radiation Monitoring Section Completed by Radiation Protection Technologist	IV-38		
	3.3.4 Authorization for Shipment and Certification Section Completed by Certifier	IV-39		
	3.3.5 Approval for Offsite Shipment Section Completed by Traffic	IV-39		
3.4	Radioactive Material Transported by the Transportation Safeguards Division, U.S. Department of Energy, Albuquerque Operations Office	IV-39		
	3.4.1 Responsibilities	IV-39		
	3.4.2 General Procedures	IV-40		
	3.4.3 Specific Receiving Procedures	IV-41		
	3.4.4 Specific Shipping Procedures	IV-42		
	3.4.5 Shipping Papers	IV-45		

HAZARDOUS MATERIAL PACKAGING AND SHIPPING		Manual Section Page	,	WHC-CM-2-14 Table of Contents 4 of 5		
TABLE	OF CONTENTS	Effective	Date	Ju	ly 15, 1989	
			<u>Page</u>	<u>REV</u>	Effective Date	
PART \	SHIPPING AND RECEIVING HAZARDOUS MATERIAL IN THE 1100 AREA		V-1	0	08/01/88	
1.0	Procurement and Materials Management (PMM) as Shipper/Receiver for DOE-R	L	V-1			
1.1	Exceptions to the PMM Function as Shipper/Receiver for DOE-RL		V-3			
1.2	Shipping, Traffic, and Receiving Ope 1.2.1 Shipping 1.2.2 Traffic 1.2.3 Receiving	rations	V-3 V-3 V-4 V-5			

C)

. . ***

HAZARDOUS MATERIAL PACKAGING	Manual	WHC-CM-2-14
AND SHIPPING	Section	Table of Contents
TABLE OF CONTENTS	Page Effective Date	. 5 of 5 July 15, 1989
INDEL OF CONTENTS	FILECTIAE DOTE	Outy 13, 1303

APPENDICES

		REV	Effective <u>Date</u>
	i Norway		
Α.	Course Outlines and Objectives.	0	03/20/89
В.	Shipment Examples.	O	08/01/88
С.	Radioactive Material Characterization.	0	03/20/89
D.	Prenotification Requirements for Offsite Shipment of Radioactive Material.	0	08/01/88
Ε.	Radioactive Materials Packaging Quality Assurance Program Plan	0	07/15/89
G1o:	ssary and Acronyms	I	07/15/89

(_)

٥٠ الإ

С

م مرازیان

THIS PAGE INTENTIONALLY LEFT BLANK

Manual Section Page Effective Date WHC-CM-2-14 Appendices 1 of 1 August 1, 1988

APPENDICES

APPENDICES

- A. Training Course Requirements, scope, outline.
- B. Shipment Examples.
- C. Radioactive Material Characterization Tables.
- D. Prenotification Requirements for Offsite Shipment of Radioactive Material.
- E. Glossary and Acronyms

Reserved

Reserved

0

 \bigcirc

101 Jan

Reserved

THIS PAGE INTENTIONALLY LEFT BLANK

WESTINGHOUSE HANFORD COMPANY

Manual Section Page WHC-CM-2-14
PART I, REV 0

HAZARDOUS MATERIAL PACKAGING AND SHIPPING

Effective Date Organization

l of 2 August 1, 1988 Procurement and Materials Mgmt

TITLE:

INTRODUCTION

Approved by

D. K. Quigley, Manager

Procurement and Materials Mgmt

1.0 PURPOSE

This manual defines the requirements, responsibilities and procedures necessary to ensure all hazardous material shipments are packaged and transported in a manner that complies with all the appropriate regulations and minimizes risk to employees, the shipping industry, the public and the environment.

2.0 SCOPE

0

 \bigcirc

(·

This manual delineates to Westinghouse Hanford Company (WHC) personnel requirements and procedures for properly packaging and shipping hazardous materials and wastes both onsite and offsite at Hanford. It incorporates handling, containment and control standards established by Defense Waste Management, Environmental, Safety, Quality Assurance and Security, Resource Allocation and Management and Advanced Reactor Development. This manual further ensures, by summary or by reference, that all hazardous material shipments will be conducted in accordance with:

- 1. DOE Order 1540.2, "Hazardous Material Packaging for Transport-Administrative Procedures."
- 2. DOE-RL Order 5480.1, Change 1, Chapter III, "Safety Requirements for the Packaging of Fissile and Other Radioactive Materials."
- DOE Order 5480.3, "Safety Requirements for the Packaging and Transportation of Hazardous Materials, Hazardous Substances and Hazardous Waste."
- 4. DOE Order 5630.1, "Control and Accountability of Nuclear Materials."
- 5. DOE Order 5632.4, "Physical Protection of Security Interests."
- 6. DOE Order 5700.6B, "Quality Assurance."
- 7. Code of Federal Regulations, "Energy," 10 CFR, Applicable Parts 0 to 199, current edition. Part 71 "Packaging and Transportation of Radioactive Material."
- Code of Federal Regulations, Protection of Environment 40 CFR, Applicable Parts, current edition.

HAZARDOUS MATERIAL PACKAGING AND SHIPPING	Manual Section Page	WHC-CM-2-14 Part I, REV 0
INTRODUCTION	Effective Date	July 15, 1988

- 9. Code of Federal Regulations, "Transportation," 49 CFR, Applicable Parts 0 to 199, current edition.
- Washington State Department of Ecology. Washington Administrative Code, Chapter 173-303WAC Dangerous Waste Regulations, current revision.
- 11. IATA "Dangerous Goods Regulations," International Air Transport Association, Montreal, Canada, current edition.
- 12. IAEA Safety Standards, "Regulations for the Safe Transport of Radioactive Materials," Rev. ed., Safety Series No. 6, International Atomic Energy Agency, Vienna, Austria, 1967 and 1973, and later editions as adopted.
- 13. DOC 9284-AN/905, "Technical Instructions for the Safe Transport of Dangerous Goods by Air." International Civil Aviation Organization, current edition.
- 14. MLM-3245 (DOE/DP/0053-H1) "DOE Evaluation Document for DOT 7A Type A Packaging" Edling, D.A. et al. March 1987.
- 15. WHC-CM-1-3 <u>Management Requirements and Procedures</u>, MRP 5.20, "Hazardous Material Packaging and Shipping."
- 16. WHC-CM-1-3 <u>Management Requirements and Procedures</u>, MRP 5.27, "Movement of Radioactive Material."
- 17. WHC-CM-4-2, Quality Assurance.

[17]

0

प्ुः

P.

- 18. WHC-CM-4-10, Radiation Protection.
- 19. WHC-CM-4-29, Nuclear Criticality Safety.
- 20. WHC-CM-4-34, Nuclear Material Control and Accountability.
- 21. WHC-CM-5-16, <u>Nonradioactive Dangerous Waste Packaging and Disposal</u>
 <u>Requirements</u>.
- 22. WHC-CM-7-5, Environmental Compliance, current revision.
- 23. WHC-EP-00063, Radioactive Solid Waste Packaging, Storage and Disposal Requirements.

WESTINGHOUSE HANFORD COMPANY

Manual Section WHC-CM-2-14 Part II, REV 1

Page Effective Date

1 of 17 March 20, 1989

HAZARDOUS MATERIAL PACKAGING AND SHIPPING

Organization

Procurement and Materials Management

TITLE:

C^

٠, ٢

(2)

κ,

("")

r - 1

Approved by

RESPONSIBILITIES AND PROCEDURES FOR ALL HAZARDOUS MATERIAL SHIPMENTS

D. K. Quigley, Manager Procurement and Materials Mgmt

1.0 RESPONSIBILITIES

Westinghouse Hanford Company (WHC) has the responsibility to develop and maintain a comprehensive program for the packaging and transport of all hazardous materials that complies with the minimum requirements identified in Department of Energy (DOE) Order 5480.3 and Department of Energy-Richland (DOE-RL) Order 5480.1, Change I supplement, and their referenced documents. Westinghouse Hanford Company will ensure that hazardous materials are prepared, packaged and transported in a safe manner that will not present a hazard to the health and safety of plant personnel or to the public. Onsite packaging and shipping shall be conducted in accordance with the Department of Transportation (DOT) regulations or, if not technically or economically practicable, provide an equivalent degree of safety. Departure from the DOT regulations shall be documented in a Safety Analysis Report for Packaging (SARP) approved by the WHC Approval Authority and DOE-RL, when appropriate.

The group responsibilities defined to carry out the hazardous material packaging and shipping program commitment are shown below and summarized in Figure II-1-1.

1.1 PROCUREMENT AND MATERIALS MANAGEMENT

Procurement and Materials Management (PMM), a Function of Resource Allocation and Management, is assigned overall responsibility for supervising implementation of, and compliance with, WHC-CM-1-1, Management Policies, MP 2.5, "Shipping and Receiving", which includes overall guidance for implementing and maintaining the shipping and receiving program, both onsite and offsite, through development and maintenance of implementing procedures and manuals.

1.1.1 Traffic

- 1. Provides overall management responsibility of inbound and outbound offsite shipments of hazardous materials.
- 2. Responds to DOE-RL inquiries concerning the overall packaging and shipping program.
- 3. Obtains formal interpretation of transportation regulations from the appropriate Federal agencies through DOE-RL.

117

O

¥.j.

(

RESPONSIBILITIES AND PROCEDURES FOR ALL HAZARDOUS MATERIAL SHIPMENTS




Figure II-1-1. Hazardous Material Packaging, Shipping and Transportation Interfaces and Internal Responsibilities.

O

*

(")

7. ".

(^)

. .

March 20, 1989

- 4. Verifies compliance with Federal regulations, DOE Orders, and company requirements of all inbound and outbound offsite shipments of hazardous materials for the Hanford Site. Traffic is the only authorized shipper for all offsite hazardous material shipments.
- 5. Performs a pre-release inspection of each outbound shipment including a review of the shipping records for compliance with DOE and other Federal regulations, requirements, and directives relative to the classification, description, packaging, marking, labeling, and tiedown of containers and certifying to the carrier that such containers leaving the Hanford Site are in proper condition for transport.
- 6. Maintains a working file of Certificates of Compliance (COCs) and Safety Analysis Reports for Packaging (SARPs) for radioactive material Containers used by Hanford contractors. Reviews the COC and SARP applicable to each container packaged for offsite shipment for quantity and type of material authorized and the certificate expiration date.
- 7. Provides temporary storage in the 1100 Area for certain inbound and outbound offsite shipments.
- 8. Reviews Hanford Site intra and interarea radioactive shipment records to ensure compliance with applicable regulations.
- 9. Prepares formal training courses, and provides instruction to qualify personnel in the proper procedures for authorizing/certifying hazardous material shipments in accordance with DOT, DOE, United States Environmental Protection Agency (EPA), and Washington State regulations.
- 10. Prepares and maintains the Hazardous Material Packaging and Shipping Manual.
- 11. Prepares and revises MRP 5.20, "Packaging and Transportation of Hazardous Materials" as required.
- 12. Provides operational overview of onsite shipping activities. This includes providing area representatives to assist onsite facilities in meeting shipping requirements. The area representative will assist in package selection and procurement, job planning, on the job training, shipment documentation and other related tasks. The area representative will perform reviews of shipping operations and make recommendations for improvements to facility management.

NOTE: In performance of the PMM shipping and receiving duties for Westinghouse and other Hanford Contractors, Traffic works closely with Materials Management to assure smooth operation. The Materials Management responsibilities in performing its part are defined in

RESPONSIBILITIES AND PROCEDURES FOR ALL HAZARDOUS MATERIAL SHIPMENTS

March 20, 1989

the <u>Materials Management Manual</u>, WHC-CM-2-2 and will not be repeated here. However, because of the various shipping and receiving activities, disbursement of hazardous materials plantwide and the close involvement with Traffic, the interactions between Materials Management and Traffic are detailed in Part V of this manual.

1.2 OPERATING ORGANIZATIONS

The Operating organizations include any group that uses, processes, generates or transports hazardous materials. They are responsible to do the following:

- 1. Manage onsite WHC shipments of hazardous material originating at the operating facilities, and make shipments in compliance with requirements and procedures established in this manual.
- 2. Coordinate with Traffic, all planned inbound and outbound offsite shipments of hazardous materials, including radioactive materials.
- Prepare written operating procedures incorporating SARP requirements to be used for the packaging, loading, transportation and unloading of hazardous materials.
- 4. Package, load, transport and unload hazardous materials in approved packagings, as specified by approved procedures and instructions.
- 5. Transport repetitive onsite shipments incidental to production, such as samples and waste, on vehicles assigned to the operating organizations.
- 6. Request preparation of SARPs.
- 7. Ensure only appropriately trained and qualified personnel are used to inspect, load, monitor, certify, authorize or transport hazardous material packages.
- 8. Inspect, visually, the vehicle used to transport hazardous material for obvious defects and the vehicle inspection tags to assure the Class A/B preventative maintenance is current.

1.3 SAFETY

- 1. Provides radiation monitoring support for all WHC hazardous material packaging and transportation activities.
- 2. Ensure ALARA practices are utilized in the packaging and shipment of radioactive material.

RESPONSIBILITIES AND PROCEDURES FOR ALL HAZARDOUS MATERIAL SHIPMENTS

March 20, 1989

- 3. Provides radiological and criticality analysis when required for the preparation of SARPs.
- 4. Reviews and approves Nuclear Criticality Specifications, when required.
- 5. Performs an annual appraisal of WHC hazardous materials packaging and transportation operations.
- 6. Reviews and approves applicable WHC documents relating to the packaging and shipment of hazardous materials.
- 7. Maintains surveillance of packaging and transportation operations to ensure adherence to the technical and safety aspects of the program and provide verification where applicable.

1.4 PACKAGING AND REMOTE SYSTEMS

(---

O

4.7

()

-

C

- 1. Coordinates and approves all WHC applications for, or amendments to, DOE/U.S. Nuclear Regulatory Commission (NRC) Certificates of Compliance (COC).
- 2. Prepares and/or evaluates SARP related analyses to assure conformance to applicable regulations, codes, or standards.
- 3. Assures that all WHC hazardous material packaging systems are designed, developed, tested, approved, and certified in compliance with DOE Orders.

1.4.1 Packaging Development

- 1. Prepares SARPs for containers used for onsite shipment of radioactive materials.
- 2. Prepares technical evaluation documentation in accordance with DOE Order 1540.2 for hazardous material packagings including tiedown, content analysis, and DOT certification.
- 3. Conducts qualification testing of hazardous material packagings to conform to applicable codes, standards, and regulations.
- 4. Reviews and approves written facility procedures covering onsite radioactive material packaging and transportation activity to assure that all relevant administrative controls related to SARPs, COCs, DOT Exemptions, and Federal/State packaging requirements are properly incorporated.
- 5. Prepares design criteria and specifications for onsite radioactive material packagings.

RESPONSIBILITIES AND PROCEDURES FOR ALL HAZARDOUS MATERIAL SHIPMENTS

Effective Date March 20, 1989

- 6. Obtains formal interpretations of package design and test criteria from the appropriate Federal agencies through DOE-RL.
- 7. Responds to inquiries from DOE-RL concerning all package design, testing, evaluation or approval activities.
- 8. Prepares and maintains the Radioactive Material Shipping Container Directory.

1.5 SAFEGUARDS AND SECURITY

1:

(,)

7.74

- 1. Establishes security requirements for onsite shipments of radioactive material including special nuclear material (SNM) shipments in accordance with MRP 5.27, "Movement of Radioactive Material".
- 2. Establishes requirements for nuclear material accountability procedures.

1.6 PACKAGING AND SHIPPING SUBCOUNCIL (PSSC)

The PSSC of The Safety and Environmental Advisory Council is chartered in WHC-CM-1-2, Organization Charts and Charters, CH-CC-5.

- Provides multi-disciplined review and support of ongoing nuclear, environmental, safety, and safeguards and security matters associated with packaging and shipping activities involving radioactive, hazardous, extremely hazardous and dangerous materials.
- 2. Provides review for:
 - a. All SARP's.
 - b. Significant changes to administrative controls and modifications to containers or casks.
 - c. Periodic updates of onsite Hazardous Material Packaging and Shipping Manual.
- 3. Recommends approval of reviewed documentation and designs to the WHC Approval Authority.

1.7 APPROVAL AUTHORITY

The Manager, Safety approves certain actions of the PSSC based on its recommendations.

Manual Section Page WHC-CM-2-14 Part FI, REV 1 7 of 17

RESPONSIBILITIES AND PROCEDURES FOR ALL HAZARDOUS MATERIAL SHIPMENTS

Effective Date

March 20, 1989

1.8 QUALITY ASSURANCE

- 1. Assists in the development, implementation, and maintenance of a Quality Assurance Program for the packaging and transportation of hazardous material which addresses the fabrication, testing, assembly, maintenance, repair and use (including reuse) of approved packagings.
- 2. Reviews and approves WHC Impact Level 1, 2, and 3 shipping container procurement documentation to ensure compliance with applicable WHC and DOE requirements.
- Reviews and approves WHC Impact Level 1, 2, and 3 plans, facility procedures, SARPs, drawings, and specifications related to hazardous material packaging and transportation.
- 4. Inspects shipping containers procured from outside sources, and those fabricated onsite, including the verification of container qualification tests.
- 5. Inspects reusable containers for integrity verification, as required by SARPs.
- 6. Conducts periodic audits and surveillances to assess program compliance with applicable codes, standards and requirements.

1.9 PROCUREMENT

C,

Curr

1.12

- 1. Procures shipping containers requested by WHC operations organizations from approved suppliers.
- Reviews all procurement requests for shipping containers.

1.10 TECHNICAL TRAINING

1. Provides guidance and assistance in developing training and qualification programs for organizations involved in packaging and transportation of hazardous materials.

1.11 DEFENSE WASTE MANAGEMENT

- 1. Maintains liaison with non-WHC originators of radioactive waste material shipments and coordinates approvals required to package and transport these materials to WHC for waste burial, interim storage, analysis, or processing.
- 2. Prepares and maintains manuals that describe packaging requirements for storage and disposal of hazardous waste. (See: WHC-EP-000-63 and WHC-CM-5-16).

Effective Date

RESPONSIBILITIES AND PROCEDURES FOR ALL HAZARDOUS MATERIAL SHIPMENTS

March 20, 1989

1.12 SITE SERVICES

- 1. Transports hazardous materials shipments, using dedicated or special equipment, in accordance with applicable regulations.
- 2. Provides qualified vehicle operators who are familiar with their vehicles, tiedown procedures and transportation requirements.
- Provides well maintained vehicles for transport of hazardous materials that are safe and have current Class A/B preventative maintenance inspections.

2.0 PROCEDURES

LO

(")

()

2.1 DELEGATION, TRAINING AND APPROVALS OF SHIPPERS

Authorized shippers are employees delegated by their respective managers to receive appropriate training and assume the responsibility of shipping hazardous materials. Exempt employees with a documented need may become authorized shippers. Nonexempt non-bargaining unit employees with a documented need and the approval of their Level III manager may become authorized shippers.

The responsible Level IV manager may initiate the delegation of an employee as an authorized shipper by submitting a Request for Authority form (BC-9600-169, Figure II-2-1, obtained from Traffic) with approval from Safeguards, Security and Traffic and, in the case of a nonexempt employee, the Level III approval.

On review and approval by Traffic, the prospective shipper is scheduled into the Hazardous Materials Training Course conducted by Traffic. On successful completion of this training, Traffic enters the person's name, payroll number and authorization on a list of approved shippers.

As a minimum, the training for authorized shippers consists of eight hours of formalized instruction in Traffic's "Certification of Hazardous Material Shipments" course, plus a take home exam. Additionally, it is the responsibility of the line manager to assure that the authorized shipper is provided the necessary supplemental training geared to the specific shipping concerns of their facility.

In order to maintain the certification, the shipper should be actively involved in the shipping of hazardous materials. The shipper is required to make at least one onsite radioactive shipment within a six month time period or retake the "Certification of Hazardous Material Shipments" training course examination; otherwise, the shipper's name will be removed from the list of authorized shippers.

€".

En Ci

 \bigcirc

Manual Section Page Effective Date WHC-CM-2-14 Part II, REV 1 9 of 17

RESPONSIBILITIES AND PROCEDURES FOR ALL HAZARDOUS MATERIAL SHIPMENTS

March 20, 1989

Training requirements for signature authority are as follows:

- o Those who sign Radioactive Shipment Records (RSRs), offsite radioactive shipment records (ORSRs) and Hazardous Material Shipping Records (HMSRs) must complete the "Certification of Hazardous Material Shipments" course. Required every twenty four months.
- o Those who sign the Uniform Manifest must complete the "Hazardous Waste Shipment Certification" course. Required annually.
- o Nuclear material custodians who sign RSRs or ORSRs for Special Nuclear Material (SNM) shipments must also complete the "Nuclear Material Custodian Training" course. Required annually.
- o For course outlines, see Appendix A.

()

C)

Manual Section Page Effective Date WHC-CM-2-14 Part II, REV 1 10 of 17 March 20, 1989

RESPONSIBILITIES AND PROCEDURES FOR ALL HAZARDOUS MATERIAL SHIPMENTS

	Westinghouse Hanford Company	•	REQUEST FOR AUTHORITY (TO SHIP HAZARDOUS MATERIALS/WASTES)					
	Name (Print)	Payroll No.	Organization	Org. Code	Work Location			
	TO: @ Security 3790/300 AREA	② Safeguards	Safeguards 2704Z/200 WEST					
	三 Shipment Records, Hazara	responsibilities for which auth dous Material Shipment Record aining listed in Section D. for each employee.	ority is sought and justif Is and Uniform Hazardo	y each request. Auth us Waste Manifests c	ority to sign Radioactive ontingent upon successful			
		N-NUCLEAR RADIDACTIVE AND						
	Authority is requested for cand Westinghouse Hanford Compar	idate, on qualification, to sign a ny.	is shipper or waste gene	rator the following d	ocuments on behalf of			
	□ o₁	nsite Radioactive Shipment Rec	ords (RSR's)					
		ffsite Radioactive Shipment Red	cords (ORSR's)		•			
		izardous Material Shipment Re						
	Ur	niform Hazardous Waste Manif	ests (uniform manifests)					
	SECTION B:	*****	ERIAL AUTHORIZATION		_			
	Authority is requested for cand DOE contractors onsite or offsit	e as indicated below:	as shipper, source data f	orms and RSR's to tra	insfer nuclear materials to			
		nsite						
		ffsite nuclear materials, special nucle 2 "Control and Accountability	er materials, accountabl of Nuclear Materials."	e nuclear materials a	nd other materials			
si i	SECTION C:	1100 AREA RECI	IVING PERSONNEL ONL	<u>Y</u>				
	Candidate is a member of Recei	iving. Authority is requested, o	n qualification, to receiv	_	al including nuclear			
**** S1 1	Candidate is a member of Rece material from transport carrier		n qualification, to receiv lite.	_	al including nuclear			
31 1	Candidate is a member of Rece material from transport carrier	iving. Authority is requested, o s and forward the shipment on	n qualification, to receiv site. d non-nuclear).	e radioactive materi	al including nuclear			
,, <u></u>	Candidate is a member of Rece material from transport carrier	iving. Authority is requested, o is and forward the shipment on: gn onsite RSR's only (nuclear an RAINING REQUIREMENTS FOR D MATERIAL SHIPMENTS"	n qualification, to receiv site. d non-nuclear).	e radioactive materi				
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Candidate is a member of Recematerial from transport carrier Si SECTION D *CERTIFICATION OF HAZARDOUS	iving. Authority is requested, os and forward the shipment one gn onsite RSR's only (nuclear an RAINING REQUIREMENTS FOR EMATERIAL SHIPMENTS" ORSR's, and HMSR's CERTIFICATION"	n qualification, to receiv site. d non-nuclear).	e radioactive materi Training V	erification			
	Candidate is a member of Recematerial from transport carrier Signature of Recematerial from transport carrier Signature of Signature	iving. Authority is requested, of and forward the shipment one gn onsite RSR's only (nuclear and RAINING REQUIREMENTS FOR EMATERIAL SHIPMENTS" ORSR's, and HMSR's CERTIFICATION" I'M Manifests I TRAINING" (Required for SEC	n qualification, to recent ite. d non-nuclear). DELEGATION TION B Only)	e radioactive materi Training V Date	Perification			
	SECTION D "CERTIFICATION OF HAZARDOUS Required for those who sign RSR's, "HAZARDOUS WASTE SHIPMENT (REQUIRED for those who sign Unifo	iving. Authority is requested, os and forward the shipment one gn onsite RSR's only (nuclear an RAINING REQUIREMENTS FOR D MATERIAL SHIPMENTS" ORSR's, and HMSR's CERTIFICATION" ITM Manifests I TRAINING" (Required for SEC ISR's or ORSR's to ship nuclear if	n qualification, to recent ite. d non-nuclear). DELEGATION TION B Only)	Training V	Perification Initials Initials			
	SECTION D "CERTIFICATION OF HAZARDOUS Required for those who sign RSR's, "HAZARDOUS WASTE SHIPMENT (REQUIRED for those who sign Unifo	iving. Authority is requested, os and forward the shipment one gn onsite RSR's only (nuclear an RAINING REQUIREMENTS FOR EMATERIAL, SHIPMENTS" ORSR's, and HMSR's CERTIFICATION" IT MANIFESTS I TRAINING" (Required for SEC ISR's or ORSR's to ship nuclear in the state of the second sec	n qualification, to recentite. d non-nuclear). DELEGATION TION B Only) naterials	Training V Date Date Date	Perification Initials Initials			
	SECTION D "CERTIFICATION OF HAZARDOUS Required for those who sign RSR's, "HAZARDOUS WASTE SHIPMENT (REQUIRED for those who sign Unifo	iving. Authority is requested, os and forward the shipment one gn onsite RSR's only (nuclear an RAINING REQUIREMENTS FOR EMATERIAL, SHIPMENTS" ORSR's, and HMSR's CERTIFICATION" IT MANIFESTS I TRAINING" (Required for SEC ISR's or ORSR's to ship nuclear in the state of the second sec	n qualification, to recent the. d non-nuclear). DELEGATION TION B Only) naterials	Training V Date Date Date	lerification Initials Initials			
N 1	SECTION D "CERTIFICATION OF HAZARDOUS Required for those who sign RSR's, "HAZARDOUS WASTE SHIPMENT (REQUIRED for those who sign Unifo	iving. Authority is requested, os and forward the shipment one gn onsite RSR's only (nuclear an RAINING REQUIREMENTS FOR EMATERIAL, SHIPMENTS" ORSR's, and HMSR's CERTIFICATION" IT MANIFESTS I TRAINING" (Required for SEC ISR's or ORSR's to ship nuclear in the state of the second sec	n qualification, to recent the. d non-nuclear). DELEGATION TION B Only) naterials	Training V Date Date Date	Perification Initials Initials			
	SECTION D "CERTIFICATION OF HAZARDOUS Required for those who sign RSR's, "HAZARDOUS WASTE SHIPMENT (REQUIRED for those who sign Unifo	iving. Authority is requested, os and forward the shipment one gn onsite RSR's only (nuclear an RAINING REQUIREMENTS FOR EMATERIAL, SHIPMENTS" ORSR's, and HMSR's CERTIFICATION" IT MANIFESTS I TRAINING" (Required for SEC ISR's or ORSR's to ship nuclear in the state of the second sec	n qualification, to recent the. d non-nuclear). DELEGATION TION B Only) naterials	Training V Date Date Date	lerification Initials Initials			
	SECTION D "CERTIFICATION OF HAZARDOUS Required for those who sign RSR's, "HAZARDOUS WASTE SHIPMENT (REQUIRED for those who sign Unifo	iving. Authority is requested, os and forward the shipment one gn onsite RSR's only (nuclear an RAINING REQUIREMENTS FOR EMATERIAL, SHIPMENTS" ORSR's, and HMSR's CERTIFICATION" IT MANIFESTS I TRAINING" (Required for SEC ISR's or ORSR's to ship nuclear in the state of the second sec	n qualification, to recent the. d non-nuclear). DELEGATION TION B Only) naterials	Training V Date Date Date	lerification Initials Initials			
	SECTION D "CERTIFICATION OF HAZARDOUS Required for those who sign RSR's, "HAZARDOUS WASTE SHIPMENT (REQUIRED for those who sign Unifo	iving. Authority is requested, os and forward the shipment one gn onsite RSR's only (nuclear an RAINING REQUIREMENTS FOR EMATERIAL, SHIPMENTS" ORSR's, and HMSR's CERTIFICATION" IT MANIFESTS I TRAINING" (Required for SEC ISR's or ORSR's to ship nuclear in the state of the second sec	n qualification, to recent the. d non-nuclear). DELEGATION TION B Only) naterials	Training V Date Date Date	Perification Initials Initials			
	SECTION D "CERTIFICATION OF HAZARDOUS Required for those who sign RSR's, "HAZARDOUS WASTE SHIPMENT (REQUIRED for those who sign Unifo	iving. Authority is requested, os and forward the shipment one gn onsite RSR's only (nuclear an RAINING REQUIREMENTS FOR E MATERIAL SHIPMENTS" ORSR's, and HMSR's CERTIFICATION" I'M Manifests I TRAINING" (Required for SEC STR's or ORSR's to ship nuclear r (Include reason v	n qualification, to recent the. d non-nuclear). DELEGATION TION B Only) naterials	Training V Date Date Date	Perification Initials Initials			
N. 1	SECTION D "CERTIFICATION OF HAZARDOUS Required for those who sign RSR's, "HAZARDOUS WASTE SHIPMENT (REQUIRED for those who sign Unifo	iving. Authority is requested, os and forward the shipment one gn onsite RSR's only (nuclear an RAINING REQUIREMENTS FOR E MATERIAL SHIPMENTS" ORSR's, and HMSR's CERTIFICATION" I'M Manifests I TRAINING" (Required for SEC STR's or ORSR's to ship nuclear r (Include reason v	n qualification, to recentite. d non-nuclear). DELEGATION TION B Only) naterials STIFICATION why authority is required.	Training V Oate Date Date	lerification Initials Initials			
	Candidate is a member of Recematerial from transport carrier SI SECTION D TI "CERTIFICATION OF HAZARDOUS Required for those who sign RSR's, "HAZARDOUS WASTE SHIPMENT (Required for those who sign Unifor NUCLEAR MATERIAL CUSTODIAN Required for custodians who sign F	iving. Authority is requested, os and forward the shipment one gn onsite RSR's only (nuclear an RAINING REQUIREMENTS FOR E MATERIAL SHIPMENTS" ORSR's, and HMSR's CERTIFICATION" I'M Manifests I TRAINING" (Required for SEC STR's or ORSR's to ship nuclear r (Include reason v	n qualification, to recent the. d non-nuclear). DELEGATION TION B Only) naterials STIFICATION why authority is required.	Training to Date Date Date Date 1100 Area	Perification Initials Initials			

BC-9600-169 (12-87)

Manual Section Page WHC-CM-2-14 Part II, REV 1 11 of 17

RESPONSIBILITIES AND PROCEDURES FOR ALL HAZARDOUS MATERIAL SHIPMENTS

Effective Date

March 20, 1989

2.2 RECEIVERS OF HAZARDOUS MATERIAL SHIPMENTS

Receivers of accountable nuclear material must be designated Material Balance Area/Item Control Area (MBA/ICA) custodians or alternates.

For other radioactive material and hazardous material shipments a receiver may be anyone knowledgeable in the receiving group or a designate. The receiver does not have to be an authorized shipper.

Upon receipt of Type B, Fissile or Highway Route Controlled Quantities (HRCQ) radioactive material shipments, the receiver shall notify the sender and sign the receiving papers or the Onsite Radioactive Shipment Record indicating abnormalities, if any. Delay in receipt beyond a reasonable time shall be cause for prompt search for the shipment.

2.3 NONCOMPLIANCE PROCEDURES AND VARIANCE REPORTS

Offsite and onsite RSRs are monitored as needed by Traffic for discrepancies. This enables Traffic to evaluate the effectiveness of the training and the strength of the shipping program.

2.3.1 Offsite Shipment

·, ·, ·

131

 \bigcirc

Outbound hazardous material shipments, particularly radioactive shipments, are inspected along with their associated shipping documents (e.g., ORSRs) by Traffic before being released to carriers for offsite transport.

If regulatory violations or errors are noted during this inspection, the shipment is held until all deficiencies are corrected.

Minor errors are corrected by Traffic after discussions with the initiating shipper. Subsequently, the shipment is released to the carrier. These errors are documented internally by Traffic.

If more serious violations are observed, the shipper will be contacted to correct the deficiencies. A determination will be made as to whether corrections can be made at Traffic, or whether the shipment must be returned to the shipper's facility for corrective action. All deficiencies must be corrected to the satisfaction of all parties involved before release can be made to the offsite carrier. Violations of this nature are documented internally by Traffic. If such discrepancies persist, a Variance Report (Figure II-2-2) is issued to the shipper with recommendations for resolution. A copy of the Variance Report, along with corrections to the problem are sent to DOE-RL Projects Management Division. Serious violations will be documented on an Event Fact Sheet or Unusual Occurrence Report.

10

111

 \bigcirc **5**. ".

 \bigcirc

RESPONSIBILITIES AND PROCEDURES FOR ALL HAZARDOUS MATERIAL SHIPMENTS

Manua l Section Page Effective Date

WHC-CM-2-14 Part II, REV 1 12 of 17 March 20, 1989

HAZARDOUS N	IATERIAL SHIPMENT REGULATIONS VA	RIANCE REPORT
ontractor Originating Shipment	Contractors Shipping Representative	Report Number

Contractor Originating Shipment Contr	actors Shipping Representative	Report Number					
Subject Shipment: Shipment Date:	ORSR	RSR No.:					
Variance Report Originated By:	, Traffic	Date Initiated					
The following variance(s) has/have been noted in a review of s	the Subject Shipment:						
Items							
 Security Classification, SNM Classification, Escort Requirements 	Packaging Description						
ldentification of Shipper, Receiver, Carrier	Container Approval Docu	mentation					
Description of Radioactive Contents	-	Container Labeling/Vehicle Placarding					
Curies/Cont and/or Total Curies/Shipment	☐ Tie Down Requirements						
Grams Fissile Mat/Cont and/or Total Fissile Mat/St		Radiation Survey Data Instructions to Carrier/Receiver's Signature					
Physical/Chemical Form Normal/Special Form		Instructions to Carrier/Receiver's Signature Certification/Shipment Approval Signature					
Quantity Category/Shipping Category	Other	•••••					
	*	· y					
Yes No Response to DOE-RL	Required	Occurrence Report Required Yes					
Response due by		i □ No					
	Date	□ NA					
Observations/Recommendations							
1.							
2 .		<u></u>					
3.							
4,							
PLEASE SUBMIT LETTER INDICATI	ING CORRECTIVE ACTION TAKEN TO PREVENT REC	URRENCE.					
	ING CORRECTIVE ACTION TAKEN TO PREVENT REC						
Distribution:	For Westinghouse shipments addit	ional copies to the following:					
<u>Distribution:</u> 1 Contractor's Shipping Representative	····	ional copies to the following:					
Distribution:	For Westinghouse shipments addit	ional copies to the following:					

BC-9600-165 (12-87)

Figure II-2-2. Hazardous Material Shipment Regulations Variance Report.

Manual Section Page WHC-CM-2-14 Part II, REV 1 13 of 17

RESPONSIBILITIES AND PROCEDURES FOR ALL HAZARDOUS MATERIAL SHIPMENTS

Effective Date

March 20, 1989

2.3.2 Onsite Shipment

Traffic conducts an Onsite Radioactive Shipment Record Review Program. This program requires Traffic Area Representatives to review Hanford onsite RSRs and document errors or omissions observed to evaluate trends and revise training as needed. More serious violations are documented in a Variance Report (Figure II-2-2) to the shipper with recommendations for resolution. Copies of the Variance Report and the final resolution are sent to DOE-RL Projects Management Division. Serious violations will be documented on an Event Fact Sheet or Unusual Occurrence Report.

2.4 PACKAGING PROCEDURES

. .

LO

.

-

general, is

Age John

The DOE-RL Order 5480.1, Change 1, Chapter III requires written procedures for packaging, loading, transportation and unloading be prepared for all shipments of fissile, Type B and HRCQ of radioactive material by the operating groups. Traffic recommends similar procedures be prepared for limited and Type A quantities also. These procedures should identify user responsibilities to ensure the container is used in accordance with the applicable federal shipping regulations, the container SARP, and the administrative controls for onsite and offsite shipments, as applicable. The procedures should be detailed to the extent to define individual steps involved and serve as a basis for a checklist of the main steps to ensure procedural compliance. These procedures should be reviewed and approved by Packaging Development and QA as appropriate.

2.5 TIEDOWN PROCEDURES

The DOT (49 CFR 177.834(a)) requires any container, not permanently attached to a motor vehicle, containing flammable liquid, compressed gas, corrosive material, poisonous material, or radioactive material must be secured against movement within the vehicle under conditions normally incident to transportation.

2.6 RADIOACTIVE SHIPMENT CHECKLIST

All onsite and offsite radioactive materials shipments of fissile, Type A and above quantities shall be documented on a Radioactive Shipment Checklist (Figure II-2-3) to show the shipment and the RSR or ORSR are properly completed.

Routine shipments documented with Onsite Routine RSRs (ORRSRs) are exempt from this requirement.

A group may develop its own shipment checklist, if preferred. However, it must embody all the items on Figure II-2-3 and be reviewed by Traffic prior to use.

0

Manual Section Page Effective Date

WHC-CM-2-14 Part II, REV I 14 of 17 March 20, 1989

RESPONSIBILITIES AND PROCEDURES FOR ALL HAZARDOUS MATERIAL SHIPMENTS

	Westinghouse Hanford Company				Inspection Date				NM Representative Oper. Org. Representative OHP Representative				
Shipment For	_					imber of Containers Type of Co Shipment		Initials	Certificate of Compliance				
Offsite 🔲			Procedure No dentified Address Label Each Cont. Yes Yes			Total		DOT Spec. or Describe		Date Cert, Expires SARP ID No.			
Each Cont. Yes						tAM Label Affixed lach Cont. Yes N/A	Secondary Hazard Label Each Cont. Yes \[\] N/A \[\]		If Type A or 8 Cont. – Marked Each Cont. Yes \[\] N/A \[\]		Cont.		
EXTERIOR Rust or excessive of Penetrations or letter of Gaskets satisfactor Safety devices satisfactor Closure lid or cap Lock bolts or rings Container identific Overall construction Q.A. Inspection ou Shoring if required Container and container and container and container Container and container and container Container container Contai	hipped pa akage evic ry and in p sfactory a cositioned positione cation labo on satisfac rrent or co d in place a	ient				RUST OF EXCESSIVE OF PENETRATIONS OF LE PACKING, SHIERING CLOSURE II OF CAP OVERALL INTERFECTION OF THE PACKING	chipped pa akage evice other safe positioned instruction re approve y, auth by itents survierly identif	int evident ident sty devices in p and secured satisfactory id and not buig SARP or cert, of eyed	lace ged of Comp	000000	00000		
DOCUME! Loading / Unloadi Shipping / Receivi Material transfer i	ng diagran ng report p	repared / Inclu	cluded			DOT-7A Type A – MLM-3245 for reti Container tied dot Patrol Vehicle Sea SNM shipments	ention and wn by proc rch for Cat	dose rate	*****		No N/A		
Radionuclides ar Total grams fissi Transport index Shipper/Receive Irradiated or noi Other hazardou Fissile class III lim	nd activitie le in shipm identified r correctly nirradiated s constitue iltations id	s for each cont ent identified on RSR and ea identified (see diradioactive m ints identified on RS	tainer and to on RSR ch container note) on RSR naterial ident on RSR R and each co	tal shipr label Rand ad tified on ontainer	dress lak RSR	ntified on RSR and consider of each container	ntainers as	appropriate	**	<u>*</u> 000000000	**00000000		
Shipment Autho	rized	☐ Yes	□ No	If Re	jected Ei	opłain							
Date Shipped _,			arized Shippi ify receiver c		ent dep	arture and expected ti	me or date	of arrival.					

Manual Section Page Effective Date WHC-CM-2-14 Part II, REV 1 15 of 17

RESPONSIBILITIES AND PROCEDURES FOR ALL HAZARDOUS MATERIAL SHIPMENTS

March 20, 1989

2.7 ONSITE PACKAGING SYSTEMS

ē = '>

10

(")

C

-

Onsite packaging systems for shipments of radioactive material are conceived and generated to fulfill a need of a user organization.

The DOE-RL Order 5480.1, Change 1, Chapter III requires a SARP to be made for each Type A, Type B, Fissile or HRCQ onsite container.

Packaging Development is responsible for coordinating onsite container design and the preparation of SARPS. The following procedure describes the process, review, and approval requirements for onsite SARPs prepared by WHC.

- Initiation A new SARP or a revision to an existing SARP can be requested by a user organization based on programmatic or operational requirements. The request is submitted to the Manager, Packaging Development in writing and includes proper justification and support documentation. Packaging Development makes routine revisions as necessary to reflect policy or regulation changes.
- Preparation Packaging Development coordinates the analyses, prepares the SARP, and guides the SARP through the review and approval process, including resolution of review comments and obtaining document approval.
- 3. Control In accordance with WP-1.12, Supporting Documents, a unique document number is issued by Engineering Configuration Management. The document numbering system provides an accessible, auditable, and retrievable method to maintain SARP documentation.
- 4. Review and Approval Cycle Revised and new SARPs require the following review and approvals:
 - o User (usually Chemical Processing, Defense Waste Management, Environmental Defense Reactor, and Advanced Reactor Development Function Manager.
 - o Manager, Radiological Assessment, Packaging and Shipping.
 - o Manager, Packaging Development.
 - o Chairman, PSSC.
 - o Packaging and Shipping Approval Authority Manager, Safety, Quality Assurance, and Security Department.
 - o U.S. Department of Energy-Richland Operations only if the container is to be used for large quantity (Highway Route Controlled Quantity HRCQ) interarea shipment in accordance with DOE Order RL 5480.1, Chapter III.

Effective Date

RESPONSIBILITIES AND PROCEDURES FOR ALL HAZARDOUS MATERIAL SHIPMENTS

March 20, 1989

5. Approvals for Editorial Changes - Inconsequential editorial corrections to the SARP require only the approval of the Manager, Packaging Development.

- 6. Utilization Once the SARP is approved, copies are sent to the affected organizations, including Process Engineering, to incorporate the administrative controls from the SARP into the affected Operating Documents. User organizations must obtain Packaging Development review of all operating procedures which implement SARP administrative controls to ensure that the administrative controls are being implemented in the intended manner.
- 7. A departure from SARP established criteria or other WHC policy or procedure that offers an equivalent degree of safety to DOT or other Federal regulations can be granted as a "deviation" with appropriate internal approval (for onsite inter- and intra-area shipments). A departure from criteria established by DOT or other Federal regulations is termed a "waiver" or "exemption" and must be approved by DOE (for onsite inter-area, HRCQ shipments). Deviations or waivers to the SARP may be obtained in the following manner.
 - o The organization requesting a waiver or deviation provides a written request, including justification to the Manager, Packaging Development.
 - o A letter requesting the waiver or deviation is prepared by Packaging Development for the Packaging and Shipping Approval Authority, and includes the time period the waiver is to be effective and any administrative control changes. Concurring approvals on the letter include User; Radiological Assessment, Packaging and Shipping; and Packaging Development. The Approval Authority's signature is final approval for the deviation or waiver.
 - o If the waiver involves a large quantity (HRCQ), inter-area shipment, a letter requesting the waiver from DOE-RL is prepared for the Approval Authority's signature.
 - o A copy of the deviation or waiver is transmitted to all those on distribution for the SARP.

Onsite containers currently approved for onsite use are cataloged and described in the Onsite Container Directory, maintained by Packaging Development. New containers are added to the directory as they are developed and approved.

Manual Section Page Effective Date WHC-CM-2-14 Part II, REV 1 17 of 17

RESPONSIBILITIES AND PROCEDURES FOR ALL HAZARDOUS MATERIAL SHIPMENTS

March 20, 1989

2.8 OFFSITE PACKAGING SYSTEMS

All offsite radioactive material packages and their use must comply with the applicable DOT/DOE/NRC regulations. Contents shipped must be in accordance with the authorized contents section of either the appropriate DOE/NRC COC for licensed containers or the 49 CFR references for specification containers.

Only a few radioactive material containers are regularly used by WHC, but for other containers for special shipments arrangements may have to be made with the container owners as to availability and use. Radioactive material specification containers are listed in 49 CFR. Containers licensed (those with COCs) by NRC and/or DOE are listed in NUREG-0383 "Directory of Certificates of Compliance for Radioactive Materials Packages" and "Directory of DOE Certificates of Compliance for Radioactive Materials Packaging."

Before WHC may use a COC container, they must apply through the local DOE-RL to be listed as a user of that container. The user must have in his possession a copy of the COC for the package and have the drawings and other documents referenced in the COC relating to the use and maintenance of the packaging.

3.0 REFERENCES

1

 \bigcirc

- DOE Order 5480.3, "Safety Requirements for the Packaging and Transportation of Hazardous Materials, Hazardous Substances, and Hazardous Wastes."
- DOE-RL Order 5480.1, "Environmental Protection, Safety and Health Protection Program for RL" (Chapters III and VI only).
- 3. WHC-CM-1-1, Management Policies, MP 2.5, "Shipping and Receiving."
- 4. WHC-CM-1-2, Organization Charts and Charters, CH-CC-5, "Safety and Environmental Advisory Council."
- 5. WHC-CM-1-3, <u>Management Requirements and Procedures</u>, MRP 5.20, "Packaging and Transportation of Hazardous Materials."
- 6. WHC-CM-2-2, <u>Materials Management Manual</u>.

THIS PAGE INTENTIONALLY LEFT BLANK

WESTINGHOUSE HANFORD COMPANY	Manua1	WHC-CM-2-14	
	Section	Part III, REV O	
•	Page	1 of 12	
	Effective Date	August 1, 1988	
HAZARDOUS MATERIAL PACKAGING	Organization	Procurement and	
AND SHIPPING	Materials Manageme		
TITLE:	Approved by	7 ,	
	1///	lide las	
NONRADIOACTIVE HAZARDOUS MATERIALS/	D. K. Quigley, M	anager	
HAZARDOUS WASTE (HM/HW) SHIPMENTS	Procurement and	Materials Momt	

1.0 INTRODUCTION

The Department of Transportation regulates the interstate transportation of hazardous materials under the Hazardous Materials Transportation Act (HMTA) and implemented in 49 CFR 100 - 199. Washington is an agreement state and requires full compliance with DOT for intrastate transportation. The regulations address all modes of transportation (air, rail, highway, waterway, and pipeline), and establish requirements for shipping papers, proper containers, marking and labeling of containers, placarding of vehicles, and incident reporting. These regulations apply to any material that may pose undue hazard in transportation including all hazardous materials and hazardous wastes.

In the State of Washington, the Washington Department of Ecology (WDOE) regulates hazardous wastes through Chapter 173-303 WAC "Dangerous Waste Regulations" as approved by the US Environmental Protection Agency (EPA). The WDOE further classifies hazardous wastes into dangerous waste (DW) and extremely hazardous waste (EHW) and defines conditions for their evaluation, handling, control and disposal. The WHC manuals WHC-CM-5-16, Nonradioactive Dangerous Waste Packaging and Disposal Requirements, WHC-EP-0063, Hanford Radioactive Solid Waste Packaging, Storage and Disposal Requirements and WHC-CM-7-05 Environmental Compliance give additional information on hazardous wastes. In any event, the packaging, shipping and handling of either hazardous materials or hazardous wastes in Washington are regulated, as applicable, by USDOT, EPA or WDOE, whichever is the most stringent.

1.1 OFFSITE HM/HW SHIPMENTS

For offsite HM/HW shipments, Traffic at the 1100 Area reviews and approves the Hazardous Material Shipment Record (HMSR) or Uniform Hazardous Waste Manifest (UHWM) from the shipper and completes the final shipping papers or bills of lading for transportation offsite. Traffic personnel rely on the shipper to supply complete, accurate and certified information by means of the HMSR or UHWM so that they can complete the shipping papers. To facilitate this flow of information to Traffic, the shipper must be familiar with the <u>Code of Federal Regulations</u>, Title 49, Parts 171-179. All offsite shipments must be in full compliance with both Federal and State Regulations as applicable.

NOTE: Offsite or onsite radioactive material shipments require either an Offsite Radioactive Shipment Record (ORSR), Onsite Radioactive Shipment Record (RSR) or an Onsite Routine Radioactive Shipment Record (ORRSR) as appropriate. Their uses will be discussed in later sections.

Manual Section Page Effective Date WHC-CM-2-14 Part III, REV 0 2 of 12

NONRADIOACTIVE HAZARDOUS MATERIALS/ HAZARDOUS WASTE (HM/HW) SHIPMENTS August 1, 1988

1.2 ONSITE HM/HW SHIPMENTS

C". 1

L()

For onsite shipments of HM/HW the same general procedures apply. The HMSR filled out by the shipper generally serves as the only documentation to accompany the shipment onsite. Onsite shipments of hazardous wastes require the Uniform Hazardous Waste Manifest (UHWM). DOE-RL Order 5480.1, Chapter III, requires that all onsite shipments of HM/HW comply with the DOT regulations, or at least be conducted with an equivalent degree of safety. Deviations from DOT regulations requires DOE-RL approval.

2.0 PROCEDURE FOR MAKING NONRADIOACTIVE HM/HW SHIPMENTS

This section describes in general terms the actions required to prepare hazardous (nonradioactive) material/waste for transport. A schematic illustration of this process is given in Figure III-2-1.

- Define the material to be shipped by chemical, technical or generic name. Determine or define hazardous properties. Determine quantity of material to be shipped (by weight, volume, or otherwise, as appropriate).
- 2. If material to be shipped is currently packaged, determine if packaging meets DOT requirements and is in good condition.
- 3. If material is a waste, determine if it is a hazardous waste per 40 CFR 261 or Washington State Department of Ecology "Dangerous Waste Regulations," WAC 173-303. The Site Hazardous Waste Engineering Support Unit (SHWESU) of Defense Waste Management Division can provide assistance in this area.
- 4. Consult the Hazardous Materials Table (HMT) in 49 CFR 172.101 and its Appendix and Exhibit III-2-1 for the HMT format.
 - a. Determine if material is a reportable quantity of a hazardous substance (49 CFR 172.101, Appendix)
 - b. Determine is material is a Poison Inhalation Hazard (173.3a)
 - c. Establish proper shipping name (Column 2 of HMT).
 - d. Determine hazard class (Column 3 of HMT).
 - e. Determine identification number (Column 3(a) of HMT).
 - f. Determine labeling requirements (Column 4 of HMT).
 - g. Determine if any packaging exceptions apply to the <u>shipment</u> (Column 5(a) of HMT).

Manual Section Page WHC-CM-2-14 Part III, REV 0 3 of 12

NONRADIOACTIVE HAZARDOUS MATERIALS/ HAZARDOUS WASTE (HM/HW) SHIPMENTS Effective Date August 1, 1988

h. Determine specific packaging requirements for the shipment (Column 5(b) of HMT).

i. See quantity and storage restrictions found in Columns 6 and 7 of HMT if shipment is by aircraft, passenger carrying railcar or vessel.

- 5. If material is a hazardous waste, submit a chemical waste disposal request to the SHWESU in accordance with WHC-CM-5-16.
- 6. Title 49 CFR Part 173 contains specific requirements for packaging hazardous materials or wastes identified in the HMT. Examine these requirements closely since they specify specific types of packaging, loading requirements and restrictions, internal packaging, and markings specific to the commodity being shipped.
- 7. Select a container based on the following considerations:
 - a. The applicable determinations of items 1 through 6 above
 - b. Size, shape, weight, and volume of material to be shipped
 - c. Destination, mode of transport, and consignee's ability to handle receipt of the shipment
 - d. Availability of shipping containers.
- 8. If material is still in the original packaging or the waste was previously packaged, verify regulatory compliance to today's current regulations through inspection of the DOT specification markings and labeling on the container for both hazardous material and waste and review of the documentation describing the packaging of the waste. If the packaged material is not in compliance, it will have to be repackaged or overpacked in a Salvage Drum (See 49 CFR 173.3 (c)).
- 9. If material is unpackaged or requires repackaging, obtain an acceptable container and inspect it. A quality assurance/quality control inspection may be required.
- 10. Load the container with authorized contents only, and assemble and seal the package in accordance with appropriate procedures. Packages must be marked and labeled in accordance with the regulations found in 49 CFR 172, Subpart D and E, respectively.
- 11. If shipment is to be made from a regulated (radiation control) area, a radiation survey is required to determine radiation and contamination information and to assure the exterior surfaces are free of contamination.

143

S

~

(_)

44 h

L

Manual Section Page Effective Date WHC-CM-2-14 Part III, REV 0 4 of 12 August 1, 1988




Figure III-2-1. HM/HW Shippers Guide.

P\$88-3147-1

(1)	(2)	(3)	(AE)	(4)	(5)		(6)			(7))
			ldenti-	l aballet	Packaging		Maximum net quantity in one package		Water shipments		
*/ &/ W	Hazardous materials descriptions and proper shipping names	Hazard class	fication	Label(s) required (if not excepted)	(a)	(b)	(a)	(b)	(a)	(b)	(c)
••					Excep- tions	Specific require- ments	Passenger- carrying aircraft or railcar	Cargo only aircraft	Cargo vessel	Pas- senger vessel	Other requirements
	Adhesive	Combustible liquid	UN1133	None .	173.118a	Noise	No limit	No kmit	1,2	1,2	Keep dry. Slow away from
	Adhesive	Flammable liquid	UN1133	Flammable liquid	173.118	173.132	1 quart	10 pounds	•		
	Cement	Combustible liquid	NA1133	None .	173.116a	Nono	No kmit				
	Cement	Flammable liquid	NA1133	Flammable liquid	173.118	173.132	1 quart				
	Chlorobenzol. See Chlorobenzene p-Chlorobenzoyl peroxide	Organic peroxide	UN2113	Organic peroxide	None	173.157 173.158	Forbidden	25 pounds	1	ָן 	
	Chromium oxychloride or Chromyl chloride	Corrosive material	UN1758	Corrosive	None	173.247	Forbidden	1 gallon	1	1	Keep dry. Glass carboys not permitted on passanger vessels.
	Cigar and cigarette lighter fluid. See Lighter fluid					:					
	Cigarette lighter (or other similar ignition device)	Flammable gas	UN1057	Flammable gas	173.21 175.10	173.308	21 ounces	25 pounds	1	1	
	Cigarette lighter (or other similar ignition device)	Flammable Liquid	UN1225	Flammable liquid	173.21 175.10	173.118	Forbidden	Forbiden	1	1	
	Cigarette load	Class C explosive		Explosive C	None	173.111	50 pounds	150 pounds	1,2	1,2	1
	Cyanide or cyanide mixture, dry	Poison B	UN1588	Poison	173.354	173.370	25 pounds	200 pounds	1,2	1,2	Keep dry. Stow away from acids.
i	Oriers, paint or varnish, liquid, n.o.s.	Combustible kouid	UN1168	None	173.118a	None	No limit	No limit	1,2	1,2	
	Driers, paint or varnish, liquid, n.o.s.	Flammable liquid	UN1168	Flammable liquid	173.118 173.128	173.128	1 quart	55 gallons	1,2	1	
	Paint	Combustible liquid	UN1263	None	173.118a	None	No limit	No limit	1,2	1,2	
	Paint	Flammable liquid	UN1263	Flammable liquid	173.118 173.128	173.128	1 quart	55 gallons	1,2	1	
	Paint or paint related material	Corrosive material	NA1760	Corrosive	173.244	173.245	1 quart	1 gallon	1,2	1,2	
	Paint related material	Combustible liquid	NA1263	None	173.118a	None	No l <i>i</i> mit	No limit	1,2	1,2	
	Paint related material	Flammable liquid	NA1263	Flammable liquid	173.118 173.128	173 128	1 quari	55 gallons	1,2	1	

Li

NONRADIOACTIVE HAZARDOUS MATERIALS/ HAZARDOUS WASTE (HM/HW) SHIPMENTS August 1, 1988

- 12. For offsite shipments, schedule shipment in advance with Traffic and Transportation, where appropriate.
- 13. A hazardous material shipment (not hazardous waste) needs a completed Hazardous Material Shipping Record (HMSR) form per instructions found in Section 3.0 that follows. The shipper retains the pink copy and sends the completed HMSR together with other pertinent papers or instructions with the shipment.
- 14. If the material is a hazardous waste, complete a Uniform Hazardous Waste Manifest (UHWM) per instruction found in Section 4.0 that follows. Send completed manifest together with other pertinent papers or instructions with the shipment.
- 15. Furnish appropriate placards (see 49 CFR part 172, Subpart F) to the carrier, or if vehicle is equipped with permanent placards, assure that placards are turned to the proper hazards.
- 16. Assure that riggers or truck drivers are aware of any tiedown requirements to secure load. It is the packager/shipper's responsibility to inspect and approve securing of all loads to assure tiedown requirements are met. Guidelines for tiedowns are found in 49 CFR 177.834(a).
- 17. Assure, prior to loading, the transporting vehicle has no obvious defects and that its Class A/B preventative maintenance inspections are current.

3.0 PREPARING A HAZARDOUS MATERIAL SHIPMENT RECORD

The following instructions are keyed to numbered blocks on the HMSR specimen copy shown in Exhibit III-3-1.

3.1 SHIPMENT DESCRIPTION SECTION COMPLETED BY ORIGINATOR

- 1. Provide the complete address of the consignee, and designate an individual to whom the shipment is being sent.
- 2. Identify originating facility. Originator signs and dates form, checking box indicating originating contractor.
- Check appropriate boxes to indicate mode of transport and method of payment for offsite shipment. Provide complete cost code.
- 4. Describe material to be shipped and its packaging as required by column headings. It is essential that all data be provided for each hazardous material being shipped.

-

117

(1)

 \bigcirc 7.

NONRADIOACTIVE HAZARDOUS MATERIALS/ HAZARDOUS WASTE (HM/HW) SHIPMENTS

Manua 1 Section Page Effective Date

WHC-CM-2-14 Part III, REV 0 7 of 12

August 1, 1988

	SHIP TO:			HAZARDOUS MATERIAL SHIPMENT RECORD (HMSR)					
INST.	Company		7	_ '	Onginating	Facility	Originator Signature		Date
	Address			Building _		(2)			
Ž					Ares		FROM: WHO KEH	PNL	☐ GTHE#
SHIPPING	City, State	, Zip	1		OFFSITE (ONLY:	SHIP: PREPAID 3		
"	Attention:				-	Parcer Post Air (Passen	Air Parcia Poet		(Rail/Truck)
			ONTAINED	/PACKAGI		All trassets	CONTENT		ION
	Number of	Type	DOT Spec	Package	Quantity	Gross Wt	See 49 CFR 172,101(c) Hazar		
	Containers	1700	001300	Dimensions	Pkg	Each Pkg	344 43 0377 772,707427 773=37	COURT (MELLITY)	140.4
							Proper Ship Name:		
							Hazard Class:		
1		(3.1 <u>)s</u>	hipment	Descripti	on <u>Secti</u>	<u>pn</u>	UN/NA No.:		
]		·]	List Secondary Hazards:		
1.						ļ	List Labels Reg'd/Applied		
]	Proper Ship Name:		
S			ĺ	(4)			Hazard Class:		
ÌĔ			1			}	UN/NA Na.:		
CR			İ			l	List Secondary Hazards:		
DESCRIPTION						}	List Labels Reg'd/Applied		
E					,]	Proper Ship Name:		
SHIPMENT			1]	Hazard Class:		!
묾			}			İ	UN/NA No.:		
			1]	List Secondary Hazards:		
]]	List Labels Reg/d/Applied		
	Total No. C	ontainers	Gross Wt of	Shipment	Identify Pla	cards Requi	red: Identify Property C (if applicable)	antrol or Re	turn Order No.:
			(5)		1	3.			
			<u> </u>		2	 4		<u> </u>	<u></u>
	Material	in manufactu	irers original o	onteiner: 🔲	Yes 🔲		ribe Internal Packaging:		_
1			erioration or c	- =	Yes (7)			
			y documented	_	Yes 🔾	/			
			sealed, marke OT requirem	_	Yes	1			
		Survey No.	 -	Date	I AM :	Signature	Print No	VTI-0	
1	DIATION		- 1	(8)					
-					(3.2) CE	RTIFICAT	TION SECTION		
-		Thu	is to certify t	har the above o			rly classified, described,	This ships	nent is within the Limita-
	NTRACTOR	S pack	aged, marked	and labeled and	d are in prop	er condition	for transport according	tions pres	cribed for:
CE	CERTIFICATION to the applicable regulations of the				- Granting	. ur iranspi		Aircraf	ger 🗆 Gargo 🗀 NA ft Aircraft
L		Aush	orizing Signat	ure:(1)		Print Name 2		Date:
		(3.3)FOR (FFSITE SH	IPMENTS	- ADDIT	ONAL APPROVAL REQUIRE	D	
		3 8.L. N	9	Date Shipped	ETA	1	Routing	Special Con	siderations
	WHC	ᇎ	1		1	}	1		
ļ		TRAFFIC	<u>-</u>						
<u></u>		- I w	HC Traffic: _				WHC Shipping:		
							άl	S. GOVERNMEN	44-3000-596 (141-87) T PRINTING OFFICE: 1987 - 581-711

EXHIBIT III-3-1. Specimen Copy of a Hazardous Material Shipment Record (HMSR).

NONRADIOACTIVE HAZARDOUS MATERIALS/ HAZARDOUS WASTE (HM/HW) SHIPMENTS Effective Date August 1, 1988

- 5. Indicate total number of shipping units and gross weight of shipment. Also identify placards required on the vehicle. See 49 CFR 172 Subpart F.
- 6. Identify property control, release to ship or return order numbers, as applicable.
- 7. Answer questions here. Describe internal packaging if any, include type and size of inner containers and quantity of material contained in each.
- 8. Have the Radiation Protection Technologist (RPT) complete the radiation release. Space is available for the survey number, date, and signature of the RPT who is responsible for the survey.

3.2 CERTIFICATION SECTION COMPLETED BY CERTIFIER

- 1. The authorizing signature shall be that of a delegated employee who has successfully completed the "Certification of Hazardous Material Shipments" course. Retraining in this course is required every two years to retain signature authorization.
- 2. For offsite shipments made via aircraft, the appropriate boxes must be checked to indicate prescribed limitations are met.

3.3 OFFSITE SHIPMENT APPROVAL SECTION COMPLETED BY TRAFFIC

1. Traffic assigns a bill of lading number, identifies the date shipped and routing, and approves release of shipment to the carrier.

4.0 PREPARING A UNIFORM HAZARDOUS WASTE MANIFEST (UHWM)

The following instructions are keyed to numbered blocks on a specimen copy of the UHWM form used (Exhibit III-4-1). For additional guidance in preparing this form, contact the Site Hazardous Waste Engineering Support Unit (SHWESU), WHC-CM-5-16 or Traffic.

Approved continuation sheets are available from the SHWESU, if necessary.

Items A through K on the form are not required by Federal regulations. However, states may require generators to complete some or all of the items as part of the state manifest reporting requirements. The SHWESU will notify the generator on a case-by-case basis if any of this data is required, for example Box I requires WDOE Waste Codes (e.g, DOO1, WPO1, etc).

Cr.

M

 \bigcirc

nece la

Manua 1 Section Page Effective Date

WHC-CM-2-14 Part III, REV O

NONRADIOACTIVE HAZARDOUS MATERIALS/ HAZARDOUS WASTE (HM/HW) SHIPMENTS

9 of 12 August 1, 1988

Plea	ee p	nnt or type. (Form designed for use on					Form A	pproved OMB N	lo. 2050-0	039. E	xpires 9	9-30-88
	U	NIFORM HAZARDOUS WASTE MANIFEST	1. Generator's US EPA ID No.		Manifest Do	cument No.	2. Pa		nation in required			
Ш	3.	Generator's Name and Mailing Add	dress			······································	****	te Manifest D	ocument	Numt	er	-
Ш												
\prod		Casamier's Stone (B. Sta	ite Generator	8 ID			
11	_	Generator's Phone () Transporter 1 Company Name	6.	USE	PA ID Numbe	er	C. Sta	te Transporte	r's ID		*****	
П			Ĺ					insporter's Ph				
Ш	7.	Transporter 2 Company Name	8.	USE	PA ID Numbe	r	E. Sta	te Transporte	r's IO			
11	_							nsporter's Ph				
Ш	9.	Designated Facility Name and Site	Address 10.	USE	PA ID Numbe	er .	G. Sta	ite Facility's II	,			
П	1				•	•	Li Ca	cility's Phone				
11			1				1"	only of more				
Π		US DOT Description (Including De	Chinaine Numa Hazand C	Y222	D Merchant	12. Conta	iners	13. Total	14. Unit	144	I. Iaste N	
å		US DOT Description (Including Pro	oper anipping Name, Hazard C	ass and I	U Number)	No.	Туре	Quantity	Wt/Vol	**	aste IV	
E	а.											
E						, [, }		} }	ı		
A	b.								+	Щ		
0	J~ ,						-					
ľ									1 1			
Ш	C.	·										
Ш		\				\ \			1	1		
П	_								╌┼╌╌╌┤			
Ш	đ.					į Į	1		1 1			
\prod	Ì,	}				i i	 		1 1	ŀ		
Ш	J	Additional Descriptions for Materia	ls Listed Above				K. Han	dling Codes f	or Waste:	s Liste	d Abov	/*
Ш	}					}						
Ш		•				ì						
Ш						ļ						
Ш	15.	Special Handling Instructions and	d Additional Information									
Ш												
	1											
Ш	16	GENERATOR'S CERTIFICATION: 1 her	reby declare that the contents of the	s consider	ent are fully and	accurately o	tescriper	above by				
$\ \ $		proper shipping name and are classifier according to applicable international ar	d, packed, marked, and labeled, an	id are in all								
Ш		If I am a large quantity generator, I ce			the volume and	taxicity of w	aste gen	erated to the d	agree i ha	ve dete	rmined	to be
Ш		economically practicable and that I has future threat to human health and the	ve selected the practicable method environment: OR, if I am a small of	d of treatme	ent, storage, or o	disposal curr ada a good (ently ava	dable to me wh	ich minimiz Waste de	zes the	presen	t and
		the best waste management method th	at is available to me and that I can	afford.								
V		Printed/Typed Name		Signa	IGIA				í	Month	<i>Day</i>	Year I
÷	17.	Transporter 1 Acknowledgement	of Receipt of Materials									
A		Printed/Typed Name		Signa	ture					Month	Day	Year
3				<u></u> l							L	
おかり の 年丁世界	18.	Transporter 2 Acknowledgement Printed/Typeg Name	of Receipt of Materials	C.22-	thurs.					· ·	Occi	Vere
Ē		Luttion) typed Mattie		Signa	uure				ĺ	Month	Day	Year
٢	19.	Discrepancy Indication Space										
F	1											
Iâl	l											
171	<u> </u>	Equility Courses of Operators Course										
[20.	racinty Owner or Operator, Certif	fication of receipt of hazardou	s material	s covered by	this manife	st excer	ot as noted in	item 19.			
44-7-DD#	20.	Printed/Typed Name	fication of receipt of hazardou	s material Signa		this manife	st excer	ot as noted in		Month	Day	Year

Style FISREV-6 Labelmaster, Div. of American Labelmark Co. Inc. 60646

EPA Form 8700-22 (Rev. 9/86) Previous editions are obsolete.

Manual Section Page Effective Date WHC-CM-2-14 Part III, REV 0 10 of 12

NONRADIOACTIVE HAZARDOUS MATERIALS/ HAZARDOUS WASTE (HM/HW) SHIPMENTS August 1, 1988

4.1 GENERATOR SECTION COMPLETED BY ORIGINATOR

- 1. Enter the generator's U.S. Environmental Protection Agency (EPA) identification number. At the Hanford Site, the identification number is WA 789 000 8967. Also enter a manifest document number assigned by the Site Hazardous Waste Management Engineering Support Unit.
- 2. Enter total number of pages used to complete the manifest (main page plus each approved continuation sheet).
- 3. Enter the name and address of the generator.
- 4. Enter the phone number of the generator.
- Identify the first transporter company by name.
- 6. Enter transporter EPA identification number, WA 789 000 8967 if WHC Transportation is used.
- 7. Enter second transporter company name, if applicable.
- 8. Enter second transporter EPA identification number, if applicable.
- 9. Identify the company and site address of the facility designated to receive the waste. The address must be the site delivery location not the company mailing address.
- 10. Enter the EPA number for the designated receiving facility.
- 11. Enter the DOT description, which includes the proper shipping name, hazard class, and identification number (United Nations (UN) or North American (NA) as applicable) for each waste as identified in 49 CFR 172. If a hazardous substance, place a reportable quantity (RQ) in the HM box and also identify the constituents making the material a hazardous substance. Any not otherwise specified (N.O.S.) entry must identify the constituent that makes it hazardous. If dangerous when wet, place words "Dangerous When Wet" in box in association with proper shipping name. If toxic by inhalation place words "Poison-Inhalation Hazard" in box in association with the basic description.
- 12. Enter the number and type of containers for each waste using appropriate abbreviations from the listing below.

TYPE OF CONTAINERS

DM = Metal drums, barrels, kegs

DW = Wooden drums, barrels, kegs

DF = Fiberboard or plastic drums, barrels, kegs

TP = Tanks, portable

Manual Section Page NHC-CM-2-14 Part III, REV 0

NONRADIOACTIVE HAZARDOUS MATERIALS/ HAZARDOUS WASTE (HM/HW) SHIPMENTS Effective Date

11 of i2 August 1, 1988

TT = Cargo tanks (tank trucks)

TC = Tank cars
DT = Dump trucks

CY = Cylinders

DM = Metal boxes, cartons, cases

CF = Fiber or plastic boxes, cartons, cases

BA = Burlap, cloth, paper or plastic bags

- 13. Enter the total quantity of waste described on each line.
- 14. Enter the appropriate abbreviation from the listing below to indicate the unit of measure. The preferred unit of measure is K for kilograms.

UNIT OF MEASURE

G = Gallons (liquid only)

L = Liters (liquids only)

P = Pounds

111

f* >

K = Kilograms

T = Tons (2,000 lb)

M = Metric tons (1,000 kg)

Y = Cubic yard

N = Cubic meters

- 15. Generators may use this space to indicate special transportation, treatment, storage, or disposal information, etc.
- 16. The generator must read, sign (by hand), and date the certification statement. The authorizing signature shall be that of a delegated individual who has successfully completed the "Certification of Hazardous Material Shipments" course or "Hazardous Waste Shipment Certification" course.

4.2 TRANSPORTERS SECTION COMPLETED BY TRANSPORTER

- 1. Enter (print or type) the name of the person accepting the waste described on the manifest by signing and entering date of receipt.
- 2. Same as item 1 but for the second transporter, if applicable.

4.3 FACILITY SECTION COMPLETED BY TREATMENT, STORAGE, DISPOSAL FACILITY

- 1. Receiving facility must note any significant discrepancies between the wastes described on the manifest and the waste actually received at the facility.
- The name of the person accepting the waste on behalf of the receiving facility must be entered (printed or typed). The person must acknowledge acceptance of waste described on the manifest by signing and entering the date of receipt.

1.11

Ç., c

Manual Section Page Effective Date WHC-CM-2-14
Part III, REV 0
12 of 12

.NONRADIOACTIVE HAZARDOUS MATERIALS/ HAZARDOUS WASTE (HM/HW) SHIPMENTS August 1, 1988

5.0 EXAMPLES OF HAZARDOUS MATERIALS SHIPMENTS

Examples illustrating the steps used in preparing specific HM shipments are shown in Appendix B.

WESTINGHOUSE HANFORD COMPANY

Manual Section

WHC-CM-2-14 Part IV, REV 0

Page Effective Date

1 of 47 August 1, 1988

HAZARDOUS MATERIAL PACKAGING

AND SHIPPING

Organization Procurement and Materials Management

TITLE:

L/)

1.7 7. Y

 \sim

...

Approved by

RADIOACTIVE MATERIAL SHIPMENTS

D. K. Quigley, Manager Procurement and Materials Momt

1.0 ONSITE SHIPPING PROCEDURES

1.1 GENERAL REQUIREMENTS/RESPONSIBILITIES

1.1.1 Manager of Facility

The manager of the facility that packages and offers a shipment of radioactive material for onsite transport shall:

- Designate personnel to become authorized shippers for packaging and shipping hazardous materials and initiate the authorizing process. (See Part II 2.1).
- 2. Assure that only appropriately trained personnel are employed to load and transport radioactive material packages, and that these personnel comply with applicable operating procedures that provide for nuclear safety, security, contamination control, and packaging and transport requirements for fissile and other radioactive materials, as well as, applicable federal, state, and contractor requirements, e.g., DOE Order 5480.3, DOE-RL Order 5480.1, Chapter III DOT 49 CFR, this manual, Safety Analysis Reports for Packaging (SARP), Certificates of Compliance (COC), WAC 173-303, etc.
- Assure that only approved packages are used.

1.1.2 Authorized Hazardous Materials Shipper

Authorized shippers must properly classify, describe, package, mark and label hazardous materials for shipment. The shipper is responsible for the shipment until it is delivered to the consignee's facility and accepted. In performance of these duties the shipper shall:

Assure that radicactive materials are loaded into packages that have been inspected, maintained, and approved for onsite transport. An auditable record of the inspection, maintenance, and certification that the package is ready for use must be maintained at the packager's facility. This includes a copy of the current SARP or COC or the Type A Certification document MLM 3245, wherever applicable.

- 2. Obtain agreement with the consignee for delivery of the material to the consignee's facility. This agreement may include prescheduling of the shipment and additional notification of an estimated time of arrival (ETA) just prior to shipment departure.
- 3. Arrange for the use of a vehicle and tiedown equipment approved for transporting the package to its destination, and assure prior to loading, that vehicles (tractor and/or trailer) are tagged showing the preventative maintenance and class A/B inspections are current.
- 4. Verify that all SARP requirements governing the use of each container are incorporated into applicable operating procedures and followed.
- 5. Schedule personnel to convoy the shipment when required by the SARP or by the safeguards and security requirements of MRP 5.27, "Movement of Radioactive Material."
- 6. Resolve all questions concerning the special services required while the package is being transported to the consignee's facility (e.g., cooling water in case of delay enroute, control of personnel because of a radiation dose, escort by Patrol for traffic control, etc.).
- 7. Properly complete an Onsite Radioactive Shipment Record (RSR, Exhibit IV-1-1) form for each shipment. This form must accompany the shipment to its destination. Certain routine onsite shipments may be shipped using an Onsite Routine Radioactive Shipment Record (ORRSR). See Section 2.4 for applicability.
- 8. Supervise and approve the loading and tie down of the package(s) into or onto the transport vehicle to assure compliance with applicable loading and tiedown requirements as specified in the procedure, SARP, COC, etc.
- 9. Assure that the transport vehicle is placarded radioactive, when required, and as appropriate for other hazardous materials being transported.
- 10. Make the following notifications when necessary:

- a. Notify the Fire Battalion Chief on duty of the starting time, estimated duration of the shipment, route to be followed, and destination, to expedite assistance, if needed.
- b. Notify the Bus and Rail Supervisor of the departure time, route, destination, and ETA to assist in traffic control.

HAZARDOUS MATERIAL PACKAGING	Manual	WHC-CM-2-14
AND SHIPPING	Section	Part IV, REV O
•	Page	3 of 47
RADIOACTIVE MATERIAL SHIPMENTS	Effective Date	August 1, 1988

c. Notify Patrol of the departure time, route, destination, and ETA. Request escort service, as required.

NOTE: Depending on the quantities shipped, some SNM shipments shall require classified notifications.

- 11. Provide the completed RSR to the truck driver, train engineer or convoy leader, as appropriate. Require that receiver's signature be obtained on the RSR indicating acceptance of the shipment.
- 12. Assure that an RPT has surveyed the package(s) and the vehicle. If a radiation protection convoy is required, an RPT will be assigned to the convoy team and provide the instrumentation needed to monitor the radiation dose and contamination level. The RPT will accompany the shipment to the onsite destination and will be prepared to take emergency action to minimize exposure to personnel and to the environs in the event of an accident.
- 13. Placard the vehicle in accordance with DOT requirements. Over placarding is acceptable for onsite shipments.
- 14. Maintain a copy of the RSR for three months as a record of the shipment.

1.1.3 Vehicle Driver

10

 \bigcirc

2.7

(2)

The driver of the transporting vehicle shall be appropriately trained by his management for transporting hazardous materials and shall:

- 1. Assure that the vehicle is appropriate for the load and free of defects that could affect the safe transport of the material.
- 2. Assure preventative maintenance and Class A/B inspections are current.
- 3. Assure that the shipment is properly positioned and secured to the vehicle.
- 4. Assure that the vehicle is placarded for the cargo.
- Assure that the radiation level in the cab has been determined to be within acceptable limits.
- Assure that radio equipment in the cab, if required, is functioning properly.

1.2 NORMAL ONSITE RADIOACTIVE MATERIALS SHIPMENTS, PROCEDURES

Onsite radioactive materials shipments require an RSR be completed for each shipment except as provided in this Part, Section 1.4, dealing with routine shipments covered with an Onsite Routine RSR.

Manual Section Page WHC-CM-2-14
Part IV, REV 0
4 of 47

RADIOACTIVE MATERIAL SHIPMENTS

Effective Date August 1, 1988

This section describes generally the actions required to prepare radioactive material for transport onsite. A schematic flow diagram of this process is given in Figure IV-1-1.

NOTE: If the material to be shipped is radioactive waste or radioactive mixed waste scheduled for storage or disposal in the 200 Area burial grounds, additional characterization and packaging requirements must be met. These requirements are found in WHC-EP-00063, "Hanford Radioactive Solid Waste Packaging, Storage and Disposal Requirements."

NOTE: In addition to this general procedure, specific operating procedures, prepared and controlled by the facility operations, shall be followed when packaging and transporting radioactive material shipments onsite. These procedures shall be reviewed and approved by Packaging Development for uniformity, SARP requirements and administrative controls.

1.2.1 <u>Definition of Material</u>

Define the material to be shipped in the following manner. (For additional assistance, see Appendix C, "Radioactive Material Characterization Tables").

- 1. List the radionuclides that are present (e.g., ^{239}Pu , ^{233}U , and ^{137}Cs).
- 2. Determine the level of radioactivity present in terms of curies. If fissile radioactive material (49 CFR 173.403(j)), determine the grams fissile for criticality control if applicable. Determine if material qualifies as a Hazardous Substance Reportable Quantity (RQ). See 171.8 and 172.101 Appendix.
- 3. Determine if material will be shipped as "normal form" or "special form" [49 CFR 173.403(s) and (z)].
- 4. If normal form, determine the physical form (e.g., solid, liquid, or gas) and the chemical form (e.g., nitrate, oxide, elemental, etc.) of the radioactive material.
- 5. Determine if other hazardous materials are present or if other hazardous characteristics are exhibited (e.g., corrosive, flammable liquid, oxidizing material, etc.).
- 6. Identify appropriate A₁ or A₂ values for radionuclides contained.
 - o Determine A₁ values for radionuclides in special form (49 CFR 173.433, 173.435).
 - o Determine A₂ values for radionuclides in normal form (49 CFR 173.433, 173.435).

∙≎ Ci

M

(T)

Alekson

,en .,

C!

n)

-

Manual Section Page Effective Date

WHC-CM-2-14 Part IV, REV 0 5 of 47 August 1, 1988




Figure IV-1-1. Onsite Radioactive Material Shippers Guide

C

1.17

()

40 W.

 \bigcirc

Manual Section Page WHC-CM-2-14 Part IV, REV 0 6 of 47

RADIOACTIVE MATERIAL SHIPMENTS

Effective Date

August 1, 1988

NOTE: Tables IV-1-1 and IV-1-2 list A_1 and A_2 values for commonly shipped radionuclides in special form and normal form, respectively.

- 7. Determine quantity category based on the radionuclides contained, their A₁ or A₂ values as appropriate and the number of curies to be packaged in each container (e.g., cask, box, drum). See the following sections of CFR for the quantities listed:
 - o Low Specific Activity Radioactive (LSA) Material, 49 CFR 173.403(n)
 - o Limited Quantity, 49 CFR 173.403(m) and 49 CFR 173.421-.424
 - Type A Quantity, 49 CFR 173.431(a)
 - o Type B Quantity, 49 CFR 173.431(b)
 - o Highway Route Controlled Quantity (HRCQ), 49 CFR 173.403.(1).

NOTE: Tables IV-1-1 and IV-1-2 list limiting values for each quantity category in terms of curies for commonly shipped radionuclides in special form and normal form respectively.

1.2.2 Shipping Container Selection, Preparation and Transport

- 1. Select a shipping container based on the following considerations:
 - a. The quantity, type, form and classification of radionuclides to be packaged.
 - b. Need for shielding and/or cooling
 - c. Size, shape, and weight of material to be shipped
 - d. Destination, mode of transport, and consignee's ability to handle receipt of the shipment
 - e. Dose rate and contamination considerations
 - f. Availability of shipping containers
 - g. Regulations found in DOE-RL Order 5480.1, Change 1, Chapter III, 49 CFR 173.400-173.478
 - If waste, the additional requirements of WHC-EP-0063.

Westinghouse Hanford onsite shipments, where possible, shall be made in DOT-specification containers loaded to meet DOT regulations as found in 49 CFR 173.401-173.478 or in containers with a valid COC (Shipper must be able to document the contents meet the authorized contents requirement applicable

O

f

C

Quantity Category	Limited Quantity ^{2,3}	Type A Quantity ^{2,4}	Type 8 Quantity ⁵	HRCQ 6	Low Specific Activity Material LSA ⁷
Radionuclides	≤10 ⁻³ A1	≤A₁	>A ₁	≥3,000×A ₁	Activity program of matrix
241Am	0.008	8	>8	24,000	N/A
243Am	0.008	8	8<	24,000	N/A
140	1	1,000	>1,000	30,000	N/A
€€Co	0.007	7	>7	21,000	N/A
137 C s	0.03	30	>30	30,000	N/A
238p _U	0.003	3	>3	9,000	N/A
239pu	0.002	2	>2	6,000	N/A
240 p ts	0.002	2	>2	6,000	N/A
Ze1p _U	1	1,000	>1,000	30,000	N/A
247 pu	0.003	3	>3	9,000	N/A
47Sr	0.1	100	>100	30,000	N/A
90Sr	0.01	10	>10	30,000	N/A
M.F.P.	0.01	10	>10	30,000	N/A
233Ų	0.1	100	>100	30,000	N/A
235U	0.1	100	>100	30,000	N/A
234()	Unlimited	Unlimited	Unlimited	30,000	N/A
U(NAT)	Unlimited	Unlimited	Unlimited	30,000	N/A
U _{(ENR} <28%)	Unlimited	Unlimited	Unlimited	30,000	N/A
U(ENR >26%)	0.1	100	>100	30,000	N/A
· U(depleted)	Unlimited	Unlimited	Unlimited	30,000	N/A

NOTE: All valves listed are in curies (Ci) unless otherwise stated.

PS83-3228-4

Table IV-1-1. Activity Limits for Commonly Shipped Radionuclides in Special Form.

¹For mixtures of radionuclides, the most restrictive values for any one member of the mixture, establishes the mixture limiting values. {Exceptions, see 49CFR 173.433(b)}.

²All values indicated, limit the activity within a given package.

¹For excepted instruments and articles see 49CFR 173.422,173.423, 173.424.

⁴Maximum activity values, if exceeded are Type 8 Quantity.

SPackage contents, restricted by Package Approval Documents only (e.g., SARP, COC).

⁶Highway Route Controlled Quantity (HRCQ) (Minimum values listed).

⁷Not applicable to special form material.

111

242Pu

#95r

905,

M.F.P.

2331;

235[]

238(;

U(NAT)

U(ENR <20%)

U(ENR >20%)

U(depleted)

0.003mCi

0.01

0.4mCi

0.4mCi

0.1mCi

0.2mCi

Unlimited

Unlimited

Unlimited

0.1mCi

Unlimited

NOTE: /	عميناديد ال۵	licted are	in ruring i	/Cilnlace	atherwise	etated.

¹For mixtures of radionuclides, the most restrictive values for any one member of the mixture, establishes the mixture limiting values. [Exceptions, see 49CFR 173.433(b)].

0.003

10

0.4

0.4

0.1

0.2

Unlimited

Unlimited

Unlimited

0.1

Unlimited

>0.003

>10

>0.4

>0.4

>0.1

>0.2

Unlimited

Unlimited

Unlimited

>0.1

Unlimited

30,000

1,200

1,200

300

600

30,000

30,000

30,000

300

30,000

PS83-3228-3

0.0001 mCi/g

0.3 mCi/g

0.005 mCi/a

0.005 mCi/q

0.005 mCi/g

0.005 mCi/g

Unlimited

Unlimited

Unlimited

0.005 mCi/g

Unlimited

Table IV-1-2. Activity Limits for Commonly Shipped Radionuclides in Normal Form.

²All values indicated, limit the activity within a given package.

³Values shown for solids and gases. For figuids divide value shown by 10.

⁴For excepted instruments and articles see 49CFR 173.422,173.423, 173.424.

⁵Maximum activity values, if exceeded are Type 8 Quantity.

⁶Package contents, restricted by Package Approval documents only (e.g., SARP, COC).

⁷Highway Route Controlled Quantity (HRCQ) (Minimum values listed).

^{*}See 49CFR 173.403(n) for additional specific criteria.

HAZARDOUS	MATERIAL	PACKAGING
AND SHIPPI	ING	

Manual Section Page WHC-CM-2-14 Part IV, REV 0 9 of 47

RADIOACTIVE MATERIAL SHIPMENTS

 \Box

1

Effective Date

August 1, 1988

in 49 CFR and COC) issued by the NRC or DOE. Where this requirement cannot be met, other containers may be used as long as an equivalent degree of safety is provided either by design or the use of administrative controls. Such containers must be used under the strict adherence to requirements of a SARP reviewed by the Packaging and Shipping Sub-Council and approved by the WHC approval authority. Additional approval is needed from DOE-RL for onsite shipments of HRCQ or fissile material. All packaging and shipping procedures used must reflect the requirements of the SARP prior to the use of the container. Loading requirements for the specification container DOT 6M are given in 49 CFR 173.417(b)(2). DOT 7A containers are authorized by 49 CFR 173.415, but their use must be supported by a safety assessment. Some 7A containers are qualified in MLM 3245. The shipper must maintain a file containing the SARP and other pertinent documentation (e.g., drawings, inspection records, etc.) pertaining to the use of the container for at least 1 year after last usage.

The "Hanford Shipping Container Directory" is a catalog of commonly used containers used by facilities for shipping radioactive materials onsite. It is not a shipping document. Additional guidance on container selection may be obtained from Packaging Development.

- 2. Obtain the container and inspect it. Work procedures, COCs, and SARPs list inspection requirements, as appropriate, and may require quality assurance/quality control verification.
- 3. Load the container with authorized contents only. Assemble and seal the package in accordance with appropriate procedures.
- 4. Arrange for a radiation survey of the package(s) to determine that smearable contamination limits and radiation dose rate limits are not exceeded (49 CFR 173.443 and 173.441, respectively). Certain packaging systems are exempt from these limits and are instead controlled by limits specified in approved SARPs.
- 5. Mark and label each package in compliance with its SARP, 49 CFR, or DOE-RL Order 5480.1A, Change 1, Chapter III, where applicable. To the extent practical, provide the following information on each package:
 - Responsible operating component (e.g., 225-B, WESF)
 - b. Date sealed or shipped
 - c. Radiation survey data
 - d. Estimated activity and identity of radioactive materials present (e.g., 2 Ci, Mixed Fission products (MFP))
 - e. Gross weight if >55 lb

- f. Radioactive labels (use either DOT approved labels or SARP approved alternative).
- g. Other hazard class labels, as appropriate (e.g., corrosive, flammable liquid, etc.). Use DOT approved labels.

NOTE: See SARP for specific requirements.

- 6. Determine the category and the security requirement if the material is SNM. (See DOE Order 5632.4.) Obtain Nuclear Materials Management Accountability review if necessary.
- 7. Determine if and when consignee can take delivery.

 \bigcirc

- 8. Schedule transportation equipment suitable for the shipment. Schedule Operational Health Physics and Patrol escorts if required.
- 9. Complete an RSR according to instructions found in Part IV, Section 2.3 that follows. This completed form must accompany the shipment to the consignee's facility, along with other pertinent papers, such as burial or storage forms (in accordance with WHC-EP-00063) and/or a list of SARP administrative controls under which the shipment must be made.
- 10. Furnish appropriate placards to the carrier (see 49 CFR Part 172 Subpart F) or if vehicle is equipped with permanent placards, assure that placards are turned to the proper hazards. All onsite radioactive shipments must be placarded in accordance with 49 CFR 172 Subpart F, or an approved alternative. See the SARP for specifics.
- 11. Supervise the loading and securing of packages into or onto the transport vehicle. Assure that riggers or truck drivers are aware of any tiedown requirements named in associated COCs, SARPs, work procedures, etc. It is the packager/shipper's responsibility to inspect and approve securing of all loads to assure tiedown requirements are met.
- 12. Assure that the carrier understands and follows all administrative controls as specified in the SARP for transport of the package(s).
- 13. Advise receiver of the ETA and request confirmation of delivery on interarea shipments exceeding Type A quantities.
- 14. Maintain a copy of the RSR for a least 3 months as a record of shipment.

HAZARDOUS MATERIAL PACKAGING	Manual	WHC-CM-2-14
AND SHIPPING	Section Page	Part IV, REV 0
RADIOACTIVE MATERIAL SHIPMENTS	Effective Date	August 1, 1988

1.3 PREPARING ONSITE RADIOACTIVE SHIPMENT RECORDS (RSR)

The following instructions are keyed to numbered blocks on a specimen copy of the onsite RSR (Exhibit IV-1-1).

NOTE: Shipments of material via the safe secure trailer (SST) and escorted by DOE couriers are classified and are, therefore, exempt from these RSR requirements.

NOTE: Minor errors on an RSR may be corrected in the field by drawing a line through the error, entering the correction above it, and signing the shipper's authorized signature adjacent to the error/correction.

1.3.1 Shipper Section Completed by Packager/Shipper

177

*

117

Mar No

7

- 1. Check appropriate blocks based on material classification, if SNM and if security escort is required (see Security Manual). Check appropriate contractor block.
- 2. Identify the receiver, shipper, and carrier by name. The shipment is to be addressed to an individual whose name must appear in the proper box. The address must also include identification of the contractor/component, building, area, and phone number. The shipper's name and complete address must be provided. Also, identify the vehicle by number.
- 3. Give a complete description of the radioactive contents. If several similar packages are being shipped, describe the worst case situation. List radionuclides present (abbreviations from 49 CFR 173.435 are acceptable). List the maximum curie content per container, maximum grams fissile material per container, total grams fissile per shipment, and total curies per shipment.
- 4. Determine if material is normal form or special form (49 CFR 173.403(s) and 173.403(z)). Identify ownership of material: DOE or licensee. Check appropriate block for physical form of material (e.g., solid, liquid, or gas). Determine quantity based on form (normal or special) and curies per container. Identify chemical form of the material (e.g., oxide, chloride, etc.).
- 5. Give a detailed description of the packaging. List the number and types of containers. Describe each, including internal packaging (e.g., absorbent). Describe any secondary hazards (e.g., corrosives). Include model numbers, identification numbers, DOT specification numbers, etc. Sketches may be made or attached.

RADIOACTIVE MATERIAL SHIPMENTS

1

Ln Manua 7 Section Page Effective Date

WHC-CM-2-14 Part IV, REV 0 12 of 47 August 1, 1988

Sp	ACISI Nuclear Material 1 (Instructions For purify Escort Required DOE CONTRACTOR: DPN:	TIVE SHIPMENT RECORD or Completion On Back) L	Nº 26080				
	Ta: From: Carrier:	er Section	Vehicle No.				
•	COMPLETE DESCRIPTION OF RADIOACTIVE CONTERTS. Radionuclide(s): 3 Maximum Activity (Curies)/Container:		ACKAGING DESCRIPTION:				
SHIPPER	Total Grams Total Curies' Fissile/Shipment Shipment	Secondary Hazards? (List): Container Approval Documenti	s): Shipment Number (when applicable)				
	Normal Form DOE Solid Gee Special Form Licensee 4 Liquid QUANTITY CATEGORY Chemical Form Limited Quantity Doxide Mixture Type A Quantity Division Elemental Type B Quantity Highway Route Controlled Quantity Specify	Absorbant Material Required . Containar(s) Free of Deterioration Labels Required	Yes				
RADIATION MONITORING	RM Escort Required Yes No	□ ≤ 22 or	d/m βγ / sq. cm d/m α / sq. cm				
	Surveyed by: Radiation Monitor Date INSTRUCTIONS: 1. Speed Limit Restricted To: Description of points In case of an accident or spill notify RM immediately. Phone A. Shipments during hazardous road conditions and/or congested traffic should be avoided. The down or restrain packages to prevent shifting or loss of packages during transport. Description of transport vehicle after delivery of radioactive materials. Other:						
	9. Obtain Receiver's Signature: Received by NOTE. Person authorizing shipment must not transport it. CERTIFICATION (1.3.4) Certification Section This/These package(s) has/have been prepared for onsite shipment in accordance with applicable federal regulations as prescribed in DOE Order 5480.1A chapter III and its Rt supplement. Shipping Organization Rep. Print Name Date						

Exhibit IV-1-1. Specimen Copy of an Onsite Radioactive Shipment Record (RSR).

HAZARDOUS MATERIAL PACKAGING	Manua l	WHC-CM-2-14
AND SHIPPING	Section	Part IV, REV 0
	Page	13 of 47
RADIOACTIVE MATERIAL SHIPMENTS	Effective Date	August 1, 1988

6. List container approval documentation, e.g., SARP numbers (e.g., HCS-047-001-00), COC numbers, or the DOT specification numbers for the container's fabrication and approved loading. If the shipment is being made under an approved waiver or deviation, the waiver or deviation letter number must also be listed. The remaining questions are self-explanatory.

1.3.2 <u>Radiation Monitoring Section Completed By Radiation Protection Technologist</u>

I. Radiation survey data for the package(s) and the vehicle are recorded here. The RPT signs and dates the form.

NOTE: The RPT will retain the white copy of the RSR in the RPT office however, the RPT shall not remove the white copy until the shipment is completely packaged and the shipper has certified the shipment. The white copies are later collected by Traffic and retained.

1.3.3 Carrier Section Completed By Packager/Shipper

1.13

747

~/^\

...

1. Shipper must record any speed limit restrictions required by SARP and list the Radiation Monitoring emergency number. The shipper should list or reference any additional administrative controls or security requirements that must be followed by the carrier. Any radiation dose rate that exceeds the DOT limit of 200 mr/hr at package surface must be specifically authorized in the SARP. For dose rates exceeding 1 rem/hr at three feet OHP must concur prior to shipment. The shipper must notify Packaging Development that the SARP limits were exceeded. The receiver must concur with conditions of shipment prior to shipment.

NOTE: The carrier must obtain a signature from the consignee indicating acceptance of the shipment. This must be done before the shipment can be considered complete.

1.3.4 Certification Section Completed By Certifier

1. An authorized and delegated shipping organization representative must sign and date the form, certifying that the shipment meets DOE-RL and contractor shipping requirements. The authorizing signature must be one of a delegated employee who has passed the "Certification of Hazardous Material Shipments" course. Retraining in this course is required every 2 years to retain signature authorization.

NOTE: Instructions are printed on the reverse side of the RSR for disposition of copies.

HAZARDOUS MATERIAL PACKAGING
AND SHIPPING
Section
Page
14 of 47
RADIOACTIVE MATERIAL SHIPMENTS
HAZARDOUS Manual
Section
Page
14 of 47
REFRORM
August 1, 1988

1.4 ONSITE ROUTINE RADIOACTIVE SHIPMENTS

Certain onsite radioactive material shipments; such as sealed sources, environmental and process samples, and low level waste not exceeding Type A; due to their frequency and uniformity of contents and packaging are considered routine. The safety record for these shipments is well established and supports their movement and documentation by use of an Onsite Routine Radioactive Shipment Record (ORRSR).

Limits, requirements, supporting documentation and qualification of personnel will be determined by Operations Manager, Radiological Assessment/Packaging & Shipping, Operational Health Physics and Traffic. Limits shall not exceed those specified in the Package Approval document.

The ORRSR shall be a documented record of all routine type shipments and used only for the shipment of radioactive material as described therein. Use of the ORRSR gives a considerable time savings and convenience in shipping activities, however, violation of the shipment conditions stated will result in withdrawal of the ORRSR and issuance of an Event Fact Sheet.

Two variations of the ORRSR form are used (Exhibit IV-1-2 and IV-1-3, Form Numbers WHCM 8708-002.1 and WHCM 8708-002.2) depending on the quantity and type of radioactive material shipped and the shipment certification needed.

The Routine Authorization Form (Exhibit IV-1-2) is authorized by Traffic after review and approvals are received from Operational Health Physics (OHP), Operations Managers and Radiological Assessment/Packaging & Shipping (RA/P&S). The Traffic approval authorizes qualified personnel (See 1.4.1, Step 9 below) as well as authorized shippers to certify that the shipments meets all the requirements as set forth on the ORRSR and that the package meets applicable requirements for onsite shipments. In most cases this will be limited to Limited Quantity, LSA, or Types A and B special forms only.

The Authorized Shipper form (Exhibit IV-1-3) is to be used for routine shipments up through Type A quantities. This form requires that each shipment be reviewed and certified by an authorized hazardous materials shipper. Limits shall be as determined by the approval organization.

1.4.1 How To Obtain An ORRSR

L()

 \bigcirc

., .

The Operating Organization will prepare a draft ORRSR (new or renewal) in accordance with the following instructions and forward it to Traffic to initiate the review and approval cycle. Step by step instructions keyed to Exhibits IV-1-2 and IV-1-3 are as follows:

1. FOR THE SHIPMENT OF Use the proper shipping name of the material and package description (Model, etc.), including its approval document number (DOE/NRC COC, DOT Specification or Exemption, SARP. etc.) that will help identify the shipment.

Same.

3

LO

 \bigcirc

⇔

RADIOACTIVE MATERIAL SHIPMENTS

Manual Section Page Effective Date WHC-CM-2-14 Part IV, REV 0 15 of 47 August 1, 1988

	ONSITE ROUTINE RADIOACTIVE SHIPMENT	RECORD	NO. (3)
	DOE CONTRACTOR WESTINGHOUSE HANF	ORD COMPANY	COPY NO. (4)
	FOR THE SHIPMENT OF	VOID DATE 5	
	BETWEEN (2)		NO INSPECTION UNCLASSIFIED
	DESCRIPTION OF RADIOACTIVE CONTENTS:	PACKAGE REQUIREMENTS	
=	RADIONUCLIDES 6	7	
ž	ACTIVITY (MAX) FISSILE (GRAMS)		
2	PHYSICAL FORM		
	FORM - NORMAL CHEMICAL FORM		
Q	_	APPROVAL DOCUMENT(S):	
7	SECONDARY HAZARD	QA INSPECTION:	
shipmen	RADIOLOGICAL PROTECTION REQUIREMENTS	QUALIFIED PERSONNEL - 10	o package and ship
7	8	9	<u> </u>
Ţ			
	LABEL(s) REQUIRED		
<u>.</u>	PHONES - RWPS -	PHONES	
1	SPECIAL REQUIREMENTS	PHONES	
Ž	SPECIAL REQUIREMENTS		
	(10)		
copy valid for	CARRIER INSTRUCTIONS (11)		
\sim	1. SPEED LIMIT RESTRICTED TO: MPH. HEV	er exceed posted limits.	
	2. O DO NOT LEAVE SHIPMENT UNATTENDED BETWE 3. O IN CASE OF ACCIDENT ON SPILL NOTIFY RPT II	MMEDIATELY. CALL 811	
ш	4. SHIPMENTS DURING HAZARDOUS ROAD COND 5. TIE DOWN OR RESTRAIN PACKAGES TO PREVE	ENT SHIFTING OR LOSS OF PACK	AGES DURING TRANSPORT.
	6. DECLARE MATERIAL AND PRESENT SHIPMENT IS OBTAIN RPT RELEASE OF TRANSPORT VEHICLE		
BLUE	* PLACARD(s) REQUIRED.	ADC AUTHODISCS TO ACCUSE	y Tro orientous
\mathbf{m}	THE ABOVE LISTED QUALIFIED PERSONNEL	ARE AUTHORIZED TO CERTIF	T THIS SHIPMENT
	ROUTINE	D SIGNATURE	
7	AUTHORIZATION		
	APPROVALS (14)	T_NAME	DATE
0		TRAFFIC	DATE
}	OPERATIONS MANAGER DATE	RACIOLOGICAL ASSESSMENT 4	DATE
		PACKAGING/SHIPPING	
	OPERATIONS MANAGER DATE	OPERATIONAL HEALTH PHYSICS	DATE
1			WHCM 8708-002,1

LI)

 \bigcirc

₽v⊤,

 \bigcirc

ጋ ላ

Manual Section Page Effective Date

WHC-CM-2-14 Part IV, REV 0 16 of 47 August 1, 1988

WHCM 8708-002.2

ONSITE ROUTINE RADIOACTIVE SHIPMENT RECORD 3 DOE CONTRACTOR WESTINGHOUSE HANFORD COMPANY COPY NO. FOR THE SHIPMENT OF VOID DATE 1 NO INSPECTION BETWEEN UNCLASSIFIED 2 DESCRIPTION OF RADIOACTIVE CONTENTS: PACKAGE REQUIREMENTS RADIONUCLIDES 6 copy valid for shipmen FISSILE (GRAMS) ACTIVITY (MAX) PHYSICAL FORM CHEMICAL FORM FORM - NORMAL I SPECIAL QUANTITY APPROVAL DOCUMENT(S): SECONDARY HAZARD GA INSPECTION: RADIOLOGICAL PROTECTION REQUIREMENTS QUALIFIED PERSONNEL · to package and ahip LABEL(s) REQUIRED PHONES -RWPS . PHONES SPECIAL REQUIREMENTS 10 CARRIER INSTRUCTIONS 1. SPEED LIMIT RESTRICTED TO: MPH. NEVER EXCEED POSTED LIMITS.
2. DO NOT LEAVE SNIPMENT UNATTENDED BETWEEN PICK UP AND DROP OFF POINTS.
3. IN CASE OF ACCIDENT OR SPILL, NOTIFY RPT IMMEDIATELY. CALL B11
4. SHIPMENTS DURING HAZARDOUS ROAD CONDITIONS AND/OR CONGESTED TRAFFIC SHOULD BE AVOIDED.
5. TIE DOWN OR RESTRAIN PACKAGES TO PREVENT SHIFTING OR LOSS OF PACKAGES DURING TRANSPORT.
6. DECLARE MATERIAL, AND PRESENT SHIPMENT RECORD AT EACH PATROL CHECK POINT.
7. OBTAIN RPT RELEASE OF TRANSPORT VEHICLE AFTER DELIVERY OF RADIOACTIVE MATERIALS.
8. PLACARD(s) REQUIRED. AUTHORIZED SHIPPER (13 to Certify on reverse side APPROVALS ORIGINATOR DATE TRAFFIC DATE OPERATIONS MANAGER DATE RADIOLOGICAL ASSESSMENT & DATE PACKAGING/SHIPPING **OPERATIONS MANAGER** DATE OPERATIONAL HEALTH PHYSICS DATE

(

- BETWEEN List buildings and areas that shipment will be going to and from. If several areas are involved it may be "All Areas Hanford Site". The buildings and areas will be recorded on the shipment record.
- 3. NO. Each routine will be assigned an identifying number by area, year and operations group by Traffic.
- 4. COPY NO. The Blue card stock, working copies will be prenumbered before issued by Traffic. The originator is responsible to ensure that adequate supplies of ORRSRs are issued and maintained so not to affect operations when the Shipment Record portion on the reverse side is completed. Completed ORRSRs should be returned to Traffic immediately.

Upon revision of the ORRSR, all previous copies still in the field should be recalled by the originator and returned to Traffic for accountability. U)

- 5. <u>VOID DATE</u> The ORRSR is void on date shown. This date will never be over one year from date of issue.
- <u>DESCRIPTION OF RADIOACTIVE CONTENTS</u> The originator shall identify activity/quantity limits for each radionuclide to be shipped based on calibration, characterization or calculation.
- PACKAGE REQUIREMENTS Descriptions of containment and package. List all approval documents relating to the container and procedures used by Operations personnel.
- 8. RADIOLOGICAL PROTECTION REQUIREMENTS The radiation limits set here are the limits for the package described on the ORRSR. If the limits are exceeded, the package must be shipped on an Onsite RSR, requiring approval by an authorized shipper.

All labeling shall meet DOT transportation regulations unless the SARP specifies otherwise. Secondary hazard class labels shall be used when appropriate.

List of any RWPs related to packaging, handling, shipping and transporting, for both the shipper and receiver.

9. QUALIFIED PERSONNEL Qualification of personnel is a determination that knowledge and abilities gained through training and experience, measured against established requirements, standards, procedures or tests, qualify an individual to perform a required function in a safe and proficient manner. In all cases, the determination of personnel qualification is by their responsible manager and his approval on the ORRSR. Auditable records documenting that only qualified individuals are assigned to organizational shipping responsibilities are required.

HAZARDOUS MATERIAL PACKAGING AND SHIPPING	Manual Section	WHC-CM-2-14 Part IV, REV 0
RADIOACTIVE MATERIAL SHIPMENTS	Page Effective Date	18 of 47 August 1, 1988

- 10. <u>SPECIAL REQUIREMENTS</u> Special instructions including specific tiedown requirements, if applicable, should be specified.
- CARRIER INSTRUCTIONS Check each requirement for the carrier's attention. Special instructions should appear above.
- 12. <u>ROUTINE AUTHORIZATION</u> ORRSRs of this type (Exhibit IV-1-2) discussed above are authorized by Traffic after other approvals are done. Qualified personnel may certify these shipments on reverse side.
- 13. <u>AUTHORIZED SHIPPER</u> ORRSRs of this type (Exhibit IV-1-3) discussed above require review and certification signatures of authorized shippers for each shipment on the reverse side.
- 14. <u>APPROVALS</u> The routine will be reviewed and approved periodically on a case-by-case basis. Approvals are required by all organizations listed on the form.

ORIGINATOR shall be the central contact for the ORRSR to control the copies being used and assure proper use of them.

<u>OPERATIONS MANAGER</u> shall be the responsible manager of the qualified personnel and the material being shipped. The shipping manager and the receiving manager shall approve.

RADIOLOGICAL ASSESSMENT/PACKAGING & SHIPPING must review and approve.

OPERATIONAL HEALTH PHYSICS must review and approve radiological conditions set forth.

TRAFFIC must review and approve.

1.4.2 Use Of The ORRSR

5"

Li

ŗ. -.

 \Box

1

Shipment Logs particular to each of the two types of ORRSRs are imprinted on the reverse side and are shown here for comparison (Exhibits IV-1-4 and IV-1-5).

Exhibit IV-1-4 is the Shipment Log appearing on the back of the "Routine Authorization" ORRSR (Exhibit IV-1-2) and allows qualified personnel, designated on the front, to certify a shipment.

Exhibit IV-1-5 is the Shipment Log appearing on the back of the "Authorized Shipper" ORRSR (Exhibit IV-1-3). In this case each shipment must be certified by an authorized shipper.

SHIPMENT LOG		ONSITE ROUTINE RADIOACTIVE SHIPMENT RECORD				NO.	i i		
QUALIFIED PERSONNEL - List on front page		DOE CONTRACTOR WESTINGHOUSE HANFORD COMPANY					У СОРУ	СОРУ НО.	
CERTIFICATION THESE PACKAGE(S) HAVE BEEN PREPARED FOR ONSITE SHIPMENT IN ACCORDANCE WITH DOE-RL AND CONTRACTOR SHIPPING REQUIREMENTS;		FOR THE SHIPMENT OF					-	VOID DATE NO INSPECTION UNCLASSIFIED	
		BETWEEN							
QUALIFIED PERSON'S SIGNATURE	PRINT NAME						OHP SURVEY	RECEIVED BY	
									
									
							`		
······································									
							 		
						·			

Only BLUE copy valid for shipment

HAZARDOUS MATERIAL PACKAGING AND SHIPPING RADIOACTIVE MATERIAL SHIPMENTS Manual Section Page Effective Date

								·
SHIPMENT LOG		ONSITE ROUTINE RADIOACTIVE SHIPMENT RECORD				NO. COPY NO.		
		DOE CONTRACTOR WESTINGISUSE HANFORD COMPANY						
CERTIFICATION THESE PACKAGEISI HAVE BEEN PREPARED FOR ONSITE SHIPMENT IN ACCORDANCE WITH ODE-RL AND CONTRACTOR SHIPPING REQUIREMENTS:		FOR THE SHIPMENT OF					VOID DATE NO INSPECTION UNCLASSIFIED	
	· · · · · · · · · · · · · · · · · · ·		-		ļ		1 1	· · · · · · · · · · · · · · · · · · ·
					ļ	<u> </u>	 -	
					 		 	·····
•					 -	 -	1	
					<u> </u>		 	·
								
	-							
	·				ļ			
			_		ļ		 	
				·			 -	
			- 				 -	
		· · · · · · · · · · · · · · · · · · ·					 -	
						•		
			<u>- </u>					
			<u> </u>				1 T	

Only Blue copy valid for shipment

WHC-CM-2-14 Part IV, REV 0 20 of 47 August 1, 1988

Manual Section Page Effective Date

RADIOACTIVE MATERIAL SHIPMENTS HAZARDOUS MATERIAL PACKAGING AND SHIPPING

HAZARDOUS MATERIAL PACKAGING	Manua l	WHC-CM-2-14
AND SHIPPING	Section	Part IV, REV O
	Page	21 of 47
RADIOACTIVE MATERIAL SHIPMENTS	Effective Date	August 1, 1988

Each shipment shall be documented by entering the required information onto a single line of the Shipment Log. When all the lines of the log are filled return the ORRSR to Traffic for a replacement. The Shipment Log is the instrument used to give Traffic a degree of control and to determine the frequency of use and need for each ORRSR.

2.0 MISCELLANEOUS RADIOACTIVE MATERIAL SHIPMENTS

2.1 FISSILE MATERIAL AND SPECIAL NUCLEAR MATERIAL

157

 \mathbb{C}

10

4

The shipment of fissile materials requires certain controls in addition to those needed for nonfissile radioactive material. Fissile materials require controls for criticality safety and accountability and since all DOT designated fissile materials are also special nuclear materials (SNM) of national strategic importance, additional controls for security and safeguards are also mandatory.

NOTE: In the Atomic Energy Act, the term SNM refers to any isotope of plutonium, uranium-233, uranium-235, uranium containing more than the normal abundance of uranium-235, or any material artificially enriched in any of these substances. Specifically, fissile isotopes are those capable of sustaining a nuclear chain reaction with thermal (slow) neutrons. (e.g. 235U, 239pu, 241pu, and 233U, while fissionable isotopes are those capable of sustaining a nuclear chain reaction by fast or thermal neutrons (e.g. 238 pu, 240pu, 237Np, 244Cm, 241Am, etc.). For purposes of this manual, the term "fissile" will include fissionable material as well as fissile.

2.1.1 Fissile Exempt Material - Onsite/Offsite Shipment

Fissile material is classified as either fissile or fissile exempt material. Fissile exempt material is exempted from criticality safety packaging requirements. These shipments must still be in accordance with both shipping and receiving facility fissionable material limits and restrictions. The most common exemption is no more than 15g fissile material in a package. If material is transported in bulk the 15g limitation applies to the conveyance. Additional fissile material exemptions are given in 49 CFR 173.453.

All fissile material, whether exempt or not, is subject to the same packaging and shipping regulations as nonfissile radioactive material, and must also be characterized as Limited Quantity, Type A, Type B, or Highway Route Controlled Quantity (HRCQ), and shipped in containers approved for those quantities.

2.1.2 <u>Fissile Material Offsite/Onsite Shipments</u>

All offsite shipments (>15g) of fissile material shall be packaged either in DOT Specification containers consistent with 49 CFR 173.417 or in containers approved by DOE or NRC for transportation of fissionable material. Approved containers do not require additional criticality safety reviews.

Offsite shipments shall be in accordance with the container Certificate of Compliance or as specifically described in 49 CFR for DOT specification containers. This certificate shall be posted or readily available within the loading areas and any place where fissile material is stored in the container. The Transport Index shall be posted on the container.

All onsite shipments (>15g) of fissile material not packaged in offsite containers shall be packaged in containers reviewed and approved by the WHC Approval Authority and DOE-RL, when applicable. Safety shall review onsite containers for criticality safety concerns. Onsite container design when coupled with other considerations shall provide criticality safety protection consistent with protection provided by approved offsite containers.

Onsite shipments shall be made in accordance with both shipping and receiving facility Criticality Safety Specifications or facility fissile material status and the container authorized fissile contents based on the container SARP. The container SARP shall be available for use within the loading and unloading areas or any place where fissionable material is stored in the container.

2.1.3 Fissile Classes

1)

 \bigcirc

ge on

 \bigcirc

Packages of fissile radioactive material are classed as Fissile Classes I, II, or III depending on the degree of control needed to provide nuclear criticality safety during handling and shipping. Criticality Safety Analysis, performed and documented in a SARP, COC or 49 CFR 173.417, determines the fissile class to be applied to a package for shipment of fissile material. Fissile classes are defined in 49 CFR 173.455.

2.1.4 · Accountable Material

2.1.4.1 Accountability

Accountability is materials management based on nuclear materials accounting control including the documentation of all transactions and adjustments that affect the materials balance, material usage and the preparation of inventory reports. Accountable Materials, consistent with DOE Safeguards and Security Division recommendations and with WHC usage, include radionuclides grouped according to their origins, uses and properties and referred to by a variety of terms:

- o Nuclear Materials
- o Source Materials

HAZARDOUS MATERIAL PACKAGING	Manual	WHC-CM-2-14
AND SHIPPING	Section	Part IV, REV 0
	Page '	23 of 47
RADIOACTIVE MATERIAL SHIPMENTS	Effective Date	August 1, 1988

o Special Nuclear Materials

Accountable Nuclear Materials defined by DOE Order 5630.2(2) are:

- o Uranium, natural, depleted, enriched <20%, ≥20% U-235
- o Plutonium, all isotopes
- o Americium-241, -243
- o Curium
- o Berkelium
- o Californium
- o Lithium-6
- ம o Uranium-233

15

* .

- o Neptunium-237
 - o Deuterium
 - o Tritium
 - o Thorium

2.1.5 Approvals for Offsite Shipments of Radioactive Material

Offsite shipments and certain onsite movements of any radioactive material, whether accountable or not, require approval by Safeguards and DOE-RL. Nonaccountable radioactive material shipments and some small amounts of accountables are generally covered by a blanket approval obtained at the beginning of each fiscal year; approvals for larger amounts of accountable materials are generated on a case-by-case basis.

The shipment originator initiates application for approval by submitting a Radioactive Material Action Request (BD-7200-035) to Safeguards. Safeguards reviews the request and submits it to DOE/RL for approval.

The <u>Nuclear Material Control and Accountability Manual</u>, WHC-CM-4-34, gives guidance for generating the approval request and the correct accountability forms.

HAZARDOUS MATERIAL PACKAGING AND SHIPPING	Manual Section	WHC-CM-2-14 Part IV, REV 0	
RADIOACTIVE MATERIAL SHIPMENTS	Page Effective Date	24 of 47 August 1, 1988	

2.1.6 <u>Categorization and Physical Protection for SNM Shipments</u>

T

Offsite shipments of SNM must comply with the physical protection requirements of 10 CFR, Energy; 49 CFR, Transportation; and DOE Order 5632.4, "Physical Protection of Security Interests".

Onsite shipments of SNM must comply with these same regulations as well as MRP 5.27, "Movement of Radioactive Material" and WHC-0076, Rev. 2, Classified, Secret, "Hanford Intrasite Shipments of SNM by Rail or Wheeled Vehicle Security Plan." These two latter onsite documents may contain more stringent requirements than those for offsite and should be inspected closely to prevent shipping problems.

Whether onsite or offsite, the degree of security imposed on the shipments is determined by the category amounts of SNM defined in DOE Order 5632.4. Table IV-2-1 defines the SNM categories. Chapter VI of DOE Order 5632.4 defines the minimum requirements for safeguarding SNM by categories while in transit.

Table IV-2-1

PHYSICAL PROTECTION
CATEGORIZATION OF NUCLEAR MATERIAL

Special Nuclear	Category <u>l</u> /	Category <u>l</u> /	Category <u>2</u> /	Category
Material	I	II	III-A	III-B
Plutonium	2 kg or	400-1,999	220-399	1-219
	more	grams	grams	grams
Uranium-233	2 kg or	400-1,999	220-399	1-219
	more	grams	grams	grams
Uranium-235 (Contained in Uranium enriched to 20% or more)	5 kg or	1,000-	350-999	1-349
	more	4,999 grams	grams	grams
Uranium-235 (Contained in Uranium enriched to less than 20%)				All quantities one gram or more

If Plutonium or Uranium-233 is combined with Uranium-235, the amounts of Plutonium or Uranium-233 must be normalized to the U-235 content by multiplying by 2.5 to arrive at the category limits shown.

^{2/} A Plutonium and/or Uranium-233 content of less than 400 grams may be combined with Uranium-235 when the total content is less than 1,000 grams.

Manual Section Page Effective Date WHC-CM-2-14 Part IV, REV 0 25 of 47 August 1, 1988

RADIOACTIVE MATERIAL SHIPMENTS

Documentation for Category I shipments is classified. Certain Category II shipments may be classified depending on the material, and the above documents.

2.1.7 Security Exemptions for Onsite Shipments of SNM

- 1. Plutonium contained with other materials, the aggregate of which is defined as waste, and transported wholly within the confines of a limited area, is exempt from requirements for patrol escort and use of a dedicated Equipment Operations vehicle.
- 2. Plutonium not readily separable from other radioactive material, the combination of which delivers an external radiation dose in excess of 100 rem/at 3 ft without intervening shielding, is exempt from these physical protection requirements.
- 3. Plutonium in quantities >2 kg transported between the 324, 325 or 308 Buildings (within the 308 Protected Area) is exempt from the physical protection quidelines. The two-man rule plus one patrolman applies. An Equipment Operations vehicle not required.
- 4. If WHC cannot provide the required physical protection for a shipment of SNM that would seriously impact operations, the requirements for use of a dedicated vehicle may be waived by DOE-RL.

2.2 RADIOACTIVE MIXED WASTE

100

S.

LO

 \bigcirc

.

Radioactive mixed wastes are radioactive wastes that also exhibit other hazardous characteristics or are cross-contaminated with materials or wastes that are hazardous as defined in 40 CFR Parts 260-265, 49 CFR Parts 171-179 and/or Washington Administrative Code (WAC) 173-303. Radioactive mixed wastes are regulated jointly under the Atomic Energy Act (AEA) and the Resource Conservation Recovery Act (RCRA), and as such, must be packaged, shipped and disposed of in accordance with the regulations established under these two Federal laws.

Based on these laws and regulations established to enforce them, it is mandatory that radioactive mixed wastes be packaged and shipped onsite and/or offsite in accordance with DOT Hazardous Material Regulations as set forth in 49 CFR Parts 171-179. Certain exceptions may be granted by applying for a DOT exemption for offsite shipments or a DOE Headquarters alternative or DOE field office exception for onsite shipments (see DOE Order 1540.2 for administrative procedures that apply). Remember that DOE policy is that these options not be used unless extraordinary circumstances exist that would justify noncompliance to established regulations.

Radioactive mixed waste at Hanford must be prepared for storage or disposal in accordance with WHC-EP-00063, "Hanford Radioactive Solid Waste Packaging, Storage and Disposal Requirements" as applicable.

HAZARDOUS MATERIAL PACKAGING	Manual	WHC-CM-2-14
AND SHIPPING	Section	Part IV, REV 0
RADIOACTIVE MATERIAL SHIPMENTS	Page Effective Date	26 of 47 August 1, 1988
REDIONOTIVE BRICKING SHIPPIGHTS	Filective Date	August 1, 1900

Radioactive mixed wastes at Hanford must be shipped in accordance with applicable DOT regulations or under a DOE approved alternative which is formally documented and provides an equivalent degree of safety. Shipping paper documentation of radioactive mixed waste shipments must consist of radioactive shipment records (RSRs) and uniform hazardous waste manifests (UHWM) when required for the type and quantity of material being shipped. For examples of this documentation, see Sections III-3.0, III-4.0, IV-2.3 and IV-4.3.

2.3 CONTROLLED VEHICLES

V

11)

Certain onsite movements of radioactive material contamination do not qualify as radioactive material shipments and therefore are not documented with an onsite RSR or onsite routine RSR. These are movements of controlled vehicles and regulated vehicles that cannot be unconditionally released. These are covered on a Radiation Work Permit (RWP). Radiation Protection, WHC-CM-4-10, defines these vehicles in sections 7.4.4.13 and 7.4.16 and shows the appropriate signs or stickers for each.

3.0 OFFSITE SHIPPING PROCEDURES

3.1. SHIPPER'S RESPONSIBILITIES

The delegated/authorized hazardous materials shipper who prepares packages of radioactive material for offsite shipment is responsible for the following functions:

- Verifying that the consignee has a license (specific or general) to receive and process the type of radioactive material to be shipped. This check is required whenever the consignee is not a licenseexempt DOE contractor.
- Properly classifying, describing, packaging, marking, and labeling the radioactive material for offsite shipment in a manner that complies with applicable government (Federal, state, local) regulations (e.g., Title 49 CFR Parts 171-179, DOE Order 5480.3.
- 3. Properly completing an Offsite Radioactive Shipment Record (ORSR) form for each shipment.
- 4. Notifying Traffic of the following items in advance of shipment:
 - a. The date the shipment will be packaged and ready for transport
 - b. The proper shipping name, hazard class, and the United Nations/North American (UN/NA) number
 - c. The radionuclides and quantity (curies and grams) of material to be shipped and for fissile material, the fissile class assigned to each package.

- d. The number and types of packages used. Each package description should include the U.S. Department of Transportation (DOT) specification or Certificate of Compliance (COC) number, as appropriate, and its size and weight.
- e. All special considerations such as suggested routings, mode of transport, special vehicle requirements, safeguards and security, destination, requested delivery dates, and any other pertinent information concerning the shipment.

NOTE: A one day advance notice of shipment is a minimum requirement and that special shipments (e.g., exports, exclusive-use, safe secure trailer (SST), etc.) require longer lead times. As example, irradiated reactor fuel shipments require that a physical protection plan be developed and approved before shipment (49 CFR 173.22(b)). This may take some time to complete. Another example, a Highway Route Controlled Quantity (HRCQ) radioactive shipment requires special routing and the filing of a route plan, as well as submittal of additional information (49 CFR 173.22(c)). The manager who arranges for the offsite shipment of a HRCQ must provide the necessary data to Traffic 60 days prior to the first shipment. Additional guidance is given in Appendix D.

00

LO

S

NOTE: Prenotification must be made to the states that shipments of spent fuel or high level waste pass through, requiring additional time. The manager who intends to ship either unclassified spent fuel or high level radioactive waste offsite must submit the necessary information to Traffic at least two weeks prior to the shipment for concurrence and subsequent transmittal to DOE-RL. Additional guidance is given in Appendix D.

5. Scheduling onsite transportation with Heavy Equipment Operations from the packager's site to the 1167 Building of less than truckload shipments, including Category III quantities of Special Nuclear Material (SNM). Assure, prior to loading, the transport vehicle/trailer is visually inspected and the Class A/B preventative maintenance is current.

NOTE: No SNM can be stored overnight in the 1100 area. Traffic must be notified in advance of any shipment of SNM to ensure a timely departure from Hanford. Otherwise, the shipment will be returned to the shipper until proper procedures are followed.

- 6. Scheduling in advance, Category II shipments of SNM through Traffic to assure availability of equipment and properly cleared drivers.
- 7. Scheduling in advance Category I shipments of SNM and "cargos of opportunity" with Traffic for movement in the SST system operated by the Albuquerque Operations Office-Transportation Safeguards Division (ALO-TSD).

8. Requesting in advance that Traffic schedule commercial carriers to load exclusive-use or full-load shipments of radioactive materials at the packager's site.

- 9. Delivering the completed ORSR form to the truck driver or train engineer making the onsite transfer to the 1167 Building or to the Traffic representative who may witness the loading of an exclusive-use vehicle at the packager's site.
- 10: Inspecting and approving tiedown systems used to secure loads to the transport equipment. Note that tiedown system approval responsibilities are shared with other functional groups, depending on the type of shipment and method of transport.
- 11. Assuring that transport vehicles are placarded for the appropriate hazards as required by the regulations (49 CFR 172 Subpart F).
- 12. Maintaining for at least one year a file of supporting documentation used as a basis for making the shipment (e.g., current COC, Safety Analysis Report for Packaging (SARP), etc.). Assure all appropriate internal procedures reflect the requirements of these documents prior to making the initial shipment.

3.2 GENERAL PROCEDURE FOR OFFSITE RADIOACTIVE MATERIAL SHIPMENTS

This section describes in general terms the actions required to prepare radioactive material for transportation offsite. A schematic illustration of this process is given in Figure IV-3-1.

NOTE: Specific operating procedures prepared and controlled by Process Engineering shall be followed when preparing a shipment, in addition to this general procedure.

3.2.1 Definition of Material

1.5)

 \bigcirc

 \bigcirc

...

Define the material to be shipped in the following manner.

- 1. List the radionuclides that are present (e.g., $^{239}\mathrm{Pu},~^{233}\mathrm{U},$ and $^{137}\mathrm{Cs}).$
- Determine the level of radioactivity present in terms of curies.
 If fissile radioactive material (49 CFR 173.403(j)), also determine
 fissile quantity in terms of grams. Determine if the material
 qualifies as a hazardous substance, RQ, see 171.8 and 171.101
 Appendix.
- 3. Determine if material will be shipped as normal form or special form (49 CFR 173.403(s) and (z)).

M

U)

45₁,71,

WHC-CM-2-14 Part IV, REV 0 29 of 47 August 1, 1988




Figure IV-3-1. Offsite Radioactive Material Shippers Guide.

- 4. If normal form, determine the physical form (e.g., solid, liquid, or gas) and the chemical form (e.g., nitrate, oxide, elemental, etc.) of the radioactive material.
- 5. Determine if other hazardous materials are present or if other hazardous characteristics are exhibited (e.g., corrosive, flammable liquid, oxidizing materials, etc.).
- 6. Identify appropriate A_1 or A_2 values for radionuclides contained.
 - a. Determine A_1 values for radionuclides in special form (49 CFR 173.433, 173.435).
 - b. Determine A₂ values for radionuclides in normal form (49 CFR 173.433, 173.435).

NOTE: Tables IV-3-1 and IV-3-2 list A_1 and A_2 values for commonly shipped radionuclides in special form and normal form, respectively.

- 7. Determine quantity category. Quantity category is based on the radionuclides contained, their A_1 or A_2 values as appropriate, and the number of curies to be packaged in each container (e.g., cask, box, drum). See the following sections of CFR for the quantities listed.
 - o LSA Material, 49 CFR 173.403(n)
 - o Limited quantity, 49 CFR 173.403(m) and 49 CFR 173.421-.424
 - o Type A Quantity, 49 CFR 173.431(a)
 - o Type B Quantity, 49 CFR 173.431(b)
 - o HRCQ, 49 CFR 173.403.(1)

(N.

Ln

U?

 $\mathcal{C}\mathcal{I}$

NOTE: Tables IV-3-1 and IV-3-2 list limiting values for each category, in terms of curies, for commonly shipped radionuclides in special form and normal form, respectively.

3.2.2 Shipping Containers, Packaging and Transport

- Select a shipping container based on the following considerations:
 - a. The determinations of Section 3.2.1
 - b. Need for shielding and/or cooling
 - c. Size, shape, and weight of material to be shipped

HAZARDOUS MATERIAL PACKAGING AND SHIPPING

1.3

LO

Ln \bigcirc

 \bigcirc ?" W

RADIOACTIVE MATERIAL SHIPMENTS

Manual Section Page Effective Date

WHC-CM-2-14 Part IV, REV 0 31 of 47 August 1, 1988

Quantity Category	Limited Quantity ^{2,3}	Type A Quantity ^{2,4}	Type 8 QuantityS HRCQ6		Low Specific Activity Material LSA ⁷
Radionuclides	≤10 ⁻³ A ₁	≤A ₁	>A ₁	, A×000,E≤	Activity program of matrix
241Am	0.008	8	>8	24,000	N/A
243Am	800.0	8	>8	24,000	N/A
14C	1	1,000	>1,000	30,000	N/A
60 ⊂ o	0.007	7	>7	21,000	N/A
137 C s	0.03	30	>30	30,000	N/A
238p _U	0.003	3	>3	9,000	N/A
239PU	0.002	2	>2	6,000	N/A
246PU	0.002	2	>2	6,000	N/A
241PU	1	1,000	>1,000	30,000	N/A
242ptj	0.003	3	>3	9,000	N/A
⁸⁹ Sr	0.1	100	,>100	30,000	N/A
⁹⁰ Sr	0.01	10	>10	30,000	N/A
M.F.P.	0.01	10	>10	30,000	N/A
2331/J	0.1	100	>100	30,000	N/A
235U	0.1	100	>100	30,000	N/A
238(J	Unlimited	Unlimited	Unlimited	30,000	N/A
U _(NAT)	Unlimited	Unlimited	Unlimited	30,000	N/A
U(ENR <28%)	Unlimited	Unlimited	Unlimited	30,000	N/A
U _(ENR >20%)	0.1	100	>100	30,000	N/A
U _(depleted)	Unlimited	Unlimited	Unlimited	30,000	N/A

NOTE: All valves listed are in curies (Ci) unless otherwise stated.

PS83-3228-4

¹For mixtures of radionuclides, the most restrictive values for any one member of the mixture, establishes the mixture limiting values. (Exceptions, see 49CFR 173.433(b)).

²All values indicated, limit the activity within a given package.

³For excepted instruments and articles see 49CFR 173.422,173.423, 173.424.

⁴Maximum activity values, if exceeded are Type B Quantity.

SPackage contents, restricted by Package Approval Documents only (e.g., SARP, COC).

⁶Highway Route Controlled Quantity (HRCQ) (Minimum values listed).

⁷Not applicable to special form material.

IL!

RADIOACTIVE MATERIAL SHIPMENTS

Page Effective Date

Quantity Category	Limited Quantity ^{2,3,4}	Type A Quantity ^{2,5}	Type B Quantity ⁶	HRCQ ^{6,7}	Low Specific Activity Material LSA ⁸
Radionuclides	≤ 10 ³ A ₂	≤ A ₂	>A ₂	≥3,000×A ₂	Activity per gram of matrix
²⁴¹ Am	0.008mCi	0.008	>0.008	24	0.0001 mCi/g
243Am	0.008mCi	0.008	>0.008	24	0.0001 mCi/g
140	0.06	60	>60	30,000	0.3 mCi/g
€0Co	0.007	7	>7	21,000	0.3 mCi/g
137Cs	0.01	10	>10	30,000	0.3 mCi/g
238Pu	0.003mCi	0.003	>0.003	9	0.0001 mCi/g
239Pu	0.002mCi	0.002	>0.002	6	0.0001 mCi/g
240pu	0.802mCi	0.002	>0.002	6	0.0081 mCi/g
241pu	0.1mCi	0.1	>0.1	300	0.005 mCi/g
242P _U	0.003mCi	0.003	>0.003	9	0.8001 mCi/g
895r	0.01	10	>10	30,000	0.3 mCi/g
90Sr	0.4mCi	0.4	>0.4	1,200	8.005 mCį/g
M.F.P.	0,4mCi	0.4	>0.4	1,200	0.005 mCi/g
533Ü	0.1mCi	0.1	>0.1	300	0.005 mCi/g
235Մ	0.2mCi	0.2	>0.2	600	0.005 mCi/g
238U	Unlimited	Unlimited	Unlimited	30,000	Unlimited
U _(NAT)	Unlimited	Unlimited	Unlimited	30,000	Unlimited
U _(ENR < 20*+)	Unlimited	Unlimited	Unlimited	30,000	Unlimited
U _(ENR > 20*4)	0.1mCi	0.1	>0.1	300	0.005 mCi/g
U _(depleted)	Unlimited	Unlimited	Unlimited	30,000	Unlimited

NOTE: All values listed are in curies (Ci) unless otherwise stated.

PS83-3228-3

¹For mixtures of radionuclides, the most restrictive values for any one member of the mixture, establishes the mixture limiting values. [Exceptions, see 49CFR 173.433(b)].

²All values indicated, limit the activity within a given package.

¹Values shown for solids and gases. For liquids divide value shown by 10.

⁴For excepted instruments and articles see 49CFR 173.422,173.423, 173.424.

SMaximum activity values, if exceeded are Type B Quantity.

⁶Package contents, restricted by Package Approval documents only (e.g., SARP, COC).

⁷Highway Route Controlled Quantity (HRCQ) (Minimum values listed).

[#]See 49CFR 173.403(n) for additional specific criteria.

- d. Destination, mode of transport, and consignee's ability to handle the receipt of the shipment
- e. Availability of shipping containers

10

1.0

1.0

.,,

-

the state of

f. Regulations found in 49 CFR 173.400-478 and DOE Order 5480.3.

The "Hanford Container Directory" lists containers commonly used for shipping radioactive materials offsite. Additional guidance on container selection may be obtained from Traffic.

Containers selected must be either DOT specification containers loaded as specified in 49 CFR 173.400-.478 (unless exempted) or containers approved by NRC or DOE on which there is a current COC, and for which DOE-RL or WHC has been registered as a user. When NRC- or DOE-approved containers are used, a thorough review of the current COC and the associated SARP must be made to identify authorized contents, unusual packaging requirements, limitations, and/or administrative controls.

These requirements must be incorporated into appropriate internal procedures prior to initial use of the container. The above documentation must be maintained by the shipper for at least one year after last usage.

- 2. Obtain the container and inspect it. Work procedures, COCs, and SARPs list inspection requirements, as appropriate, and may require quality assurance/quality control verification.
- 3. Load the container with authorized contents only. Assemble and seal the package in accordance with appropriate procedures.
- 4. Arrange for a radiation survey of the package(s) to determine that smearable contamination limits (49 CFR 173.443) and radiation dose rate limits (49 CFR 173.441) are not exceeded.
- 5. Assure that if heat producing radionuclides are being shipped the thermal limits of 49 CFR 173.442 are met.
- 6. Determine the fissile class for each package based on an appropriate criticality analysis if packages contain greater than exempted quantities of fissile material (49 CFR 173.453).
- 7. Determine the Transport Index for each package as appropriate (49 CFR 173.403(bb)).
- 8. Mark and label each package as required by 49 CFR 172 Subpart D and 49 CFR 172 Subpart E, respectively. See Tables IV-3-3 and IV-3-4 for summary requirements.

HAZARDOUS MATERIAL PACKAGING	Manual	WHC-CM-2-14		
AND SHIPPING	Section	Part IV, REV 0		
RADIOACTIVE MATERIAL SHIPMENTS	Page Effective Date	34 of 47 August 1, 1988		

- Determine category and security requirements if SNM. (See DOE Order 5632.4 and WHC-CM-4-33, "Security Manual".)
- Schedule shipment in advance with Traffic, Transportation, and Safeguards and Security, where appropriate.
- 11. Complete an ORSR per instructions found in Part IV, Section 3.3 that follow. Send the completed ORSR, together with other pertinent papers or instructions, with the shipment to the WHC shipping facility, 1167 Building, 1100 Area.
- 12. Furnish appropriate placards to the carrier (see 49 CFR Part 172 Subpart F) or, if vehicle is equipped with permanent placards, assure that placards are turned to the proper hazards.
- 13. Assure that riggers or truck drivers are aware of any tiedown requirements named in the associated COCs, SARPs, work procedures, etc. It is the packager/shipper's responsibility to inspect and approve securing of all loads to assure tiedown requirements are met.

3.3 PREPARING OFFSITE RADIOACTIVE SHIPMENT RECORDS (ORSR)

LO

()

The following instructions are keyed to number blocks on a specimen copy of the ORSR (Exhibit IV-3-1).

3.3.1 Shipment Instructions Section Completed By Originator

- 1. Provide a complete shipping address. (NOTE: Post office box numbers are not acceptable as an address unless routing is by parcel post.) The shipment is to be directed to the attention of an individual whose name must appear after the complete address. Check the DOE Directory of Reporting Identification Symbols (RIS book) to assure proper address for receipt of materials (usually different from mailing address).
- 2. Check the box identifying the originating contractor.
- 3. Indicate if the shipment is prepaid or collect. Recommend the mode of transport.
- 4. Print site carrier's name, payroll number and vehicle number.

3.3.2 <u>Shipment Description Section Completed By Originator/Shipper</u>

1. Check appropriate box to indicate proper shipping name and UN identification number for each package (e.g., Radioactive Material, Fissile n.o.s., UN 2918).

MARKING REQUIREMENT SUMMARY*

PACKAGE MARKING CHECKLIST

- PROPER SHIPPING NAME (e.g. RADIOACTIVE MATERIAL n.o.s.)
- IDENTIFICATION NUMBER (e.g. UN2982)
- CONSIGNEE'S/CONSIGNOR'S NAME AND ADDRESS
- GROSS WEIGHT (IF >110 lbs (50 kg)
- TYPE A OR TYPE B AS APPROPRIATE
- USA (IF FOR EXPORT)


-

In

 \Box

, 677- *E

- DOT SPECIFICATION NUMBER OR CERTIFICATE OF COMPLIANCE NUMBER
- THIS SIDE UP/THIS END UP (WHEN INSIDE PACKAGE CONTAINS LIQUID HM)
- *FOR DETAILS SEE 49CFR172 SUBPART D



PS8307-37

Manual Section Page Effective Date

WHC-CM-2-14 Part IV, REV 0 36 of 47 August 1, 1988

LABELING REQUIREMENT SUMMARY*

- 1. NO RADIOACTIVE LABELS REQUIRED ON PACKAGES CONTAINING.
 - . LIMITED QUANTITY RAM, INSTRUMENTS AND ARTICLES
 - . LSA MATERIAL BEING SHIPPED EXCLUSIVE USE
- 2. EMPTY LABELS GO ON EMPTY RAM SHIPPING CONTAINERS

EMPTY

3 LABEL PACKAGE FOR EACH HAZARO CLASS CONTAINED (e.g. RADIOACTIVE, CORROSIVE)





4. USE DOT APPROVED LABELS ONLY.

£ .

LO

17

 \bigcirc ~ ·

5. SELECT PROPER RADIOACTIVE LABEL USING THE FOLLOWING CRITERIA:



WHITE !

- 1. ≤0.5 meem/hr AT SURFACE OF PACKAGE
- 2. NOT FISSILE CLASS II OR NI
- 3. NOT HIGHWAY ROUTE CONTROLLED QUANTITY





YELLOW H

- 1. >G.5 mnem/hr SURFACE OF PACKAGE 2. ≤50 mnem/hr SURFACE OF PACKAGE 3. ≤1.0 mnem/hr AT 1 METER
- 4. NOT FISSILE CLASS IS
- 5. NOT HIGHWAY ROUTE CONTROLLED QUANTITY 6. FOR FISSILE CLASS II. T.I = 1.0



YELLOW M -

- 1. >50 mism/hr SURFACE OF PACKAGE
- 2. >1.0 mrem/hr AT 1 METER
- 3. FOR FISSILE CLASS II, T.I>1.0
- 4. FISSILE CLASS UI
- 5. HIGHWAY ROUTE CONTROLLED QUANTITY
- 6 PROPER DATA MUST BE ENTERED ON EACH LABEL (a.g. CONTENTS 239pu; ACTIVITY 2 CI; T.I.3)
- 7 LABELS MUST BE PLACED ON OPPOSITE SIDES OF THE PACKAGE IN UNOBSCURED POSITIONS.
- 8 APPLY SPECIAL NOTIFICATION LABELS AS APPROPRIATE In.g. CARGO-AIRCRAFT ONLY: DANGEROUS WHEN WET, ETC.)
- . *FOR LABELING DETAILS SEE 49CFR172 SUSPART E

Table IV-3-4. Labeling Requirement Summary.

HAZARDOUS MATERIAL PACKAGING AND SHIPPING

O

M ம்

-. .

 \bigcirc 14.7 Page

RADIOACTIVE MATERIAL SHIPMENTS

Manual Section Page Effective Date

WHC-CM-2-14 Part IV, REV 0 37 of 47 August 1, 1988

		CONTRACTOR CHIPSET IN THE COURSE
ĺ	(3.3.1) SHIPPING INSPECTION SECT	OFFSITE RADIOACTIVE SHIPMENT RECORD TION - EXTERIOR INSPECTION PERMITTED -
널	Company	Contractor: (2) Ship: Prepaid Collect Via:
SHIPPING INST	Address	PNL KEH WHC Motor-Rail Air Psgr
Man	City, State, Zip	Site Carrier 3 Excl. Use
£	Attention:	PR No. Veh. No. UPS Sur.
_	113.31	(2) For Normal Form
	Proper Shipping Name UN Number Nadioactive Material,	Material Form: ☐ Special (A1) ☑ Normal (A2) Identify:
	i i empry rackages 😑 on seco i j	Labels Applied Material Category Physical Form Empty Solid Liquid Gas
	2. Low Specific Activity, n.o.s UN 2912 Specific Activity, n.o.s. UN 2910 UN 2	Radioactive LSA Low Specific Act (CSA) Chemical Form
	4. N.O.S. 1 UN 2982 UN 2988	White I Umited Quantity Metal Oxide Yellow II 3 Tyge A Quantity Elemental Nitrate
	6. Special Form, n.o.s. UN 2974	Yellow III Type A Quantity
	7. Instruments & Articles	☐ Danger (Air Cargo) ☐ Highway Route
İ	TYPE PACKAGE CONSTRUCTION	Secondary Controlled Quantity
	Strong Tight Box, FB	Non Fissile No Yes Classified (8) Unclassified
	TypeA Wood	Fissile Exempt
	Type8	Fissile II (6) Category Pu, EU > 19 NU, DU > 1 Kg
3	1 후 '/=='(*) 후 [Grams Fissile Gr
I de	5 Other	Grams Fissile Category III External Cask Temperature (Max. 122* FLTL, 180* FEx. Use)
DESCRIPTION	Packaging conforms to appropriate packaging proceds	dure N/A Yes Container examined: No evidence of deterioration or damage Yes
F	Complies with O. O. T. packaging marking and labeling requirements	
SHIPMENT	Container acceptability documented (incl. 7A cert.)	
15	No. Pkgs. Model Package COC/Spec. No.	Sarial No Seal No. Isotopes CuriesPRG T, t Gr VVT.
	(3.3/2	2) SHIPMENT DESCRIPTION SECTION
1		
		inused (ines above) TOTAL
	(Packager may describe package in detail on one of un Originator's Signature Date	Organization Complete Cost Code (inc. end function)
L	(12)	
	of Parkage	Meter from Surface Smears of Outer Container 2 TRUCK LOAD OR EXCLUSIVE USE Surface: □ ≤ 200 mrem/hr (N + βγ)
Į	☐ ≤0.5 ormrem/hrtff+βγ) ☐ ≤0.5 or	mrem/hr $(N + B\gamma)$ $\leq 2.2 \text{ dpm } \alpha/cm^2$ @ 6 feet: $\leq 10 \text{ mrem/hr } (N + B\gamma)$
AREA MONITOR	Additional Date and Instructions (inc. Readings on Inte (3.3.3) AREA RADIATION MON	ternal Packaging) @ Cab
SEA.	Signature - Radiation Monitoring	3 Sidg. Survey No. Date
_		HORIZATION FOR SHIPMENT AND CERTIFICATION SECTION STORAGE: 1. Ltd. Qty. 3. Research or Medical Diagnosis Pkg. Dippensions
5	CERTIFICATION > Labels Applied (1
ERTIFIE	This is to certify that the above named materials are p	properly classified, described, packaged, marked and labeled, and are in proper condition for state, local and international regulations for the transportation of hazardous materials.
630	Authorized 2	Printed
L	1 Signature P 1 (-)	Name Name Name SECTION
[B. L. No. Oate Shipped E. T. A.	Routing . N/A (3) Placards
TRAFFIC	(1)	Yes No Route Plan
IB	Surveyed By 2 Date Approved West:	stringhouse Hanford Company (4)
_		54-6000-088 (4/88)

- Identify material form (e.g., special or normal). If normal form, the physical and chemical form of the material must also be identified by checking the appropriate boxes.
- 3. Identify labels applied to the package(s) including secondary hazard labels (49 CFR 172 Subpart E).
- Identify quantity category (e.g., limited quantity, Type A, Type B, HRCQ).
- 5. Identify type of package (e.g., strong tight, Type A, Type B) and identify the type of construction (e.g., wood or steel box).
- 6. Make fissile declaration by checking appropriate box. If fissile, check class and indicate total grams of fissile material.
- 7. Indicate if SNM is present by checking appropriate boxes. (See DOE Order 5632.4.)

L!

Parce

 \bigcirc

Ţ,

- 8. Indicate if shipment is classified or unclassified and if consignee is authorized to receive this material. Check if signature security service is required, indicate criteria used for this determination. Check if security escorts are required.
- 9. Indicate external cask temperature if over ambient temperature.
- 10. Answer self explanatory questions and identify shipping document number and authorization number.
- 11. Identify each package and its contents by inserting the required data. This information must be detailed and complete.
 - NOTE: The activity in curies must be converted to becquerels for shipment of radioactive material by air.
- 12. Sign and date the form and identify the originator's organization and cost code.

3.3.3 <u>Area Radiation Monitoring Section Completed By Radiation Protection Technologist</u>

- 1. A Radiation Protection Technologist (RPT) surveys each package and records dose rates at the surface and at 1 m. Shipments with multiple containers must show highest readings found. Smears are taken on each package and the data is entered. Packages must not be released for shipment until Federal standards are met (49 CFR 173.443 and 173.441).
- When truckload or exclusive-use shipments are made, the transport equipment is surveyed and required data recorded. Show actual readings.

HAZARDOUS MATERIAL PACKAGING	Manual	WHC-CM-2-14
AND SHIPPING	Section	Part IV, REV O
•	Page	.39 of 47
RADIOACTIVE MATERIAL SHIPMENTS	Effective Date	August 1, 1988

The RPT signs and dates the form and records the survey number.

3.3.4 <u>Authorization for Shipment and Certification Section Completed by Certifier</u>

- If shipment is to be by air, indicate if shipment is authorized for passenger aircraft and under which criteria it qualifies (e.g., limited quantity, T.I. ≤3.0, etc.). If not authorized for passenger aircraft, indicate the "Danger, Cargo Aircraft Only" labels have been applied.
- 2. If shipment is to be by air, the package dimensions must also be provided.
- 3. The authorized signature in this section certifies that materials are properly classified, described, packaged, marked, and labeled, and are in proper condition for transportation all in compliance with the DOT regulations. The authorizing signature must be one of a delegated employee who has passed the Certification of Hazardous Material Shipments course. Retraining in this course is required every 2 years to retain signature authorization.

3.3.5 Approved for Offsite Shipment Section Completed By Traffic

- 1. Traffic records the bill of lading number, the date shipped, the ETA, and routing information.
- 2. The 1100 Area RPT signs and dates the form, indicating concurrence of area radiation monitoring data.
- 3. Traffic indicates whether placards or route plans are required by checking appropriate boxes.
- 4. Traffic signs and dates the form indicating final shipment approval.

3.4 RADIOACTIVE MATERIAL TRANSPORTED BY THE TRANSPORTATION SAFEGUARDS DIVISION, U.S. DEPARTMENT OF ENERGY, ALBUQUERQUE OPERATIONS OFFICE

These operating instructions establish specific practices for the shipping and receiving of radioactive shipments transported by Transportation Safeguards Division (TSD) of DOE-ALO.

3.4.1 Responsibilities

1

111

 \bigcirc

The Manager, DOE-ALO, manages the Transportation Safeguards System for domestic shipments of nuclear explosives, Category I quantities of SNM (excluding Naval reactor core shipments), classified configurations of Category II quantities of material when requested by responsible outlying program managers, and any form of ²³⁸Pu in excess of 5 g. This responsibility is executed by the Director of the TSD.

RADIOACTIVE MATERIAL SHIPMENTS

Effective Date /

The DOE-RL delegated Westinghouse the Operational Contact responsibility for SST transport between the TSD and Hanford Site contractors. The Operational Contact shall exercise total control of all TSD movement at the Hanford Site and shall keep DOE-RL Safeguards Branch informed of all activity.

The following individuals function as Operation Contacts:

- o D. V. Kelley, 373-2541
- o J. Washburn, 373-2393
- o C. D. Hansen, 376-7494

Duties of the Operational Contact include the following:

- 1. Coordinate all SST shipments at the Hanford Site. This includes preparation, classification, and submission of shipment requests and other communications concerning individual movements directly to TSD via secure communications with a copy to DOE-RL.
- Maintain appropriate records of correspondence relating to TSD services.
- 3. Submit an annual forecast of Hanford Site SST requirements to DOE-RL.
- 4. Compare the annual forecast to actual and planned use of TSD services on a quarterly basis for RL information, and as a tool to evaluate the need to update the annual forecast.
- Provide assistance to TSD couriers.
- 6. Provide services defined by the TSD Operating Principles Document or those dictated by TSD.

3.4.2 General Procedures

¢".

(1)

()

The following general procedures shall be observed.

1. Information concerning movement of TSD vehicles is classified "Confidential-National Security Information" and shall be provided only to authorized recipients on a need-to-know basis. Personnel administering the SST at Hanford must possess a Level 2 or 3 clearance and those receipting for material, custody of vehicles and equipment or shipping material on a courier receipt must be authorized to do so by TSD upon the recommendation of DOE-RL. The movement of materials associated with defense weapons programs is classified "Secret-Restricted Data" and must be documented and handled accordingly.

Manual Section Page Effective Date WHC-CM-2-14 Part IV, REV 0 41 of 47 August 1, 1988

RADIOACTIVE MATERIAL SHIPMENTS

2. Personnel who execute Radioactive Shipment Records (Onsite (RSRs) or Offsite (ORSRs)) for the movement of the SST while on the Hanford Site must hold the proper delegation of authority. Signature

Security Offices.

3. Shipments in the SST are exempt from "sabotage device/unauthorized personnel" searches before loading that are prescribed in DOE Order 5632.4.

cards for such personnel must be on file with the Contractor

3.4.3 Specific Receiving Procedures

The following specific receiving procedures shall be observed.

- 1. Formal notification of all inbound shipments will be sent to the Operational Contact before the delivery date. This notification will be received via classified message when the shipper requests TSD service. The TSD will provide the actual schedule of the SST and will provide all pertinent information about the shipment. When the TSD message is received, the Operational Contact will advise the DOE-RL contractor representative of the arrival date and what materials are involved.
- 2. Movement of SSTs are classified. Care should be taken to prevent the dissemination of schedules and changes by unsecured methods. A classified system established by Security is used to accommodate communications of schedules and changes.
- 3. The SST may arrive after normal working hours. The SST is authorized to seek safe haven at any government facility and may come and go without local coordination or documentation. Materials moved via the SST must meet specific criteria outlined in DOE Order 5632.4 to be accepted for this method of transportation. Accountability for these materials is transferred through use of Form DOE/NRC 741. Material custody is transferred by special courier receipt, therefore, normal receiving procedures are not appropriate. The shipments are not stopped at the 1100 Area, are not received by a Material Function storekeeper, and are not required to have a radiation survey check at the 1100 Area.
- 4. The SST will proceed either to the 300 Area for safe haven in the 308 protected area or to the Plutonium Finishing Plant (PFP) protected area, depending on who the consignee is and where the material is to be offloaded or loaded.
- 5. When the shipment is consigned to PNL or WHC at the 300/400 Area, the contractor field representatives will arrange for radiation survey and personnel for unloading. The WHC riggers move the materials from the SST to a designated place under escort where the authorized custodians accept the material.

2000

C)

HAZARDOUS MATERIAL PACKAGING
AND SHIPPING
Section
Page
FADIOACTIVE MATERIAL SHIPMENTS

Manual
Section
Page
42 of 47
RADIOACTIVE MATERIAL SHIPMENTS

Effective Date
August 1, 1988

When the shipment is consigned to the 200 Areas, there are two designated points for unloading:

- a. Shipment consigned for waste disposal will be off-loaded and received by burial grounds personnel at the 200 West Disposal Site staging area. The staging area is a materials handling area consisting of a large asphalted pad with a truck loading dock capable of handling three trailers. Trailer-to-trailer and trailer-to-loading dock operations may be completed at the staging area. The burial ground manager on duty will arrange for radiation monitoring, riggers, and burial ground personnel as required based on arrival time of the SST. Close coordination between the SST Operational Contact and the burial ground manager is essential to maintain effective utilization of personnel. The SST shipments to the burial grounds are infrequent, therefore, must be performed in addition to other scheduled work and completed within the shortest possible delay to other activities.
- b. Shipments consigned to the PFP will be unloaded at the 2736-ZB Shipping and Receiving Facility. Product handling custodians must coordinate their activities to allow scheduling of personnel to monitor, receive, and handle unloading operations.
- 6. If no authorized contractor recipients are present, the Operational Contact may receive material and arrange for temporary custody and security as circumstances require.
- 7. If the SST does not have a return load, the custodian of the delivered material will execute Form AL-75, "Shipment Certification" certifying that radiation dose rate levels and removable contamination are within the limits prescribed in 49 CFR 173.443. A radiation survey must support this certification, 49 CFR 173.441.

3.4.4 Specific Shipping Procedures

The following specific shipping procedures must be observed.

- 1. The TSD preplans each of its trips based on the shipper's request for services and issues a plan to the convoy leader on or before departure from the point of origin. The preplan may provide for transloading and for storage enroute to destination. Changes are not permitted without the approval of the TSD. Changes in type and quantity of material, number, type and size of container, and destination should be scheduled two weeks in advance of loading to ensure acceptance by TSD.
- 2. The packager will perform the following duties:
 - a. Prepare the material transfer documents and unclassified "gate pass"-type of ORSRs before SST loading.

RADIOACTIVE MATERIAL SHIPMENTS

- b. Witness and approve the loading configuration and the tiedowns.
- Ensure that radiation survey data for packages and vehicle is on the ORSR, and that Form AL-75 "Shipment Certification" is executed after the shipment has been released by the Operational Contact and made a part of the shipping papers.
- Approve release of shipment to the convoy commander, and distribute copies of the ORSR.
- Use a special receipt provided by the DOE courier to document and transfer custody to the TSD. The TSD two-man rule requires two couriers to sign every receipt for SNM. Custody transfer receipts are maintained in the shipment case file.
- Traffic will perform the following regulatory compliance duties:
 - a. Assign a shipment number to the ORSR.
 - Inspect the exterior of each package to verify that the package is in good order and properly marked, labeled, closed, and sealed.
 - Verify that the packaging meets the applicable regulations for shipment via the SST and that package data is accurately entered on the transfer documents and ORSR.
 - Sign the ORSR in the "Approval for Shipment" block.
- Procedures for requesting transportation services by the TSD via SST are found in DOE-ALO Order AL-56XA, "DOE Transportation Safeguards System", and repeated here for user convenience.
 - The nuclear materials control officers for DOE-RL contractors must submit a TSD Standard 19-point request for SST services to the Operational Contact through the appropriate classified document control channels.
 - The request must reach the TSD Planning Branch, Albuquerque, New Mexico at least 14 days before the requested date of Emergency requests may be submitted at any time and the Planning Branch will try to accommodate the request.
 - c. All requests are classified. Defense weapons material must be classified "Secret, Restricted Data," and with few exceptions, the movement of non-weapons material will be classified "Confidential, National Security Information."

15 5

1.17 \bigcirc

10.17

100

_5*×

(*)

HAZARDOUS MATERIAL PACKAGING	Manual	WHC-CM-2-14
AND SHIPPING	Section.	Part IV, REV O
	Page	44 of 47
RADIOACTIVE MATERIAL SHIPMENTS	Effective Date	August 1, 1988

5. The TSD Standard 19 point request to be completed for services follows:

ITEM

5

(1.1

INFORMATION REQUIRED

- 1. Material type (AEC Appendix 74010C, Part 13.F, page 7)
- 2. Available date and time (do not indicate "as soon as possible").
- 3. Level of classification and type of information (when appropriate).
- Transport index per container.
- 5. High explosive content. Enter net weight and class of explosives in the shipment. Enter the word "none" if appropriate.
- 6. Consignor (RIS Symbol) and pickup point (location/area/building).
- 7. Number of containers.
- 8. Shipment I.D. This shall be the unique identifier formulated by the consignor or his DOE organization as needed for computerized recordkeeping.
- Gross weight per container.
- 10. Consignee (RIS Symbol) and delivery point (location/area/building).
- 11. Item common name (when one exists).
- 12. Composition code (AEC Appendix 7401-C, Part II 13.G., page 7).
- 13. Deadline delivery date and time (do not indicate "as soon as possible").
- 14. Justification for TSD courier safeguarding. Designate the appropriate category by paragraph number (i.e., 1.c., 2.b.) as specified in Chapter IV of this order.
- 15. Material gram weight per container.
- 16. Type container to be used and dimension. Dimensions not required when this data is available in the publications: "Directory of Packagings for Transportation of Radioactive Materials" (WASH 1279) and "Directory of DOE Certificates of Compliance for Radioactive Material Packaging" however, dimensions must be provided when more than one container external size is shown in WASH 1279 under one DOT identification or when shown in the TSD maintained document, "Component/Product Hazardous Material Record."

HAZARDOUS MATERIAL PACKAGING
AND SHIPPING

RADIOACTIVE MATERIAL SHIPMENTS

Manual
Section
Page
45 of 47
Effective Date

August 1, 1988

- 17. Special handling requirements (when temperature control is required, specify acceptable range).
- 18. Budget activity program code.
- 19. DOE/NRC Form 741 transfer series data is recorded in Block 3 of form when nuclear materials are to be shipped. This can be provided orally subsequent to initial input.

The planning branch, TSD, will review the request for transportation services and schedule movement of the material as close to the requested dates as the availability of personnel and equipment will allow.

3.4.5 Shipping Papers

(m)

1000

Public Law 86-710 and 49 CFR 173.7(b) exempts DOE-couriered shipments in the SST from commercial shipping paper requirements that describe the hazardous material being transported. For internal control purposes however, DOE issues a Courier Receipt that, together with Nuclear Material Transfer Documents, serve as shipping papers, all of which are classified. An unclassified "gate pass"-type document will record the radiation survey to allow the SST to exit from protected areas. A standard ORSR form will serve that purpose when properly executed.

The following instructions are keyed to numbered blocks on a specimen copy of the ORSR (Exhibit IV-3-2). These forms shall be prepared for each shipment offered for movement.

- 1. The Shipment Instruction Section is to be completed by the Originator.
 - a. Enter the words "See file (#_____) and assign a file number.
 - b. Check box for originating contractor.
 - c. Check box for DOE vehicle.
- 2. The Shipment Description Section is completed by the Originator.
 - a. Check box for Radioactive material, n.o.s, UN 2982.
 - b. Identify labels on containers.
 - c. Identify quantity category (e.g., Type A, Type B, etc.).
 - d. Check normal form or special form as appropriate. Disregard physical and chemical form questions.

HAZARDOUS MATERIAL PACKAGING AND SHIPPING

(° "

V)

LD.

 \bigcirc 7

(,")

4

RADIOACTIVE MATERIAL SHIPMENTS

Manual Section Page

WHC-CM-2-14 Part IV, REV 0 46 of 47

Effective Date

August 1, 1988

_						SHIPM					SECTIO								_ ,
SHIP TO: OFFSITE RADIOACTIVE SHIPMENT RECORD - EXTERIOR INSPECTION PERMITTED -																			
ᄩ	Company		1.a)			 			ATERIC		.b)								\dashv
SHIPPING INST.	Address SEE FILE (#					PNL DKEH WHO STATE					_ `	paid		.ollect	Via:	ŀ			
3	l						Site Cari	rier				-	(1.c)	= "	tor-Rail !. Use		Air Ps	-	
3	!	, Zip				-						_		=	E Veh.		Mail	, 90	ŀ
	Attention:						PR No		- 1	Veh. M	Vo.			UP:	Sur.				.
		pping Name		UNN	lumber	Materi	al Form:		Speci	al (A)	(2.d)	Norm	1al (A2)		Normal	Form		1	٦
		e Material,					Applied				terral Ca				ntify: vs:cal For	_			
		y Packages pecific Activ	ity. n.o.s	_	N 2908 N 2912	1	npty				Empty		(2.c	\ I'	Solid		Liquid	☐ Gas	. 1
		d quarants			N 2910		idioactiv hite l	PLSA			Low S	pecific A	ACT. TESA) Ch	emical Fo	 ITM	-	_	- 1
	4. N.O.S. 5. Fissile	, ,)		N 2982 N 2918	III v	ellow II	(2.t)	IB		d Quan Quant	-] Meta		_	Oxide	İ
Ì	6 Specia	l Form, n.o.		<u> </u>	N 2974		ellow III one			占		Quant			ther		ш,	litrate	ı
i	7. Instru 8.	ments & Art	icles		N 2911	🗖 🗅	anger (A		10)		Highw	ay Rou	te	٦	- Tries				
							E CLASS			1		illed Ot							4
1		ACKAGE		<u>INSTRUÇTI</u> Box, FB	ON		n Fissile	' 1		<u>SN</u> No	<u>™</u> □ '	,	AL		ABILITY/		Unclas		
		ong Tight pe A		wood		THE FIR	sile Exec	-07		NO <1 g	_		_		rized to ri	eceive	Hus qty		
İ		ре В		Steel		☐ fo	sile i (2	.f)	=	-	ory I		g. Securi				.g) №		
_		pe B (U)	. =	Drum	- 1	=	sile II 🔪 sile III	7	=		ory II		i, EU > 1 curaty E:			_ `	1 K حريد Not.!	- =	
₽		pe B (M)	_ =	Cask Other	1	Grams		ļ	_	•	jory III	- ⊢			pperatur	_	h) N		\dashv
훙	(2,	.e)									,,				180°F Ex	UseX	<u> </u>	**	
SHIPMENT DESCRIPTION	Packaging	conforms to	appropr	ate packa	ging proc	edure [N/A			Conta	iner exa	mined:	No evic	lence o	f deterior	ration	or dama	ge 🔲 Yes No 📋 Yes	
IE NO	labeling re	contement			(り!	N/A		Yes				_		via seat uthorizat		_		
3		cceptability				Seria	N/A		Yes eal No	קקויונ	1								
×	No Pkgs	Model Pa	ckage	COCSo	ec vio	Seria	I IVQ.	,	ęai wo		<u> </u>	Isoto	pes		CunesiP	Kg	T. I.	Gr Wt	\dashv
		6				SE	E ATT	ACHI	וו מי	CTI	NG		······			-			ᅱ
		(2)						,,,,,,,											\dashv
						SHIP	ENT D	ESCI	RIPTI	ON	SECTI	ON				\neg			ヿ
																			ヿ
		· · · · · ·														$\neg \vdash$			\neg
	(Packager	may describ	e packagi	e in detail	on one of	unused l	nes abov	e)				TOTA	L.			\neg			\neg
	Originator	's Signature			Date		Orga	nizat	ian					Comp	lete Cost	Code (inc. enc	function)	\neg
-	Surface Do	en Paro		Darr	Rate at 1	Marerie	J. S., e4-	re l	Sme=r*	of O:	ster Cont	PIDS!		70	UCK LOA	ם מס	XCI 1160	E LICE	\dashv
E	of Package	: (;	3.a)	of Pa	ckage			l	☐ ≤.	22 d;	pm BY/c	m²	Su		S 20				
AREA MONITOR		mrem			0.5 or				<u></u> ≤:	2.2 d	pm avem	2	@	6 feet	<u>□</u> ≤ 10	mrem:	hr (N + f	β γ)	
M		RADIAT					ickaging)					@	Cab Sleepe	≤ 2.0 r	mrem	/hr (N +	8 Y)	
ARE/		Radiation N			$\overline{}$			Blo	dg. •			Survey	No			Date			7
L		- ·		(3	.ь)											L			
_			_ _	. = -		HORIZAT					•				a				—
~	AIR TRANS CERTIFICAT			y: 🔲 Dan s Applied	ger Pas	senger:	[] 1. L [] 2. ≤				search or man Mei			OSIS	Pkg, Dim	ension	15		
CERTIFIER	This is to ce	rtify that th	e above r	amed ma	teriais are	property	classifie	d, des	cribed.	packa	aged, ma	rked at	nd label	ed, and	are in pr	operco	ndition	tor	\dashv
#	transporta: Authorized	tion, accordi		applicable	e federal.	state, loc	al and in Printei		lional n	egula	tions for	the tra	nsporta	tion of	nazardou	is mate	erials.		
	Signature	<u> </u>	4.b)	·			Name		1_			-ATT-	<u> </u>		Date	•			_
	B. L. No.	· · · · · · · · · · · · · · · · · · ·	Date Sec	nond 1	E, T. A.	APP			FFSITE	SHIPA	MENT SE	C110	AT .		7			carde	\neg
F.	J. C. 11U,		Date Shi	ppea	z. 1. A.		Rout	រោជ្ជ							□ N/A	_ [⊒ Yes	<u>cards</u> ☐ No	
TRAFFIC	Surveyed B	у	Date			d for Ship					(5)		i	Date				te Plan	
ш		1		لـــــــــــــــــــــــــــــــــــــ	Wes	tinghous	e Hanfo	d Con	npany		اليك.					50.50	00-088 (□ No	

Exhibit IV-3-2. Specimen Copy of an Offsite Radioactive Shipment Record for Safe, Secure Trailer Shipments.

- e. Identify package types (e.g., strong tight, Type A, Type B, etc.). Indicate type of container construction (e.g., wood, steel).
- f. Disregard fissile class and SNM questions.
- g. Identify security requirements.
- h. Indicate external cask temperature, if above ambient.
- i. Answer questions as appropriate. Provide shipping document number and authorization number.
- j. Enter words "see attached listing."

6,50

Q

LO

 \mathbb{C}^{3}

\$. · · ·

Janes.

-

 \bigcirc

....

- k. The manager of the group packaging the material or the manager's delegate signs and dates form and enters complete cost code information.
- 3. The Area Radiation Monitoring Section is completed by the Radiation Protection Technologist (RPT).
 - a. The RPT surveys each package and records dose rates at the surface and at 1 m. Shipment with multiple containers must show highest readings found. Smears are taken on each package and this data is entered. Packages must not be released for shipment until Federal standards are met (49 CFR 173.443 and 173.441).
 - b. The RPT signs and dates the form and records the survey number.
- 4. The Authorization for Shipment and Certification Section is completed by the Certifier.
 - a. Disregard air certification questions.
 - b. The authorized signature in this section certifies that materials are properly classified, described, packaged, marked and labeled, and are in proper condition for transportation. The authorized signature must be one of a delegated individual that appears on a list of approved signatures maintained by Traffic for employees who have passed the "Certification of Hazardous Material Shipments" course.
- 5. The Approval for Offsite Shipment Section is completed by Traffic.

THIS PAGE INTENTIONALLY LEFT BLANK

WESTINGHOUSE HANFORD COMPANY

Manual Section Page WHC-CM-2-14 Part V, REV 0 1 of 6

Effective Date

August I, 1988 Procurement and

Organization

Materials Management

HAZARDOUS MATERIAL PACKAGING AND SHIPPING

TITLE:

 \Box

بونہ ۔ آ

100

Approved by

D. K. Quigley, Manager,

SHIPPING AND RECEIVING HAZARDOUS MATERIAL IN THE 1100 AREA

Procurement and Materials Mgmt

1.0 PROCUREMENT AND MATERIALS MANAGEMENT AS SHIPPER/RECEIVER FOR DOE-RL

The WHC Procurement and Materials Management function (PMM) is responsible for checking and verifying material shipments before they leave the Hanford Site to assure compliance to Federal regulations. This function is also designated "shipping agent" for other Hanford Site Contractors, in the offsite shipment of hazardous materials other than radioactive materials.

As the shipper for DOE-RL or agent for other contractors, PMM will perform the following tasks:

- 1. Receive shipments of hazardous materials or shipments requiring special handling from the packager's site to the 1167 shipping facility at the request of the packager. Only those packages accompanied by the Offsite Radioactive Shipment Record (ORSR), Uniform Hazardous Waste Manifest (UHWM), or Hazardous Material Shipment Record (HMSR) form which has been completed, signed, and certified that the package is in proper condition for transportation offsite will be accepted for onsite pickup and delivery to 1167.
- 2. Verify the radiation survey data recorded on the ORSR are correct, or that the HMSR or UHWM has a radiation release.
- 3. Inspect the exterior of the package visually and verify the package is in apparent good order, the packaging data have been correctly recorded on the ORSR, UHWM or HMSR, the delivery address on the address label is appropriate for the mode of transportation selected, and the package is properly closed and sealed.
- 4. Analyze the data on the ORSR, UHWM or HMSR and verify that the material, as packaged for offsite shipment, meets the applicable regulatory requirements for the packaging, marking, and labeling of such material and is, therefore, in proper condition for transportation via the mode selected.
- 5. Arrange with the packager to correct any nonconforming detail of the shipment. Document minor exceptions internally after resolution. Issue a Variance Report for more serious infractions or persistent minor exceptions citing exceptions to the packager with a copy to DOE-RL Projects Management Division (DOE-RL PMD) after correction has been made.

HAZARDOUS MATERIAL PACKAGING AND SHIPPING	Manual Section	WHC-CM-2-14 Part V, REV O
	Page	2 of 6
SHIPPING AND RECEIVING HAZARDOUS MATERIAL IN THE 1100 AREA	Effective Date	August 1, 1988

- 6. Select mode of transport to accommodate the type of material to be shipped and, if possible, the desired delivery date.
- 7. Provide temporary storage in the 1167 Building for other than exclusive-use shipments of hazardous materials awaiting transport inbound or outbound.
- 8. Prepare shipping papers (e.g., bills of lading, air bills, etc.) in accordance with applicable DOT and DOE directives.
- 9. Schedule commercial carriers to load, other than exclusive-use shipments of hazardous materials, at the 1167 Building and elevate packages to the carrier's equipment. The carriers will secure the loads for shipment.
- 10. Schedule commercial carriers to load exclusive-use shipments of hazardous materials and/or Category II quantities of SNM at the packager's site. Traffic will inspect and approve tiedowns.
- II. Assure that vehicles are placarded for the appropriate hazards, as required by regulations.
- 12. Process and ship packages daily if they are received at the PMM shipping facility in the 1100 Area at the times shown in the following schedule:

Schedule for Shipments with Normal Handling

Routing	Due in Shipping
United Parcel	2:00 p.m.
Air Freight	2:00 p.m.
Motor-Freight (less than truckload)	2:00 p.m.

- 13. Notify the consignee, via teletype, of the shipping date, routing, carrier and estimated time of arrival (ETA). Follow the progress of the shipment enroute, expedite delaying factors, and apprise the consignee and originator of revised ETA, if necessary. Confirm actual delivery date and apprise DOE-RL PMD Management of that date.
- 14. Notify DOE-RL PMD of the shipment on the day it leaves the Hanford Site and provide DOE-RL PMD with copies of the bill of lading, the ORSR or HMSR, and the teletype to the consignee.

Traffic will return to the originator, copies of the ORSR, UHWM or HMSR, complete with any data added by Traffic, regarding the shipment.

15. Inspect packages for regulatory compliance prior to loading onto the safe secure trailer (SST).

- 16. Maintain on file, the Bureau of Explosives Pamphlets 6, 6A and 6C, and other guidance for developing blocking and bracing plans used in rail shipments. Also see tiedown guidelines found in Appendix C of this manual.
- 17. Secure export licenses, book space, and prepare documentation for shipments to be exported from the United States. Input information into the International Nuclear Materials Tracking System at Oak Ridge National Laboratory (ORNL), as appropriate.
- 18. Maintain on file all Certificates of Compliance (COC) covering containers used by Hanford Site contractors. Verify prior to shipment that a certificate is in force and that the package presented for shipment meets its provisions. Distribute copies to users. Verify that the Hanford Site contractor is using a container registered with the NRC (if container is under a NRC-COC) or DOE before first use.

LO 1.1 EXCEPTIONS TO THE PMM FUNCTION AS SHIPPER/RECEIVER FOR DOE-RL

1. Pacific Northwest Laboratory (PNL) is authorized to arrange for offsite shipment of PNL private materials that are of an experimental nature. The conditions and limitations for this are specified in PNL-MA-81, "Radioactive Material Shipping Manual." All DOE-owned material goes through Traffic.

1.2 SHIPPING, TRAFFIC, AND RECEIVING OPERATIONS

In performance of the PMM shipping and receiving duties for Westinghouse and other Hanford Contractors, Traffic works closely with Material Management to assure an efficient operation. The Material Management responsibilities in performing its part are defined in the <u>Material Distribution Manual</u>, WHC-CM-2-2, and will not be repeated here.

The Material Management and the Traffic groups of the PMM function are responsible for performing the following functions:

1.2.1 Shipping

0

- 1. Requests the Radiation Protection Technologist (RPT) to survey the radioactive material packages(s) and the delivery vehicle at the 1100 Area shipping facility. The RPT will confirm the radiation and contamination levels of the package(s) and sign the ORSR. For exclusive-use shipments loaded in the outer areas, the exterior of the vehicle is surveyed at the 1100 Area prior to departure offsite.
- 2. Weighs the package(s) when necessary and records the weight on the ORSR and HMSR, as appropriate.

SHIPPING AND RECEIVING HAZARDOUS MATERIAL IN THE 1100 AREA

Effective Date August 1, 1988

- 3. Inspects the package(s) for evidence of damage.
- 4. Calls the offsite Hazardous Material Specialist (OHMS), Traffic, to inspect the package(s), review, and approve the shipment.
- Obtains the prior shipping papers from Traffic.
- 6. Loads the shipment into/onto the carrier's equipment secures the driver's signature on the shipping papers, then furnishes appropriate copies to the driver.
- Provides locked temporary storage in the 1100 Area for other than exclusive-use shipments of radioactive materials awaiting offsite transfer.

1.2.2 Traffic

LO

()

- 1. Determines the mode, routing, ETA, and special handling requirements. Issues special instructions to the carrier to assure safe, secure transport within the framework of various regulations. Special considerations suggested by the contractors will be accommodated, when feasible. If considerations as suggested cannot be accommodated, Traffic will make proper arrangements with the originator and carriers.
- 2. Prepares the shipping papers for delivery to the carrier in the 1100 Area.
- 3. Performs shipping functions 1 and 2 above when outbound truckload or exclusive-use shipments of empty containers or radioactive materials stop at the 1166 Building for inspection and survey. Secures the driver's signature on the shipping papers and furnishes him with appropriate copies.
- 4. Performs the following tasks on the day the shipment leaves the Hanford Site:
 - a. Notifies the consignee, by teletype, of the shipment, name of the carrier, and ETA.
 - b. Notifies DOE-RL PMD of the shipment and provides copies of the bill of lading, ORSR or HMSR, and the teletype to the consignee.
 - c. Sends the originator copies of the ORSR or HMSR complete with data added by Traffic regarding the shipment.
- 5. Follows the progress of outbound shipments, expedites delaying factors, and verifies the shipment was delivered to the consignee.

HAZARDOUS MATERIAL PACKAGING AND SHIPPING

Manual Section Page Effective Date WHC-CM-2-14 Part V, REV 0 5 of 6

SHIPPING AND RECEIVING HAZARDOUS MATERIAL IN THE 1100 AREA

August 1, 1988

Notifies appropriate parties of final delivery date, as well as any deviation from the ETA.

- 6. Maintains an inbound and outbound log book from which shipment control numbers are assigned. Completes the entries with delivery information after the shipment arrives at its destination.
- 7. Makes progress checks on incoming shipments when information has been provided by the consignor or consignee.
- 8. Notifies Receiving and others with a need-to-know when a shipment is enroute to the Hanford Site and its ETA.
- Develops, coordinates, and administers activities according to this manual.
- 10. Coordinates and approves offsite shipments of hazardous materials. This involves interpreting Federal regulations, inspecting containers tendered for shipment and their associated shipment documentation (ORSR, UHWM, HMSR), reviewing container authorizations, and scheduling carriers.

1.2.3 Receiving

de la

1

1.17

-

(_)

- Accepts delivery of all inbound hazardous material shipments (except exclusive-use (full-load) shipments) transported by commercial carriers that are consigned to DOE-RL contractors.
- 2. Requests a radiation survey in each incoming radioactive material package and carrier vehicle to ensure it is free of significant surface contamination. For exclusive-use shipments, only the exterior of the vehicle is surveyed the 1100 Area shipping/receiving facility.
- 3. Escorts exclusive-use (full-load) shipments directly to the consignee's dock after the RPT survey at the 1100 Area shipping/receiving facility. Processes receiving papers upon verification of package count and condition.
- Identifies each inbound shipment with a control number obtained from Traffic.
- Prepares a receiving report for each inbound shipments and inspects packages for evidence of damage.
- 6. Provides temporary, locked storage in the 1100 Area for other than exclusive-use shipments, pending onsite delivery.
- Arranges for temporary clearance of carrier personnel making delivery onsite beyond project barricades.

HAZARDOUS MATERIAL PACKAGING AND SHIPPING

1 # 7

1.17

 \bigcirc

()

Manual Section Page Effective Date WHC-CM-2-14 Part V, REV 0 6 of 6 August 1, 1988

SHIPPING AND RECEIVING HAZARDOUS MATERIAL IN THE 1100 AREA

8. Ensures that only Level 3 cleared employees are assigned to receiving, transporting, and escorting shipments of SNM. Arranges Patrol escort of SNM as required.

- 9. Prepares and issues an RSR to forward radioactive material shipments to onsite consignees.
- 10. Notifies the contractor's source and SNM representative upon receipt of this type of material at the 1167 Building. Notifies the consignee when the shipment is ready for dispatch from the 1100 Area for final onsite delivery.

Manual Section Page Effective Date WHC-CM-2-14 Appendix A A-1 of A-7 March 20, 1989

COURSE 0059 - CERTIFICATION OF HAZARDOUS MATERIAL SHIPMENTS

COURSE OUTLINE

- I. Introduction
- II. Resource documents used in making hazardous material shipments
- III. Service organizations:

Traffic Department Packaging Development

- IV. How to use Title 49 CFR Parts 171, 172, & 173
 - V. Requirements of DOE-RL Order 5480.1 Chapter III
- VI. Workshop--preparing Offsite Radioactive Shipment Records (ORSRs)
- VII. Workshop--Preparing Onsite Radioactive Shipment Records (RSRs)
- VIII. Workshop--Preparing Hazardous Material Shipment Records (HMSRs)
 - IX. Examination

PRIMARY COURSE OBJECTIVE

Provide training in the Department of Transportation "Hazardous Material Regulations", as required by law, to those who certify the compliance of Hanford hazardous material shipments. The main focus will be on the proper preparation and release of radioactive material shipments. Recertification will be required every two years.

SECONDARY OBJECTIVES

- 1. The student will understand the reasoning behind the establishment of the regulations, historical background, scope, etc.
- 2. The student must recognize the primary resource documents used in making hazardous material shipments. They must know where the regulations exist, the general content of the regulations, and how to use the documents properly.
- 3. The student must know whom to turn to if assistance is needed in interpreting or applying the regulations. Each Hanford Contractor has service organizations who provide this service. The student must know how to interface with these organizations.

-

₩. ×

 \mathbf{C}

, j +

Manual Section Page WHC-CM-2-14 Appendix A A-2 of A-7

COURSE OUTLINES AND OBJECTIVES

Effective Date March 20, 1989

- 4. The student must become familiar with the Department of Transportation "Hazardous Material Regulations" found in Title 49 Code of Federal Regulations, Parts 171 thru 173. They must know what kinds of requirements are in the document, how to use the document, and understand their responsibility for compliance.
- 5. The student must be familiar with the requirements found in DOE-RL Order 5480.1 Chapter III "Safety Requirements for the Packaging of Fissile and other Radioactive Materials" and understand their responsibility for compliance.
- 6. The student must understand the unique terminology used in the packaging and transportation of radioactive materials (e.g., normal form, special form, Type A, Type B, Highway Route Controlled Quantity, etc.).
- 7. Given sample data concerning materials to be shipped, the student must be able to follow procedures and apply the regulations to properly classify, describe, package, mark, and label the material for shipment; placard the vehicle; and document the shipment on a shipping record.
- 8. The student must be familiar with the shipping papers used at Hanford for hazardous material shipments, and if given sample data, properly complete each form in compliance with the federal regulations.

HAZARDOUS MATERIAL PACKAGING AND SHIPPING

COURSE OUTLINES AND OBJECTIVES

Manual Section Page

WHC-CM-2-14 Appendix A A-3 of A-7

Effective Date March 20, 1989

COURSE 006S - HAZARDOUS WASTE SHIPMENT CERTIFICATION

COURSE OUTLINE

به میاداند م

1.17

 \bigcirc

17

 \bigcirc

15

- I. Course Introduction
- II. Non-Radioactive Dangerous Waste Management
 - A. Introduction to applicable regulations
 - B. Waste identification and designation
 - C. Generating facility management
 - D. Waste packaging and shipment
 - E. Exercise
- III. Hazardous Material Release Reporting
 - A. Hazardous material releases
 - B. CERCLA reportable releases
 - C. WDOE reportable releases
 - D. SARA reportable releases
 - E. Exercises
 - IV. Other Environmental Reporting
 - A. SARA hazardous materials inventory
 - B. SARA toxic chemical release report
 - C. Waste minimization
 - D. Generating/TSD Facility report
 - E. Exercise
 - V. Mixed Waste Management
 - A. Introduction to mixed waste (MW)
 - B. Scope of DOE-RL MW Management Directive

-
- D. Management of MW consistent with non-radioactive hazardous waste management

Action planning for the segregation of MW from HLW, TRU, and LLW

E. Summary

VI. PCB Management

O

10

 \bigcirc

()

Ç.

- A. Introduction to PCB's
- B. WHC PCB management
- C. Compliance with 40 CFR 761 requirements
- D. Overview of facility PCB management systems
- E. PCB management system responsibilities
- F. Summary of inspections, records, and reporting
- VII. Preparation and Shipment of Hazardous Waste
 - A. Introduction to applicable regulations
 - B. Instructions for using 49 CFR 171-173 & 178
 - C. Sample cases
 - D. Summary
- VIII. Summary and Preparation for Test

PRIMARY COURSE OBJECTIVE

At the completion of this course, the student will have a working knowledge covering the fundamentals of non-radioactive dangerous waste, mixed waste, and PCB management. Re-certification is required every year.

SECONDARY OBJECTIVES

At the completion of this session, the student will be able to:

- 1. List the major sets of regulations concerning management of hazardous waste.
- 2. List the dangerous waste characteristics regulated in Washington State.

U)

*** :

1

3

- 3. Identify information for, and complete a Disposal Analysis Request form.
- Define RCRA/WDOE waste numbers assigned in the waste designation process.
- 5. Identify waste management and accumulation requirements for a generating facility under Washington State law.
- 6. Assign accumulataon dates to hazardous/dangerous waste.
- Identify requirements for management of unknown waste. 7.
- Read and interpret the disposal analysis letter instructions packaging, labeling, marking, and transportation of hazardous/dangerous waste.
- List packaging requirements for "Lab Packs."
- 10. Differentiate between the three regulatory classes of empty drums.
- 11. Complete a Uniform Hazardous Waste Manifest.
- List the waste acceptance and return criteria at the Non-12. Radioactive Dangerous Waste storage facility (616 Bldg.).
- 13. Identify a hazardous material release and list internal remediation and response actions.
- 14. Identify and differentiate between CERCLA, WDOE, and SARA reportable releases.
- 15. List SARA hazardous materials inventory reporting requirements and identify reportable items.
- List SARA toxic chemical release reporting requirements and 16. identify reportable items.
- 17. List regulatory requirements and recommended methods for waste minimization.
- 18. List information reported to the State in the annual Generator/TSD facility report.
- Identify mixed waste management requirements for generating facilities under DOE-RL directive.
- 20. List mixed waste storage area inspection requirements.

HAZARDOUS MATERIAL PACKAGING	Manual	WHC-CM-2-14
AND SHIPPING	Section	· Appendix A
	Page	A-6 of A-7
COURSE OUTLINES AND OBJECTIVES	Effective Date	March 20, 1989

- 21. Identify mixed waste management activities.
- 22. List mixed waste segregation and certification requirements.
- 23. List PCB container marking and labeling requirements.
- 24. Identify PCB storage area requirements.

C

L()

()

- 25. List criteria for use of PCB equipment/systems at a facility.
- 26. Identify information for the completion of a Uniform Hazardous Waste Manifest.
- 27. Identify marking requirements for a given container of waste.
- 28. Identify labeling requirements for a given container of waste.
- 29. Identify information for the completion of a Hazardous Waste sticker.

HAZARDOUS MATERIAL PACKAGING
AND SHIPPING
Section
Page
A-7 of A-7
COURSE OUTLINES AND OBJECTIVES
AND OBJECTIVES
Manual
Appendix A
Page
A-7 of A-7
Effective Date
March 20, 1989

COURSE 060401 - NUCLEAR MATERIAL CUSTODIAN TRAINING

Prerequisite: Nominated by manager, and 3 or 5 Clearance.

C .

OC.

n O

This is the formal training required as certification for Safeguards approval as a Nuclear Material Custodian. The course requires an end of course examination completion with 80% accuracy. Annual re-qualification is necessary to maintain continuing certification.

This course is directed to the supervisory or technical personnel who are responsible for activities involving the storing, processing, or transfering of nuclear materials.

The main objectives are to train the custodians in the methods used for the control and accountability of nuclear materials and their requirements and responsibilities for implementing those methods.

THIS PAGE INTENTIONALLY LEFT BLANK

WESTINGHOUSE HANFORD COMPANY Manual WHC-CM-2-14 Section Appendix B, REV 0 B-1 of B-9 Page Effective Date August 1, 1988 **Organization** Procurement and

HAZARDOUS MATERIAL PACKAGING AND SHIPPING

TITLE: Approved by

D. K. Quigley, Manager, SHIPMENT EXAMPLES

Procurement and Materials Mgmt

Materials Management

1.0 HAZARDOUS MATERIAL SHIPMENTS

LO

The following examples illustrate the steps used in preparing a HM shipment. To assist in the examples, a small portion of the 49 CFR 172.101 Hazardous Materials Table is reproduced here in Table APP B-1-1. All column references in the examples are to Table APP B-1-1, where applicable. Each example includes a completed HMSR form (Exhibit APP B-1-1, APP B-1-2) with on the specific data.

TABLE APP B-1-1

EXCERPT FROM 49CFR 172.101 HAZARDOUS MATERIALS TABLE

	(2)	(3)	(3A)	(4)	(5) Packaging		
*****	Hazardous materials descriptions and proper shipping names	Hazard class	Identi- fication number	Label(s) required (if not excepted)	(a) Exceptions	(b) Specific require- ments	
C	> Sodium, metal or metallic (RQ-1000/454)	Flammable solid	UN1428	Flammable solid & Dangerous when wet	None	173.206	
	Sodium potassium alloy (liquid) (RQ-1000/454)	Flammable solid	UN1422	Flammable solid & Dangerous when wet	None	173.206	
	Sodium potassium alloy (solid) (RQ-1000/454)	Flammable solid	UN1422	Flammable solid & Dangerous when wet	None	173.206	
	Denatured alcohol	Flammable liquid	NA1986	Flammable liquid	173.118	173.125	

- 1.1 <u>EXAMPLE I</u> -- Offsite shipment of a sodium-bonded, double-welded, stainless steel capsule containing structural specimens for irradiation. Sodium (40 g) is used as a heat transfer medium. Assume truck transportation.
 - Determine the proper shipping name (Column 2), the hazard class (Column 3) and the identification number (Column 3A). Example: 1. Sodium, metal (or Sodium, metallic); Flammable solid; UN1428. Hazardous substance determination from 172.101 Appendix: 10 1b RQ.

2. Determine the required packaging from Column 5. Column 5(a) references any applicable exceptions. None is listed for sodium. Column 5(b) references specific requirements for the HM. Those for sodium are given in 173.206. 173.206(a) states: "Metallic sodium or potassium... must be packaged as follows...". Further search takes us to 173.206(a)(10), which states:

"Tubes of stainless steel, or other metals of equivalent strength and nonreactivity, having sealed, welded end caps, and containing not more than 50 grams of metal. Authorized only for metallic sodium, metallic lithium, metallic potassium, and sodium potassium alloy. Each tube must be enclosed within a secondary sealed metallic tube and further enclosed within strong tight outer packaging."

 $\alpha >$

Ln

3

Strong tight packaging is so designed and constructed and its contents so limited that under conditions normally encountered during transportation:

- -- There will be no significant release of the hazardous materials to the environment;
- The effectiveness of the packaging will not be substantially reduced; and
- -- There will be no mixture of gases or vapors in the package which could, through any credible spontaneous increase of heat or pressure, or through an explosion, significantly reduce the effectiveness of the packaging.

Strong tight containers may be made of many different materials, e.g., cardboard boxes, sealed tin cans, etc., as long as the finished container meets these criteria.

- 3. Determine the labels required. Column 4 shows that both FLAMMABLE SOLID and DANGEROUS WHEN WET labels are required on the package. One of each is sufficient, and they must be placed near the proper shipping name marking on the package.
- 4. Determine the markings required on the package. Marking should be done with 0.5 in. high letters.
 - -- 172.301 states that the package shall be marked with the proper shipping name and the identification number (preceded by UN or NA, as appropriate). For the shipment use SODIUM, METAL (or SODIUM METALLIC), UN1428.
 - -- 172.306 states that the package must be marked with the name and address of the consignee or the consignor, as appropriate.

5. Label, mark and address the package(s) as directed above. See Figure APP B-I-1.

150

C)

LO

7

- 6. Determine the vehicle placarding requirement. (See 172.504.) FLAMMABLE SOLID placard is required for this sodium shipment.
 - 7. Fill out and complete the Hazardous Materials Shipment Record. See Exhibit APP B-1-1. Remember, the information supplied here is used by Traffic (in the case of offsite shipment) to fill out the shipping papers.
 - 8. Arrange transportation. Advise driver and furnish placards unless the truck is permanently placarded.

Note: Other problems may occur when making HM shipments. Inspection of the 49 CFR 172.101 table from which Table APP J-1-1 and 172.101 Appendix table shows the sodium classified as hazardous substance in addition to being a hazardous material, and has a reportable quantity (RQ) of 10 lb or 4.54 kg. The amount of sodium shipped in this example is only 40 g. Had it been 10 lb or more the letters RQ would also have to be entered along with the proper shipping name on the package and on the shipping papers, 172.203(c)(2).

- 1.2 <u>EXAMPLE II</u> -- Onsite shipment of two 55-gal drums of denatured alcohol. Flash point, 50°F. Assume truck transportation.
 - 1. Determine the proper shipping name (Column 2), the hazard class (Column 3) and the identification number (Column 3A). Example: Denatured alcohol, Flammable liquid, NA1986. Hazardous substance determination from 172.101 Appendix table: not listed, no RQ involved.
 - 2. Determine the packaging requirements (Column 5). Exceptions [Column 5(a)] exist and are defined in 173.118. These exceptions do not apply, however, since they deal in quantities much smaller than those involved in shipment or with a flash point of 73°F or higher. Specific packaging requirements [Column 5(b)] direct us to 173.125, which states: "...alcohol, n.o.s., which is classed as flammable liquid, must be packaged as follows: (1) In containers as prescribed in 173.119(a) and (b)." Both references provide for either a 17E or 17C drum (49 CFR 178.115 or 178.116).
 - 3. Determine the labels required. Column 4 shows that a FLAMMABLE LIQUID label must be affixed to each drum. 172.406(a) requires that this label must be affixed to the package near the marked proper shipping name. One label is sufficient so long as no radioactive material is present and the package has volume less than 64 ft³, 479 gal, [172.406(3)].

HAZARDOUS MATERIAL PACKAGING AND SHIPPING	Manual Section	WHC-CM-2-14 Appendix B, REV 0
	Page	B-4 of B-9
SHIPMENT EXAMPLES	Effective Date	August 1, 1988

c)

LI)

 \Box

○

4. Determine the markings required on the package. Marking shall be done with 0.5 in. high letters.

SHIPMENT EXAMPLES

-

CO

4

 \bigcirc

74,74

(

....

Manual Section Page Effective Date

WHC-CM-2-14 Appendix B, REV 0 B-5 of B-9 August 1, 1988




Figure APP B-1-1. Package, labeled, marked and addressed.

SHIPMENT EXAMPLES

C.3

L()

Manual Section Page Effective Date WHC-CM-2-14 Appendix B, REV 0 B-6 of B-9 August 1, 1988

	SHIP TO:			HAZARDOUS MATERIAL SHIPMENT RECORD (HMSR)			ORD				
SHIPPING INST.	ALL GONE LAB Address 1865 CIVIL WAR AVE.			Originating Building . Area		Originator Sig		XX/XX/XX			
ם	City, State, Zip			OFFSITE	ONLY:	SHIP: K	PREPAID [COLLECT			
돐	ANV	MHEI	DE Y	Y 12345			Parcel Po	- Dai	Parcel Post	X Freight (Rail/Truck)	
	ANYWHERE, XX 12345				. =	Air (Pass			Code: VG1861 MAZMAP		
			CC	NTAINER	S/PACKAGI	NG				DESCRIPTION	
	Number of Containers	Т	ype	DOT Spec	Package Dimensions	<u>Quantity</u> Pkg	Gross V Each Pk		R 172.101(c) Haza	rdous Material Table	
	1		000 X	15A	8x8x62*	1 CAPSU 40g SODIUM	LE 40	Hazard Class: UN/NA No.:	UN 1428		
								Lest Secondar	y Hezerds: NONE		
						<u> </u>	<u> </u>	List Labels R	,	MMABLE SOLID and	
							ľ	Proper Ship N		GEROUS WHEN WET	
	1						1	Hezerd Class:			
ē							,			Į	
₫.						j	1	UN/NA No.:			
5					1		1	List Seconder	ry Hazards:		
ĕ					<u> </u>			List Labels R	List Labels Reg'd/Applied		
SHIPMENT DESCRIPTION								Proper Ship N	Proper Ship Name:		
호								Hezerd Class:			
ᇙ					1			UN/NA No.:		İ	
								List Seconder	y Hazards:	j	
								List Labels Re	eo'd/Applied		
	Total No. C	Conta	nert	Gross Wt of	Shipment	Identify Placards Requi		wired:		Control or Return Order No.:	
	,			40.7	L_	1. FLANMABLE 3. SULTU-N-		3	(if applicable)		
	1			40 1	DS			4	WHC-83	-XXXX	
	Mazarial	in m		rers original (onrainer, [V]	Yes 🗆		scribe Internal Pa	ckaging:		
				rioration or (<u> </u>	Yes		40g SODIUM	IN DOUBLE WE	LDED SST CAPSULE	
				y documente	_	Yes		PACKED IN	VERMICULITE	IN DOT SPECIFICATION	
				seeled, marke OT requirem		Yes		15A BOX			
		Surv	ey No.	-	Date	RM	Signature		Print N	tame	
1	DIATION	ν,	·		XX/XX/X	x .	Ju- 2	0 =	xx :	XXXXXXXXXX	
RELEASE XXXXX XX/XX/X				140	<u> </u>						
<u> </u>			_		 		ERTIFIC		· · · · · · · · · · · · · · · · · · ·		
CONTRACTORS CERTIFICATION This is to certify that the above of peckaged, marked and labeled and to the applicable regulations of the			nd are in pro	per condit	ion for transport : sportation:	according	This shipment is within the Limitations prescribed for: Passenger				
<u> </u>			Auth	orizing Signat					e <u>XX XXXXX</u>		
<u> </u>							- ADD		ROVAL REQUIR		
1		ان	B.L. N	о.	Date Shipped	ETA		Routing		Special Considerations	
	WHC	Ē				1					
MHC RAFFIC			!		.1						

54-300-596 (10-47) FUS GOVERNMENT PRINTING OFFICE 1987 - \$61-711

WHC-CM-2-14 HAZARDOUS MATERIAL PACKAGING Manual · Section Appendix B, REV 0 AND SHIPPING B-7 of B-9 Page SHIPMENT EXAMPLES Effective Date August 1, 1988

> 172.301 states that the packages shall be marked with the proper shipping name and the identification number. From the above steps, these are: Denatured alcohol, NA1986. 172.306 states that the package must also be marked with the

> name and address of the consignee or consignor, as appropriate.

- Label, mark and address the packages as directed above. See Figure 5. APP B-1-2.
- Determine the vehicle placarding requirements (172.504). 6. placarding of the vehicle is required since the two drums of alcohol weigh less than 1000 lb [172.504(c)(1)]. Alcohol weighs 6.8 lb/gal; therefore 55 gallons weighs about 375 pounds. Allowing about 40 1b for an empty drum, each drum of alcohol weighs a maximum of 415 1b, or 830 1b total for two drums.
- Complete the Hazardous Materials Shipment Record using the above 7. data. See Exhibit APP B-1-2.
- 8. Arrange transportation.

9

C

11)


(")

--

> .

HAZARDOUS MATERIAL PACKAGING AND SHIPPING	Manual Section	WHC-CM-2-14 Appendix B, REV 0	
SHIPMENT EXAMPLES	Page Effective Date	B-8 of B-9 August 1, 1988	

Figure APP B-1-2. Package, labeled, marked, and addressed



0

LD

(_)

О

PLACARDS: NONE REQUIRED FOR THIS SHIPMENT

78804-143.2

SHIPMENT EXAMPLES

O

Ln

\$. T

 \bigcirc

Manual Section Page Effective Date WHC-CM-2-14 Appendix B, REV 0 B-9 of B-9

August 1, 1988

Exhibit APP B-1-2. Hazardous Materials Shipment Record.

	SHIP TO:	·			HAZ	ARDOUS	MATERIAL (HMSF	SHIPMENT RECO	RD	
SHIPPING INST.	WESTINGHOUSE Address BLDG. 4983			Originating Facility Building 324 Area 300		Originator Signature Signa		□ PNL	XX/XX/XX	
1 th	City, State, Zip			OFFSITE (ONLY:	<u> </u>	PREPAID	COLLECT		
22	400 AREA				_	Parcel Post	===		Freight (Rail/Truck)
┝	Attention	9.0				Air (Passen	ger) [Ai	r (Cargo) Cost C		APPLICABLE)
	CONTAINERS / PA			Package	·		CONTENT DESCRIPTION			
	Containers	Туре	DOT Spec	Dimensions	Pkg	Each Pkg	See 49 CF	R 172.101(c) Hazard	ous Matéria	Table
	2	DRUM	17C	55 GAL	55 GAL	415 lb	1 ' '	Name: DENATURED		-
		<u> </u>						FLAMMABLE LIC	UID	
							ł	NA 1986		•
]		A Hesserge: NONE		
]						<u> </u>	List Labels R	eq'd/Applied FLAM	ABLE L	IQUID
							Proper Ship A	Name:		
8							Hazard Class:	:		i
Ē						į	UN/NA No.:			
DESCRIPTION							List Seconder	ry Hezerde:		
							List Labels Reg'd/Applied			
SHIPMENT							Proper Ship Name:			
₹			1				Hexard Class:			
돐							UN/NA No.:			
			-				List Seconder	y Hazarde:		
							List Labels Re	eq'd/Applied		
	Total No. (Containers	Gross Wt of	Shipment	Identify Place		red:	Identify Property Co. (if applicable)	ntrol or flet	urn Order No.:
	2		830 1	bs	1. NON	<u> </u>	NA NA			
					2	4. Dans	ribe Internal Pac	the sign of		
	Material	in manufactu	irers anginal d	ontsiner: 🏋	Yes 🔲 f	40	The Internal Fac	weduid.		
			erioration or c		Yes		110 GAL DI	ENATURED ALCOH	OL IN T	WO 55 GAL DRUMS
			y documented sesied, merke	_	Yes .	l				
			OT requireme		Yes					
	51471611	Survey No.	1	Date	[AM_S	ignature		Print Nan	10	
1	DIATION ELEASE	xxxxxx		XX/XX/X	. [MU	1	** **	XXXXXX	
ANAMA ANAMA					RTIFICAT	ION	<u> </u>	AAAAAA		
-		This	is to certify t	hat the shove n			trly classified, d	lacor had	This shoom	ent is within the Limita-
co	NTRACTOR	RS pack	aged, marked	and labeled an	d are in prop	er condition	for transport a		tions presc	ribed for:
CERTIFICATION to the applicable regulations of the				e Cebertuali	t Of Transpi	or catron.	ı	Aircraft	er Cargo DNA : Aircraft	
Authorizing Signature:Print Name SS SSSSS Date: XX/XX/						Date: XX/XX/XX				
			FOR	OFFSITE SH	PMENTS .	- ADDIT	ONAL APPR	OVAL REQUIRED)	
		8,L, N	o.	Date Shipped	ETA		Routing	s	pecial Cons	iderations
	WHC	Ē						-		ļ
		TRAFFIC	dC Testile	T						
WHC Traffic: WHC Shipping:										

THIS PAGE INTENTIONALLY LEFT BLANK

Manua 1 Section Page

WHC-CM-2-14 Appendix C C-1 of C-34

RADIOACTIVE MATERIAL CHARACTERIZATION

Effective Date

March 20, 1989

1.0 RADIOACTIVE MATERIAL CHARACTERIZATION

The shipper must properly describe the radioactive material on the RSR for shipment. This includes: [See 49 CFR 172.203(d)]

- Proper Shipping Name, Hazard Class, ID Number and Quantity (Wt., Vol., etc.)
- Radionuclides packaged (Sr-90, Am-241)
- Physical and chemical form (solid, oxide)
- Activity in each package (Ci)
- Labeling (White-I, Yellow-II, Yellow-III)
 Transport Index (TI = 1.0) 0
- 0
- Fissile class (I, II, III)
- Container used (Certificate of Compliance ID Number)
- Other information

C. 1

(3)

153

Considering the large number of radionuclides, there could be almost endless combinations of shipment/package possibilities. Fortunately, the number of radionuclides normally shipped at Hanford is only a small fraction of those possible, and the number is still further reduced when the specific nuclides shipped at any one facility are considered.

This Appendix discusses radioactive material characterization for shipments. The Glossary, Appendix E, defines radioactive material for both onsite and offsite shipments.

1.1 RADIOACTIVE MATERIAL WITH OTHER HAZARDOUS MATERIAL PROPERTIES

In some cases, radioactive material may be associated with other hazardous materials either in chemical combination or as a mixture. The presence of these secondary hazards must be addressed in the shipping papers. Modified packaging and labeling may be required. A list of these hazardous constituents are given in 49 CFR Part 172 or in EPA 40 CFR 260-265. Radioactive wastes containing hazardous constituents are termed "mixed wastes" and require special treatment in handling and shipping. (See WHC-EP-0063, Hanford Radioactive Solid Waste Packaging, Storage and Disposal Requirements).

RADIONUCLIDES AND THEIR ACTIVITIES 1.2

Each radioactive shipment description must include an estimate of the total activity as well as a list of the radionuclides involved. originator of the shipment must supply this information since he presumably is most familiar with the material. Several methods for the estimation of activities are available. For example:

0 Radioactive counting methods that identify and measure radionuclide disintegration rates in a sample.

RADIOACTIVE MATERIAL CHARACTERIZATION

Effective Date

March 20, 1989

- o Computer programs relating the irradiation history and radioactive decay of the material. FFTF Core Engineering generates these programs to identify nuclides and their activities in FFTF fuel assemblies.
- o Calculations based on physical weight, chemical and isotopic analyses, and specific activities of the radioisotopes. Table APP C-1 shows some examples of plutonium feed materials for FFTF. Similar data could be developed for other source, feed, and product materials.
- o Calculations from unshielded exposure rate measurements of irradiated material at a specific distance and an assumed average spectral energy of the radiation giving the dose rate. Accuracy of this method is relatively poor compared to those above, but in some cases the only choice available. Table APP C-2 gives some dose rates at one centimeter and one foot from some unshielded one curie radionuclide sources. Included along with this table are some example calculations.
- o Calculations based on exposure through shielding when the composition and thickness of the shielding, as well as the energy of the principal emissions are known. This is the least accurate method.

For onsite and offsite movement, radionuclides must be clearly identified by symbol and isotopic weight (e.g., 239Pu, 235U, or Pu-239, U-235). If fissile material is being described, the mass of material present is as significant as its activity in curies. The number in grams must also be indicated to assure compliance with criticality requirements.

1.3 UNITS OF RADIOACTIVITY

(")

0

LI

The activity of a RAM shipment must be expressed in units of curies, millicuries, etc. The following list shows a few of the more widely used expressions of activity and their acceptable abbreviations, as well as some conversion factors.

1 curie = Ci = $3.7 \times 10^{10} \text{ dps}^{*} = 2.22 \times 10^{12} \text{ dpm}^{**}$

1 millicurie = mCi = $3.7 \times 10^7 \text{ dps} = 2.22 \times 10^9 \text{ dpm}$

1 microcurie = uCi = $3.7 \times 10^4 \text{ dps} = 2.22 \times 10^6 \text{ dpm}$

1 nanocurie = $nCi = 3.7 \times 10 \text{ dps} = 2.22 \times 10^3 \text{ dpm}$

1 picocurie = pCi = $3.7 \times 10^{-2} \text{ dps} = 2.22 \text{ dpm}$

Manual Section Page WHC-CM-2-14 Appendix C C-3 of C-34 March 20, 1989

RADIOACTIVE MATERIAL CHARACTERIZATION

* dps = disintegrations per second

Effective Date

** dpm disintegration per minute

ACTIVITY UNITS

Multiply no. of ——>	by>	to obtain no. of
to obtain no. of <	by <	Divide no. of
curies	103	millicuries
curies	106	microcuries
curies	1012	picocuries

All radioactive material shipments transported by air, whether domestic or international, must comply with the International Air Transport Association (IATA) Dangerous Goods Regulations. The IATA requires all activities be expressed in the International System of Units (SI) as well as the more traditional units. The traditional and SI units are compared in Appendix E. (See International System of Units).

1.4 QUANTITY CATEGORIES

The amounts of the radionuclides to be shipped in a given package must be compared with the A_1 and A_2 values assigned for each of the radionuclides given in 49 CFR 173.435. Applying the specific multiplication factors (1/1000, 1, 3000) to these A_1 and A_2 values gives the quantity ranges for these radionuclides to be shipped, defines the quantity categories involved and further decides the type of container to be used. Tables APP C-3 and APP C-4 show the quantity values for Special Form (A_1) and Normal Form (A_2) respectively.

1.4.1 Treatment of Unknown and Mixtures of Radionuclides

The estimation of activity for a shipment of unknown and mixed radionuclides requires special attention. Directions for these situations are given in 49 CFR 173.433. For example, consider the following use of the unity rule or the sum of the fractions rule:

EXAMPLE: Assume a normal for mixture of 0.001 mCi of Pu-239 and 0.04 mCi of U-233. Can this mixture be shipped as a limited quantity?

First determine the ratios of the activity for each radionuclide present to its $A_2/1000$ value allowed for a limited quantity. Limited quantities ($A_2/1000$) for Pu-239 and U-233 separately are 0.002 mCi and 0.1 mCi, respectively. The calculated ratios then are: 0.001/.002 = 0.5 for Pu-239 and 0.04/0.1 = 0.4 for U-233. The sum of these ratios is 0.9,

0 0

My II

C)

-

Manual Section Page WHC-CM-2-14 Appendix C C-4 of C-34 March 20, 1989

RADIOACTIVE MATERIAL CHARACTERIZATION

Effective Date

which is less than one (unity). Therefore, this mixture can qualify as a limited quantity with all the rights and privileges of a limited quantity.

Additional directions for this example and other situations are given in 49 CFR 173.433.

1.5 OTHER TABLES

10

0

LIT

()

ر ا Table APP C-5 shows the specific activities of the radionuclides.

Table APP C-6 gives the activity-mass relationships for depleted, natural and enriched uranium.

Manual Section Page Effective Date WHC-CM-2-14 Appendix C C-5 of C-34 March 20, 1989

RADIOACTIVE MATERIAL CHARACTERIZATION

٠.٢

O

15)

C

ħΩ.

TABLE APP C-1

CURIE AND ISOTOPIC CONTENTS OF SOME TYPICAL
FFTF PLUTONIUM FEED MATERIALS

RADIOACTIVE MATERIAL CHARACTERIZATION

Effective

Date

TABLE APP C-1

CURIE AND ISOTOPIC CONTENTS OF SOME TYPICAL FFTF PLUTONIUM FEED MATERIALS

	Specific Activity	FFTF Typ 12% Py-		High Expo 17% Pu		High Exp 19% Pu	
<u>Isotope</u>	(Ci/g Iso)	wt/fr Iso*	<u>Ci/Iso</u>	wt/fr Iso	Ci/Iso	wt/fr Iso	Ci Iso
Pu-238 ·	16.8	0.00046	0.008	0.00241	0.040	0.00197	0.033
Pu-239	0.0617	0.8681	0.054	0.7906	0.049	0.763	0.047
Pu-240	0.227	0.1166	0.026	0.1678	0.038	0.195	0.044
Pu-241 ()	114.0	0.0129	1.471	0.0306	3.488	0.028	3.192
Pu-242	0.0039	0.00189	0.00001	0.0087	0.00003	0.0117	0.00005
	TOTAL + (Ci/g Pu)		1.558		3.616		3.316
	(Ci/g Pu)		0.087		0.128		0.124

^{*}wt = weight, fr = fraction, Iso = Isotope.

HAZARDOUS MATERIAL PACKAGING AND SHIPPING	Manual Section	WHC-CM-2-14 Appendix C
	Page	C-7 of C-34
RADIOACTIVE MATERIAL CHARACTERIZATION	Effective Date	March 20, 1989

TABLE APP C-2

7.7

C)

 \bigcirc

£.

- 1. GAMMA DOSE RATES FROM VARIOUS ISOTOPIC SOURCES*
- 2. SAMPLE CALCULATIONS ESTIMATION OF ACTIVITY

^{*} Health Physics Handbook, OSP 379, General Dynamics, Fort Worth, April 1963.

ď١

O>

LI)

271

RADIOACTIVE MATERIAL CHARACTERIZATION

Effective Date

TABLE APP C-2

1. GAMMA DOSE RATES FROM VARIOUS ISOTOPIC SOURCES

	Half-Life	Energy in MEV (Percent Abundance)	Roentgens Per Hou At 1 CM	ır Per Curie At 1
Foot Au-198	2.69 d	0.4118(95), 0.676(0.82), 1.089(0.16)	2,480	2.65
As-76	26.5 hr.	0.55(41), 0.64(8), 1.20(9), 1.4(.08), 2.05(1.6)	2,300	2.46
Br-82	35.9 hr.	Many up to 1.5	14,600	5.62
Co-58	71.0 d	.81(100)1.62(0.5) ⁺ (14)	5,300	5.67
Co-60	5.25 yr.	1.17(100), 1.33(100)	12,800	13.69
Cs-137	30.0 yr.	.662(82)	3,100	3.31
Cu-64	12.8 hr.	1.34(.05) +(100)	1,140	1.22
Fe-59	45.1 d	1.10(57), 1.29(43)	6,800	7.28
Ga-72	14.1 d	0.63(21), 0.83(83), 0.89(10), 2.20(30), 2.49(10), 2.51(17)	12,300	13.16
Hg-203	47 d	0.279(83)	1,100	1.18
I-128	25 m	0.46(16), 0.54(1)	450	0.48
I-130	12.5 hr.	0.41(23), 0.53(100), 0.66(100) 0.74(69), 1.15(29)	12,000	12.84
I-131	8.04 d	0.08(2), 0.28(5), 0.36(80), 0.64(9), 0.72(3)	2,500	2.41
Ir-192	74.4 d	Many up to 0.6	5,000	5.35
K-42	12.5 hr.	1.53(18)	1,520	1.63
Mn-52	5.7 d	0.73(100), 0.94(100), 1.45(100 +(33)), 19,700	21.08
Mn-54 2	291 d	0.84(100)	4,700	5.03
Na-22	2.6 yr.	1.28(100), +(89)	11,600	12.41

HAZARDOUS MATERIAL PACKAGING AND SHIPPING	Manual Section	WHC-CM-2-14 Appendix C
RADIOACTIVE MATERIAL CHARACTERIZATION	Page Effective Date	. C-9 of C-34 March 20, 1989

TABLE APP C-2 (Continued)

1. GAMMA DOSE RATES FROM VARIOUS ISOTOPIC SOURCES

Isotopio	: Half-Life	Energy in MEV (Percent Abundance)	Roentgens Per H At 1 CM	lour Per Curie At 1
<u>Foot</u>				
Na-24	15.0 hr.	1.37(100), 2.06(100)	18,700	20.01
Ra-226	1590 yr.	.186 (5.7%)	8,440	9.03
Ta-182	111 d	Many up to 1.219	5,690	6.13
Tm-170	127 d	0.084(3) and Bremsstrahlung fr (0.87, 0.97 Mev)	om 40	0.04
Zn-65	245 d	1.11(45) +(2)	2,800	1.93

(2)

 \bigcirc

Manual Section Page WHC-CM-2-14 Appendix C C-10 of C-34

RADIOACTIVE MATERIAL CHARACTERIZATION

Effective Date

March 20, 1989

2. SAMPLE CALCULATIONS

ESTIMATION OF ACTIVITY

A useful rule of thumb will give the activity of a source of gamma radiation to within $\pm 20\%$ (for photon energies between 70 keV and 4 MeV), if the exposure rate and distance from the source are known. The activity (in mCi) may be calculated from the following formula:

$$A = \frac{X}{6Ff}$$
, at a distance of 1 ft

where:

 \bigcirc

A = Activity (mCi)

E = Energy (MeV)

X = Exposure rate (mR/h)

f = Fraction of disintegrations resulting in photons of energy E

If the source emits photons of more than one energy, the activity due to each one must be separately calculated and summed in order to determine total activity.

When distance is expressed in cm rather than ft, the expression becomes:

$$A = \frac{\chi}{5000 \text{ (Ef)}}$$

If the radiation measurement is not made at a distance of 1 ft or 1 cm, use of Inverse Square Law will allow this expression to apply to a source of radiation from any distance. (Correction for distance must be made first.)

$$\frac{X_1}{X_2} = \frac{(d_2)^2}{(d_1)^2}$$

HAZARDOUS	MATERIAL	PACKAGING
AND SHIPP	ING	

Manual Section Page WHC-CM-2-14 Appendix C C-11 of C-34

March 20, 1989

RADIOACTIVE MATERIAL CHARACTERIZATION

Effective Date

2. SAMPLE CALCULATIONS (Continued)

Example 1

£"5 1

1

1

C

Calculate the activity of an unshielded source of Co-60 that reads 13.8 mR/h at 1 ft.

Co-60 emits 2 photons per disintegration:

 $_{1} = 1.17 (100\% abundance)$

2 = 1.33 (100% abundance)

X = 13.8 mR/h at 1 ft

$$A = \frac{13.8}{6[(1.17)(1.0) + (1.33)(1.0)]}$$

= 0.92 mCi

This activity value is within 20% of the actual activity of this sample, which is 1.0 mCi.

HAZARDOUS	MATERIAL	PACKAGING
AND SHIPPI	ING	

Manual Section Page WHC-CM-2-14 Appendix C C-12 of C-34 March 20, 1989

RADIOACTIVE MATERIAL CHARACTERIZATION

Effective Date

2. SAMPLE CALCULATIONS (Continued)

Example 2

• 🗥

C

ന ൃഷ Calculate the activity of an I-131 source that reads 2.2 R/h at a distance of 1 cm.

I-131 emits photons of 5 separate energies:

0.080 MeV (2.6% abundance),
$$Ef = .080 \times .026 = .002$$

0.284 MeV (5.4% abundance),
$$Ef = .284 \times .054 = .015$$

0.637 MeV (6.8% abundance), Ef =
$$.637 \times .068 = .043$$

0.723 MeV (1.6% abundance), Ef =
$$.723 \times .016 = .012$$

$$X = 2200 \text{ mR/h}$$
 at 1 cm

$$A = \frac{2200}{5000[(0.002) + (0.015) + (0.299) + (0.043) + (0.012)]}$$

$$=\frac{2200}{1854}$$

= 1.19 mCi

As in Example 1, this calculated activity is within 20% of the actual sample activity of 1.0 $\,\mathrm{mCi}$.

07.44

1

Manual Section Page Effective Date WHC-CM-2-14 Appendix C C-13 of C-34 March 20, 1989

TABLE APP C-3

ACTIVITY LIMITS FOR RADIONUCLIDES IN SPECIAL FORM

10

****...

()

55

RADIOACTIVE MATERIAL CHARACTERIZATION

Manual Section Page Effective Date

WHC-CM-2-14 Appendix C C-14 of C-34 March 20, 1989



Special Form Only
Activity Limits for Radionuclides in Special Form.
(All values in curies [CI] unless otherwise stated.)

Redionuclide symbol	Element & atomic number	Limited qty* (≤A ₇ /1,000)	Type A qty (≤A ₁)	Type 6 ety (>A ₁)	Highway Rouse controlled quant (3,000 × A ₁ or 3
227Ac	Actinium (89)	≤1,0 —	£1.000	>1.000	≥30K
228 _{AC}	Actinium (89)	≤0.01	£10 ———	>10	≥30K
105 _{Ag}	Silver (47)	≤0.04	£40 ———	>40	≥30K
110mAg	Silver (47)	≤0.007 —	£7	>7	≥21K —
111A0	Silver (47)	±0.1	≤100 ———	>100	≥30K
241 _{Am} ••	Americium (95)	≤0.008	x8	×	1
243 _{Am}	Americium (95)	≤0.006	, ,		≥24K ———
37Ar (Comp/Uncomp) —			±8 ———	×8	≥24K ———
	Argon (18)	≤1.0 ———	£1.000	>1,000	≥30K —
41Ar (Uncomp)	Argon (18)	≤0.02	≤20 ———	>20	≥30K
41Ar (Comp)	Argen (18)	≤0.001	≤1.0 ·	>1.0	≥3K
73 _{As}	Areenic (33)	≤1.0 ———	≤1,000	>1.000	≥30K
74 As ———	Amenic (33)	≤0.02	≠20 ———	>20	≥30K
76As	Areenic (33)	≤0.01 ————	£10 ———	>10	≥30K
77 _{As}	Arsenic (33)	≤0.3	≤300	>300	≥30K
211At	Astatine (85)	≤0.2	≤200 ———	>200 ————	≥30K
193 _{Au}	Gold (79)	≤0.2 ————	≤200	>200	≥30K
196 _{Au}	Gold (79)	≤0.03	≤30	>30	≥30K —
196 _{Au}	Gold (79)	≤0.04	±40 ——	>40	≥30K —
189 _{A11}	Geld (79)	10.2	≤200 ———	>200	≥30K
1318		±0.04		1	
1338.	Berium (55)		340	>40	≥30K ———
	Berlum (56)	≤0.04	≤40	>40	≥30K
14080	Serium (56)	≤0.02	≤20 ———	>20	≥30K
784	Beryllum (4)	≤0.3 ————	±300	>300	≥30K
206gi	Blometh (83)	£0.005	≤5	ж	≥15K ———
207#	Stamuth (63)	⊈0.01	≤10 ————	>10	≥30K —
210 _{Ri (ReE)}	Blomuth (83)	≭0.1 ———	≤100 ————	>100	≥30K
21281	Storracth (83)	≤0.006	st	ж ———	≥18K —
249 _{Bk}	Berkellum (97)	±1.0	≤1,000 ———	>1,000	≥30K
77 _{3r}	Bromine (35)	≤0.07	s70 ———	>70	≥30K ———
62 _{Br}	Bromine (35)	≤0.008	£6 ————	>0	≥18K
11c	Cerbon (5)	≤0.02	s20 ———	>20	≥30K —
14c	Cerbon (6)	£1.0 ———	£1,000	>1,000	±30K
45 _{Ca}	Calcium (20)	£1.0 —	≤1.000	>1,900	≥30K —
47Ce	Catalum (20)	£0.02	±20 ———	>20	≥30K ———
109 _{Cd}	Cadmium (48)		-1	>1,000	
115mCd		£1.0	£1,000 ————	_	≥30K
115 _{Cd}	Cadmium (48)	≤0.03	≤30	>30	≥30K
	Cadmium (48)	±0.08	±80 ———	>00	≥30K ———
139 _{Ce}	Corium (58)	±0.1 ———	£ 100 ———	>100	≥30K
141Ca	Cerium (58)	x0.3 ———	≤300	>300	≥30K
143 _{Ce}	Cerium (56)	≤ 0.06	≤60	>=0	≥30K
144Co	Cerium (58)	±0.01	≤10 ———	>10	≥30K
249Cf	Californium (98)	≤0.002	≤2	>2	≥6K
250 _{Cf.}	Californium (96)	≤0.007	≤ 7	>7	≥21K —
252 _{Cf}	Celifornium (96)	s0.002 ———	≤2 ———	>2	≥6X
36 _{Cl}	Chierine (17)	±0.3 —	≤300	>300	≥30K
38 _{Cl}	Chierine (17)	≤0.01	≤10 	>10	≥30K —
242 _{Cm}	Curium (96)	≰0.2 ————	≤200 ————	>200 ————	≥30K
243 _{Cm}	Curium (96)	≤0.009	49	>9	≥27K —
244Cm	Curium (96)	±0.01	±10 ———	>10	≥30K —
245 _{Cm}	Curium (96) ———	≤0.006	≤6	> -	≥18K ———
246 _{Cm}	Curium (96)		s6	×	
56 _{Co}					≥18K
57Co	Cobalt (27)	±0.005 ———	≰B	>6	≥15K ———
Samco	Cebelt (27)	±0.09	≤90 ———	>90	≥30K ———
	Cebelt (27) ———	±1.0	≤1.000 —————	>1,000	≥30K ———
58 _{Co}	Cobelt (27)	≤ 0.02	≤20 ————	>20	≥30K —
50Ce	Cobelt (27) ———	≤0.007 ———	≤7 ———	>7	≥21K
51Cr	Chromium (24) ———	≤0.6 ———	≤600	>500 ————	≥30K
	1		40	1 >40	- 204
129 _{Cs}	Cesium (55) ————	≲0.04	s40 ———	>40	≥30K
129 _{Cs} 131 _{Cs} 134 _{mCs}	Cesium (55) ———	≤1.0 ————	≤1,000 —	>1,000	≥30K

^{*}Values given for solids and gases only, for liquids divide value given by 10 or divide the A₁ value by 10,000.
**For shipments solely within the United States the A₁ value is 20 Ci for americium and plutonium contained in Am-Be or Pu-Be neutron sources or in nuclear-powered pecemakers.

4

 \bigcirc

1

C>

 \mathbb{C}

, , .

RADIOACTIVE MATERIAL CHARACTERIZATION

Effective Date

TABLE APP C-3 (Continued)

Special Form Only
Activity Limits for Radionuclides in Special Form. (All values in curies [CI] unless otherwise stated.) (Continued)

Redenucide symbol	Element & atomio number	Limited qty* (≤A1/1,000)	Type A qty (≤A1)	Type B qty (>A ₁)	Highway Rouse controlled quantity (3.000 × A ₇ or 30K)
134 _{Ca}	Coolum (55)	≤0.01	±10 —	>10	≥30K
135 _{Cs}	Coolum (ISS) ———	≤1.0	≤1,000 ———	>1.000	≥30K
136 _{Cs}	Cookers (55)	≤0.007	1 27	>7	≥21K
137 _{Ca}	Contum (55)	≤0.03	≤30	>30	2.30K
64Cu	Copper (20)	≤0.08	≤80	>80	≥ 30K —
67 _{C4}	Copper (29)	≤0.2	≤200	>200 ———	≥30K
165 _{Dy}	Dysprosium (66)	≤0.1 ————————————————————————————————————	≤100	>100	≥30K ———
166 _{Dy}	Dysprealuse (06)	£1.0	s1,000	>1,000	≥30K
169-	Erblum (68)	≤1.0 ———	£1,000	>1.000	≥30K —
1716	Erbhann (68)	≤0.05	≤50 ———	>50	≥30K
152mg _M	Europhum (63)	≤0.03	±30 ———	>30	≥30K —
152 _{Eu}	Europium (63)	≤0.02	≤20	>20	≥30K
154 ₅₄	Europium (83)	≤0.01	±10 ———	>10	≥30K
155 ₆₄	Europhum (62)	≤0.4 ———	s400	>400	≥30K
18p	Fluerine (8) ————	≤0.02	≤20 ———	>20	≥30K —
52gg	Iran (20)	≤0.006	15	>6	≥15K —
55 _{Fe}	Iren (29)	±1.0 —	£1.000	>1.000	2 30K
59 _{Fe}	Iran (26)	≤0.01	s10	>10	≥30K —
67 _{Ge}	Gaillem (31)	≤0.1	≤100 ———	>100 —	≥ 30K
66 _{Ge}	Gallian (31)	10.02	± 20	>20	≥30K
72 _{Ge}	Gaithum (31)	≤0.007	57	>7	≥21K
153 _{G4}	Gedelinium (64)	±0.2	s200 —	>200	≥30K
153 _{Gd}	Gadelnium (64)	≤0.3	≤300 ———	>300	
6800	Germanium (32)				≥30K
71Ge	Germanium (32)	≤0.02 ≤1.0	≤20 ————————————————————————————————————	>20	≥30K ———
341	Hydrogen (1)	\$1.0	t	†————	2.3K
181)44	Hefolum (72)	≤0.03	s30	>30	≥30K —
197mHg	Moreury (BO)	±0.2	≤200	>200	≥30K —
197119	Mercury (80)	10.2	5 200	>200	≥30K
203144	Moreury (80)	50.00	520	>80	≥30K
16614	Holmhum (67)	10.03	130	>30	≥30K
1234	lectine (53)	±0.05	±50 ————	>50	≥30K —
125	ledine (63)	≤1.0	±1,000	>1,000	≥30K —
126	ledine (53)	≤0.04	±40 —	>40	≥30K
129	logine (53)	±1.0 ———	±1.000	>1.000	≥30K
131,	losine (53)	≤0.04	540	>40	≥30K
1324	locine (53)	≤0.007 ———	17	>7	≥21K
133	locino (53)	10.03	130	>30	≥30K
134	leding (53)	±0.006	58	>8	234K
136	louine (53)	±0.01	±10 —	>10	≥30K
11110	Indian (49)	≤0.03	±30 ———	>30	≥30K
113m ₁	Indium (48)	≤0.06	560	>60	≥30K
114m	Indium (48)	50.03	≤30 ———	>30	≥30K
115mm	Inclum (49)	≤0.1	±100	>100	≥30K
190 _{tr}	Iridium (77)	±0.01	\$10	>100	≥30K
192	irlation (77)	≤0.02	\$20	>20	≥30K
194%	Iridian (77)	≤0.01	\$10 —	>10	≥30K
42 _K	Potassium (19)	≤0.01	s10	>10	≥30K
43 _K	Potassium (19)	≤0.02	£10 ————————————————————————————————————	>10	≥30K
SSm(r (Uncomp)	Krypton (36)	s0.1	± 100	>100	≥30K ———
SSIM(r (Comp)	Krypton (36)	≤0.1	±3 ————	>100	≥30K ————————————————————————————————————
85Kr (Uncomp)	Krypsen (36)			>1,000	
BEKr (Comp)	Krypton (36)	≤1.0 <u> </u>	±1,000 ———	1	≥30K —
87Kr (Uncomp)	}		≾5	>5	≥15K ———
87Kr (Comp)	Krypton (36) ———	≤0.02	≤20	>20	≥30K ————
140 _{Lb}	Krypton (36) ————————————————————————————————————	≤0.0006		>0.8	≥ 1,800
LSA (Low Specific Activity)		70.02	≤30 ———	>30	≥30K ———
177 _{Lu} ————————————————————————————————————	See 173,403 (n)	-03 ·	z 200	>300	
WFP	Mixed fission products—	≤0.3	≤300	>300	≥30K ———
28 _{Mg}	·	≤0.01	≤10 ——	>10	≥30K ———
1976	Magnesium (12) ———	≤0.006	56	>6	≥18K ———

^{*}Values given for solids and gases only, for liquids divide value given by 10 or divide the A_1 value by 10,000. †See tritlum.

 \Box

Manua 1 Section Page **Effective Date**

WHC-CM-2-14 Appendix C C-16 of C-34 March 20, 1989

TABLE APP C-3 (Continued)

Special Form Only Activity Limits for Radionuclides in Special Form. (All values in curies [CI] unless otherwise stated.) (Continued)

Reclementale symbol	Element & atemic number	Limited qty* (≤A ₇ /1,000)	Type A aty (≤A ₁)	Type E aty (>A ₁)	Highway Route controlled quarks (3,000 × A ₁ or 3)
52 _{Ma}	Mengenese (25) ———	≤0.005	35	>5	≥15K
54 _{Mn}	Manganese (25)	≤0.02	≤20	>20	≥30K ———
56Ma	Manganass (25)	≤0.005	45	>5	≥15K —
99 _{Mg}	Melyledenum (42)	≤0.1	≤100 ———	>100	≥30K —
13%	Mitrogen (7)	≤0.02	≤20 ———	>20	≥30K
22/10		1		- ==	1
24 _{Na}	Sedium (11)	≤0.000	£8 ———	*	≥24K ———
93m _{94b}	Sodium (11)	≤0.005 —	≤5	>5	≥15K
	Niebium (41)	≤1.0	≤1,000	>1,000	≥30K
95 _{Nb}	Nichhan (41) ———	≤0.02	≤20	>20	≥30K
97 _{Nb}	Nichlum (41)	≤0.02	≰20 ————	>20	≥30K
147 _{Nd}	Needymium (60)	≤0.1	£100 ———	>100 ———	≥30K
149 _{Nd}	Needymium (60)	≤0.03	≤30 ———	>30	≥30K
59 _{Ni}	Nickel (28)	≤1.0	≤1,000	>1,000	≥30K
63 _{Ni}	Mickel (28)	1.0	≤1,000	>1,800	≥30K
66 _{Ni}	Mickel (28) ———	≤0.01	≤10	>10	≥30K
237 _{Np}	Neptunium (93)	≰0.005 ———	£5 ———	>5	≥15K —
239 _{Np}	Negtunium (\$3)	50.2	≤200 —	>200 ———	≥30K
18604	Comium (78)	±0.02	520	>200	≥30K
19104	Oemium (76)	±0.02	\$600	>20	
191mOs		1			≥30K
19300	Ountern (76)	≤0.2	≤200	>200	≥30K
	Osmium (76)	≤0.1	≤100	>100	≥36K
32 _P	Pheepherus (15) ———	≤0.03	×30 ———	>30	≥30K
230 _{Pa}	Protestinium (91)——	≤0.02	≤20	>20	≥30K ———
231 _{Pa}	Pretactinium (91)	≰0.002 ————	≤2	>2	≥eK
233 _{Pa}	Protectinium (91)	≤0.1 ————	£100 ———	>100 ———	≥30K
201 _{Pb}	Leed (\$2)	≤0.02	±20 —	>20	≥30K
210 _{P6}	Leed (62)	±0.1 ———	≤100 ————	>100	≥30K
212	Land (82)	±0.006 ————	≤6	>6	≥1#K ———
103 _{Pd}	Palledium (48)	£1.0 ————	≤1.000	>1.000 ———	≥30K
109 _{Pd}	Palledium (46)	≤0.1 ———	£100 ———	>100	≥30K ———
147 _{Pm}	Promethium (61) ———	£1.0 ———	£1,000	>1,000	≥30K ·
149 _{Pm}	Promothium (61)	≤0.1 ———	£100	>100 —	≥30K
210 _{P0}	Pelenium (84)	≤0.2	≤200	>200	≥30K
14297	Presentlymium (59)	≤0.01	≤10	>10	≥30K
143 ₆₇	Pracectymium (53)	≤0.3	≤300	>300	≥30K
191 _{Pt}	Platinum (78)				1
193mpt		≤0.1 ———	≤100	>100	≥3CK
197mp;	Plotinum (78)	±0.2 ———	≤200	>200 ———	≥30K
	Pletinum (78)	≤0.3 ———	≤300 ————	>300	≥30K ———
197 _{Pt}	Platinum (78) ———	≤0.3 ———	≤300	>300	≥30K —
236 _{Pu} ••	Plutenium (\$4) ———	≤0.003	≤3 ———	×3 ———	≥9K
239 _{Pu}	Plutenium (94)	≤0.002 ———	≤2	>2	≥ 6 K ———
240 _{Pu}	Plutenium (94)	≤0.002	£2	>2 ————	≥ GK
241 _{Pu}	Plutonium (94)	≤1.0	≤1,000	>1,000 ————	≥30K
242 _{PU}	Plutonium (94)	±0.003 ————	≤3 ———	>3	≥9K
223 _{Re}	Reclium (88)	≤0.05	≤50 ———	>=0	≥30K ———
²²⁴ Pa	Radium (88)	≤0.006 ———	≤6	>6	≥18K
22 6 20	Redium (86)	≤0.01	£10 —	>10	≥30K
22889	Redum (88)	≤0.01	£10	>10	≥30K
81 _{Rb}	Rubidium (37)	≤0.03	≤30	>30	≥30K
96 _{Rb}	Rubidium (37)	≤0.03	±30 ———	>30	≥30K
87 _{No}	Rubidum (37)	UL++	UL#	UL#	>30K
Rb (Net)	Rubidium (37)	UL++	ULH	UL++	≥30K
1849,4	Rhenium (75)	≤0.1	≤100 —	>100 —	≥30K
187 _{Re}	Rhenium (75)	UL11	ULH —	UL#	≥30K —
180 _{Re}	Rhenium (75)	≤0.01	_	>10	
Re (Net)			≤10 ———		≥30K
103mgh	Rhenium (75)	ULH -	ULH ———	ULH	≥30K ———
	Rhodium (45) ———	±1.0 —	≤1,000 ————	>1,000 —	≥30K
105 _{Rh}	Rhodium (45) —	≤0.2	≤200	>200 ———	≥30K ———
222 _{Rn}	Radon (88)	≤0.01	≤10 ———	>10	≥30K ———
	Ruthenium (44) ———	≤0.08	≤80	>80	≥30K

^{*}Values given for solids and gases only, for liquids divide value given by 10 or divide the A₁ value by 10,000.
**For shipments solely within the United States the A₁ value is 20 Ci for americium and plutonium contained in Am-Be or Pu-Be neutron sources or in nuclear-powered pacemakers. ++Unlimited.

RADIOACTIVE MATERIAL CHARACTERIZATION

Manua₁ Section Page Effective Date

WHC-CM-2-14 Appendix C C-17 of C-34 March 20, 1989

TABLE APP C-3 (Continued)

Special Form Only Activity Limits for Radionuclides in Special Form. (All values in curies (Ci) unless otherwise stated.) (Continued)

	Radionustide symbol	Sement & atomic number	Limited qty* [≤A ₇ /1,000]	Type A qty (≤Aq)	Type B qty (>A ₁)	Highway Route cantrolled quentity (3,000 × A ₁ or 30K)
	103	Flushenken (44)	<0.03	≤30 ———	>30	≥30K
	1069	Ruthenium (44)	≤0.02	≤20 ———	>20	≥30K
	106	Ruthenken (44)	≤0.01	≤10 ———	>10	≥30K ———
	35g	Suiter (18)	≤1.0 ———	≤1.000 ————	>1,000	≥30K ———
	122	Antimery (51)	≤0.03	≤30 ———	>30	≥30K
	12499	Antimeny (51)	≤0.006	<u> 45</u>	>6	≥15K
	1259	Antimony (51)	≤0.04	s40	>40	≥30K
	4454	Scandlum (21)	≤0.008	s8	ж	≥24K
	47 ₅₄	Seendlum (21)	≤0.2 ———	≤200	>200 ———	≥30K
	48 ₅₆	Soundhare (21)	≤0.006	45 ————	×6 ———	≥15K
(f)	755e	Selenium (34)	≤0.04	s40 ———	>40	≥30K ———
	31g;	Silicon (14)	≤0.1	≤100	>100	≥30K
0	147 _{5m}	Samarium (62) ———	ULH	UL11	ULH ———	≥30K
1	151 ₅₇₈	Samarkam (62)	£1.0 ————	≤1,000	>1,000	≥30K ———
	153 _{5m}	Samertum (62)	≤0.3	≤300	>300	≥30K
\	113 _{5m}	Tin (50)	≤0.06	s60 ———	>60	≥30K
	119mga	Tie (50)	±0.1 ———	s100	>100	≥30K ———
$\boldsymbol{\circ}$	12530	Tie (50)	≤0.01	±10 ———	>10	≥30K ———
	35mgr	Strenthum (38)	≤0.08	≤80	>80	≥30K
w, -,	865,	Strontlum (36)	≤0.03	≤30 ———	>30	≥30K
. *	87mg	Strontium (39)	≾0.05	≤60	.>60	≥30K
	895,	Strontium (38)	≤0.1 ———	≤100	>100	≥30K
-	90%	Stronthum (38)	≤0.01	≤10 ———	>10	≥30K ———
	918.	Strenthum (38)	≤0.01	≤10 ———	>10	≥30K
	928,	Strontham (38)	≤0.01	£10 ————	>10	≥30K
1 -	T (Uncomp)	Tritham (1)	≤20	≤1,000	>1.000 ———	≥30K —
	T (Comp)	Trittum (1)	≤20 ———	≤1,000	>1,000	≥30K
AND A	T (Activated luminous point)	Trisium (1)	≤20 ————	≤1,009	>1,000 ———	≥30K ——
	T (Absorbed on solid)	Trithum (1)	≤20	≤1,009	>1,000	≥30K ——
····	T (Tritigand water)	Trichase (1)	<0.1 Cl/liter	≤1,000	>1,000	≥30K —
	•		0.1-1.0 Cl/New			
~			>1.0 Cl/Reer		l . <u></u>	
\bigcirc	T lother formel	Tritium (1)	≤0.02	≤20	>20	≥30K ———
	182 ₇₈	Tentalum (73)	≤0.02	≤20 ———	>20	≥30K
**************************************	160 _{Tb}	Techlum (55)	≤0.02	≤20	>20	≥30K ——
	96mTc	Technetium (43)	≰1.9 ·	≤1,000	>1.000	≥30K
	96 _{TG}	Technolium (43)	≤0.005	36	>6	±30K —
	97mTc	Technetium (43)	≤1.0 ————	≤1.000	>1,000	≥30K
	9770	Technotium (43)	≤1.0 ———	≤1,000	>1,000 ———	≥30K ———
	9 9m yc	Technetium (43)	≤0.1	£100	>100	≥30K
	9976	Technotium (43)	≤1.0	±1,000	>1,000	≥30K
	125mg	Telherham (52)	≤1.0 ————————————————————————————————————	≤1,000	>300	≥30K
	127/1070	Tellurium (52) ———	≤0.3	≤300	>300	≥30K —
	127 ₇₀	Tellurium (52)	≤0.3	≤300	>300	≥30K —
	129mye	Teiherium (52)	≤0.03	≤30 ————————————————————————————————————	>100	≥30K —
	129 ₇₀	Tellurium (52)	≤0.1 ———	±10	>100	≥30K ———
	132 _{Te}		≤0.007	\$7	>7	≥21K ———
	227 _{Th}	Tellurium (52)	50.2	s200	>200	≥30K ———
	229 _{Th}	Thorium (90)	≤0.006	50	>6	≥ 16K
	23010	Therium (90)	≤0.003	±3 ———	>3	±30K
	231 _{Th}		≤1.0	≤1.000 ———	>1.000	≥30K ———
	23270	Thorium (90)	UL#	ULtt	ULII	230K —
	234 _{Th}	Thorium (90)	≤0.01	≤10	>10	230K
	Th (Nat)	Thorium (90)	ULIT	ULIT ———	ULII -	≥30K —
	Th (irred)	Thorium (90)	\$	\$:	≥30%
	200 ₁₁	Theilium (81)	≤0.02	≤20 ———	>20	≥30K
	20171	Theillum (81)	≤0.2	≤200 ———	>200	≥30K ———
		1		≤40 ———	>40	≥30K
	202 _{TJ}	Theilium (81)	s0.04———————————————————————————————————	≤40 ————————————————————————————————————	>40	≥30K —

^{*}Values given for solids and gases only, for liquids divide value given by 10 or divide the A₁ value by 10,000. ++Unlimited

 $[\]ddagger$ The values of A_1 and A_2 must be calculated in accordance with the procedure specified in 49CFR173.433, taking into account the activity of the fission products and of the uranium-233 in addition to that of the thorium.

TABLE APP C-3 (Continued)

Special Form Only Activity Limits for Radionuclides in Special Form. (All values in curies [Ci] unless otherwise stated.) (Continued)

Redienuclide symbol	Element & atentic number	Limited 417° (≤A ₇ /1,000)	Туре А qt у (≤А ₁)	Type 8 qty (>A ₁)	righway Route centrelled quantity (3,000 x A ₁ or 30K)
170 _{7m}	- Thullum (69)	≤0.3	≤300	>300	≥30K ———
171 _{Tm}	- Thullum (69)	£1.0 ———	£1,000	>1.000	≥30K
2300	- Uninium (92)	≤0.1 ———	≤100	>100	≥30K0
2320	- Uranium (92)	≤0.03	≤30	>30	≥30K
2330	- Urenium (92)	≤0.1 ————	≤ 100 ———	>100	≥30K
2340	- Urenium (92)	≤0.1 ———	≤100	>100	≥30K ———
2360	- Urenium (92)	≤0.1 ————	≤100	>100 ———	≥30K
2360	- Uranium (92)	≤0.2 ————	≤200 ———	>200 ———	≥30K
23 4 U	- Uranium (92)	UL++	UL++	UL#	≥30K
U (Net)	- Unanium (\$2)	UL#	UL11	ULH	≥30K ———
U (Enr<20%)	- Uranium (92)	UL11	UL#	UL#	≥30K
U (Enr>20%)	- Uranium (92)	≤0.1 ————	≤100 ————	>100	≥30K ———
U (Depl)	- Uranium (92)	UL#	ULIT -	ULTT -	≥30K ———
U (Icrad)	- ##	#	#	#	≥30K
48v	- Vanedium (23)	≤0.006	≤6	>6	≥18K ———
181 _W	Tungeten (74)	≤0.2	≤200 ———	>200 ————	≥30K
185 _W		£1.0 —	£1,000	>1.000	≥30K
187 _W		≤0.04	±40	>40	≥30K
127Xe (Uncomp)		≤0.07	±70 ———	>70	≥30K
127Xe (Comp)	- Xenon (54)	≤0.005	45	>6	≥15K ———
131mXe (Cemp)	- Xenon (54)	±0.01	s 10 ————	>10	≥30K
131mXe (Uncomp)	- Xanon (54)	≤0.1	£100 ———	>100	≥30K
133Xe (Uncomp)	- Xenen (54)	£1.0	£1.000	>1.000	≥30K —
133Xe (Ceme)	- Xenen (54)	×0.005 ———	s6 ———	>5	≥15K ———
135 _{Xe} (Uncerno)	- Xenen (54)	≤0.07	£70 ———	>70	≥30K ———
135 _{Xe} (Comp)	- Xenen (64)	≤0.002	≤2 ———	>2	≥6K
87 _Y	- Yttriam (38)	≤0.02	≰20 ————	>20	≥30K
90y	Yttrium (29)	≤0.01	s10	>10	≥30K
91my	- Yttrium (39)	≤0.03	≤30 ———	>30	≥30K
917	- Yttrium (39)	≤0.03 ———	≤30 ———	>30	≥30K
92 _Y	- Yeslum (39)	≤ 0.01	£10 ———	>10	≥30K
93 _Y	- Yttsken (39)	≤0.01	£10	>10	≥ 30K
169 _{Yb}	- Ytteblum (70)	±0.08	±80	>80	≥30K
175 _{Yb}	Yttebium (70)	≤0.4	≤400 ———	>400 ———	≥30K
65 _{Zn}	Zinc (30)	≠0.03	±30	>30	≥30K ———
69m _{Zn}	- Zinc (30)	≤0.04	≤40 ———	>40	≥30K
672n	- Zinc (30)	≤0.3 ———	≠300	>300	≥30K
93 _{2r}	Ziroenium (40)	≤1.0 ———	≤1,000 ———	>1,000	≥30K
95 _{2r}	Ziroonium (40)	≤0.02	≤20 ———	>20	≥30K
972,	- Zirosnium (40)	≤0.02	s20 ———	>20	≥30K

^{*}Values given for solids and gases only, for liquids divide value given by 10 or divide the A1 value by 10,000.

()

 \mathbb{C}

PEB408-134

⁺⁺ Unlimited

^{##}The values of A₁ and A₂ must be calculated in accordance with the procedure specified in 49CFR173.433, taking into account the activity of the fission products and of the plutonium leotopes in addition to that of the uranium.

RADIOACTIVE MATERIAL CHARACTERIZATION

 \bigcirc

ار بدر د بدر بدر

C

* *

 \bigcirc

Manual Section Page Effective Date WHC-CM-2-14 Appendix C C-19 of C-34 March 20, 1989

TABLE APP C-4

ACTIVITY LIMITS FOR RADIONUCLIDES IN NORMAL FORM

Manua 1 Section Page Effective Date

WHC-CM-2-14 Appendix C C-20 of C-34 March 20, 1989

TABLE APP C-4

Normal Form Only Activity Limits for Radionuclides in Normal Form. (All values in curies [CI] unless otherwise stated.)

	Radionuolide symbol	Bement & atemic	, Limited aty*	Тура А цту	Туре В ску	Highway Route
		member	(#A ₂ /1,900)	(≤A ₂)	DA ₂)	controlled quantity (3,000 × A ₂ or 30K)
	227 _{Ac}	Activium (89) —	≤0.003 mCi ——	≤0.003	>0.003	≥9
	228 _{Ac}	Activition (89)	≤0.004	s4	>4	≥12K ———
	105 _{Ag}	Silver (47)	≤0.04	540 ———	>40	≥30K
1	110mAg	Silver (47)	≤0.007 ————	s7	>7 ———	≥21K ———
	111Ag	Silver (47)	≤0.02	s20	>20	≥30K —
	241 _{Am} • • • • • • • • • • • • • • • • • • •	Americium (95)	≤0.008 mCl ———	≤0.008	>0.008 ———	≥24
	243 _{Am}	Americhan (95)	≤0.008 mCl ——	£0.008 ———	>0.008 ————	≥24
	37Ar (Comp/Uncomp)	Argen (18)	±1.0 ———	£1,000	>1,000	≥30K ———
	41Ar (Uncomp)	Argon (18)	≤0.02	s20	>20	≥30K ———
	41Ar (Comp)	Argon (18) ————	≤0.001 ———	£1.0 ———	>1.0	≥3K ———
	73 _{As}	Amenic (33)	≤0.4	≤400 ———	>400 ———	≥30K
	74 _{As}	Arsenic (33)	≤0.02	≤20	>20	≥30K ———
ĺ	76As	Arsenic (33)	≤0.1	£10	>10	≥30K
' i	77 _{As}	Arsenic (33)	≤0.02	≤20 ———	>20	≥30K ———
	211 _{A1}	Astatine (85)	≤0.007 ———	±7 ———	>7	
	193 _{A4}	Gold (79)	≤0.2		1 ' '	≥21K
,	196 _{Au}	Geld (79)		≤200	>200 ———	≥30K
	196 _{AU}		±0.03	≤30 ———	>30	≥30K ———
ļ	199 _{Au}	Geld (79)	≤0.02	≤20 ———	>20	≥30K
	131 _{Be}	Gold (79)	≤0.025 ———	£25 ———	>25	≥30K
		Rarium (56)	≤0.04	s40	>40	≥30K
	133 _{8a}	Berlum (\$6)	±0.01	≤10 ————	>10	≥30K
1	140ga	Berkum (56)	≤0.02	≤20 ———	>20	≥30K ———
	7 ₈₀	Barythum (4)	≤0.3	≤300	>300	≥30K ———
	206gr	Biomuth (83)	≤0.005	≤5	*	≥15K ———
	2078	Blomuth (B3)	≤0.01 ———	±10 ———	>10	≥30K ———
	210gi (RaE)	Blomush (\$3) ———	≤0.004	4	*	2 12K —
i	2128	Blomush (83)	≤0.006	×6	* ——	≥18K
	249 _{8k}	Borkelium (97)	≤0.001 ———	£1.0 ————	>1.0	±3K
	77 _{br}	Bromine (35)	≤0.025 ———	≤25 ————	>25	≥30K ————
	829,	Bramine (35)	±0.00€	≤6	×	≥16K
1	11c	Certson (6)	±0.02 ———	≤20 ———	>20	≥30K ———
1	14c	Certen (6)	±0.06	≤60	>60	≥30K
1	45ca	Catalium (20)	≤0.025	≤25 ————	>25	≥30K ———
	47Ga	Gatolum (20)	≤0.02	≰20 ———	>20	≥30K ———
ļ	109 _{Cd}	Codmium (48)	≤0.07 ———	≤70 ———	>70	≥30K ———
	115mCd	Cadmium (48)	≤0.03	£30 ———	>30	≥30K
ļ	115 _{Cd}	Cadmium (48)	±0.02———	≤20	>20	≥30K
İ	139 _{Ce}	Corkum (64)	±0.01	≤ 100	>100	≥30K
	141 _{Ce}	Corlum (58)	≤ 0.025 ———	≤25 ———	>25	≥30K ———
ŀ	143 _{Ce}	Certum (58)	≤0.02	≤20 ———	>20	≥30K ———
. [144 _{Ce}	Corlum (58)	≤0.007	£7 ———	>7	≥21K ———
ŀ	249 _{Cf}	Californium (98)	≤0.002 mCi	≤0.002	>0.002 ———	≥6
. 1	250 _{C!}	Californium (86)	≤0.007 mCi	≤0.007	>0.007	≥21
J	252 _{Cf}	Celifornium (96)	±0.009 mC!	±0.009 ———	>0.008	≥27 ———
1	36 _{Cl}	Chierine (17)	≤0.01 ———	≤10	>10	≥30K —
1	3\$CI	Chlorine (17)	≤0.01	£10 ———	'>10	≥30K ———
1	242 _{Cm}	Curium (96)	≤0.0002	≤0.2 ———	>0.2 ———	≥000
į	243 _{Cm}	Curlum (96) ———	±0.009 mCl	≤0.009	>0.009 ———	≥27
i	244 _{Cm}	Curium (96) ————	≤0.010 mCi	≤0.01	>0.01 ————	≥30
l	245 _{Cm}	Curium (96)	≤0.006 mCi	≤0.006	>0.006 ———	≥18
Į.	246 _{Cm}	Curium (95) ————	≤0.008 mCl ———	±0.006 ———	>0.006	≥18 ———
į	56 _{Co}	Cebelt (27)	≤0.006 ———	≤5	>5	≥15K ———
	57Co	Cobelt (27)	≰0.09 ———	≤90	>#0	≥30K ———
į	58mCo	Cobelt (27)	≤1.0 ————	≤1,000	>1,000	≥30K
į	58Co	Cobelt (27)	≤0.02	≤20 ———	>20	≥30K
ļ	60 _{Co}	Cobelt (27)	≤0.007 ———	47	>7	≥21K ————
I	51Cr —	Chromium (24) ———	≤0.6 ————	≤600	>600 ———	≥30K ———
Ī	129 _{Cs}	Cesium (55) ————	≤0.04	≤40	>40	≥30K ————
•	131 _{Cs}	Cesium (55) ———	≤1.0	£ 1,000	>1,000 ———	≥30K ———
į	134m _{Cs}	Cesium (55) ———	≤0.01 ———	≤ 10 ·····	>10	≥30K ———
1						

 ^{*}Values given for solids and gases only, for liquids divide value given by 10 or divide the A2 value by 10,000.
 **For shipments solely within the United States the A2 value is 20 Ci for americium and plutonium contained in Am-Be or Pu-Be neutron sources or in nuclear-powered pacemakers.

Ç...

9

ന ത

 \bigcirc

1 to

TABLE APP C-4 (Continued)

Normel Form Only

Activity Limits for Radionuclides in Normal Form. (All values in curies (CI) unless otherwise stated.) (Continued)

Redervelide symbol	Bamurit & stemis number	Limited qty* (≤A ₂ /1,009)	Type A qty · (≤A ₂)	Type B qty (>A ₂)	controlled quanti (3,000 × A ₂ or 3
134 _{Ce}	Cestum (55)	≤0.01	s10	>10	≥30K
135 _{Cs}	Cesium (58)	≤0.025	±25	>25	≥30K
136 _{Ca}	Ceeium (58)	≤0.007	57	>7	≥21K
137 _{Ga}	Coolum (SE)	≤0.01	±10 —	>10	≥30K
64Cu		1			
67 _{Cu}	Copper (29)	≤0.025	≤25	>25	≥30K
	Copper (29)	≤0.025	≤25	>25	≥30K
165 _{Dy}	Dyspresium (56)	±0.02———	≤20	>20	≥30K
166 _{DV}	Dyspresium (66)	≤0.025	≤25 ———	>25	≥30K
169 _{Er}	Erbium (68)	±0.025	≤25	>25	≥30K
1716	Erbium (68)———	≤0.02	s20 ———	>20	≥30K
162mgu	Europium (63)	≤0.03	≾30	>30	≥30K
152gg	Europium (63)	≤0.01	±10	>10	≥30K
16464	Surreign (63)	≤0.006	s5	>5	≥15K
155 _{Es}	Surgetum (63)	≤0.06	1 = -	>40	230K
			≤60		1
18¢	Fluorine (\$)	≤0.02	≤20	>20	≥30K
52 _{Fe}	Iren (26)	≤0.006 ———	≤5	>5	≥15%
55 _{Fe}	iren (26)	≤1.0 ———	£1,000 ———	>1,009 ———	≥30K
59Fe	iron (26)	≤0.01	≤10	>10	≥30K
67 _{Ge}	Gaillium (31)	≤0,1 ———	£100 ———	>100	≥30K
68 _{Ge}	Gaillium (31)	≤0.02	\$20	>20	≥30K ———
72 _{Ge}	Gallian (31)	≤0.007	±7	>7	≥21K —
153 _{G4}				1	•
	Gadolinium (64) ——	≤0.1 :	≤100	>100 ———	≥30K
159 _{Gd}	Gadelinium (64)	≤0.02	≼20 ———	>20	≥30K
6EG+	Germanium (32)	≤0.01	±10 ———	>10	≥30K
71ge	Germanium (32) ———	s1.0 ———	≤1,000 ———	>1,000	≥30K
3H	Hydrogen (1)	+- 	+	+	t
167 _H	Hefnium (72)	≤0.025	≤25 ———	>25	≥30K
197mHg	Managery (80)	±0.2 ———	≤200	>200	≥30K
187 _{Hg}	Mercury (80) ———	≤0.2	≤200	>200 ———	≥30K
20314	Marsary (80)	≤0.025 —	≤25	>25	≥30K —
166140	Holmium (67)	10.03	t	>30	≥30K ———
123,	1		130		
•	ledino (53)	±0.06	±50 ———	>60	≥30K
125,	ladite (53)	≤0.07	≤70 ———	>70	≥30K ———
125	lodine (53)	≤0.01	x10	>10	≥30K
129,	lodine (53)	≤0.002	£2	>2	≥6K
131,	fodine (53)	≤0.01	≤10 ———	>10	≥30K —
132	lodine (53)	≤0.007	37	>7	≥21K ———
133,	lodine (53)	≤0.01	\$10	>10	≥30K
134	lodine (53)	≤0.008	s8	>#	≥24K —
135	lodine (53)	≤0.01	s10	>10	≥30K
111 _{le}	1 ' '				
1137	Indium (49)	≤0.025	±25	>25	≥30K
	Indian (49)	≤0.08	≤50 ————	>60	≥30K
114min	Indium (48)	≤0.02	≤20 ———	>20	≥30K
115m;n	lodium (49)	≤0.02	≤20 ———	>20	≥30K —
190 _{fr}	Iridium (77)	≤0.01	≰10 ————	>10	≥30K
192 _k	Iridium (77)	≤0.01	£10 ————	>10	≥30K
194 _{ly}	(ridium (77)	≤0.01	≤10	>10	≥30K
42 _K	Potassken (19)	≤0.01	s10 ———	>10	≥30K
43 _K	Potassium (12)	≤0.01	1 -	>10	≥30K —
85mKr (Uncomp)			≤10		
	Krypton (36)	≤0.1	≤ 100 ———	>100	≥30K
85mKr (Comp)	Клуртов (36) ———	≤0.003	≤3	>3	≥9K
85Kr (Uncomp)	Krypton (36)	s1.0 ———	≤1,000 ———	>1,000	≥30K
85Kr (Comp)	Krypton (36)	≤0.005 ———	≤5	>5 ———	≥15K
87Kr (Uncomp)	Krypton (36)	≤0.02	≤20 ———	>20	≥30K
87Kr (Comp)	Krypton (36)	≤0.0008	≤0.6 ———	>0.6	≥ 1,800-
1401.0	Lanthenum (57)	s0.03	≤30 ———	>30	≥30K
LSA (Low Specific Activity)	See 173,403 (n)				
177 _{Lu}	Lutetium (71)	r0.025		>25	
MFP	1	≤0.025	≾25	1	≥30K ———
	Mixed fission products	≤0.0004	≤0.4	>0.4	≥ 1,200
28 _{Me}	Magnesium (12)	s0.006	≤6	>6	≥1814

^{*}Values given for solids and gases only, for liquids divide value given by 10 or divide the A_2 value by 10,000. \pm See tritium.

Manual Section Page **Effective Date**

WHC-CM-2-14 Appendix C C-22 of C-34 March 20, 1989

TABLE APP C-4 (Continued)

Normal Form Only Activity Limits for Radionuclides in Normal Form. (All values in curies [CI] unless otherwise stated.) (Continued)

 Redionuolide symbol	Element & atemic number	Limited qty* (≤A ₂ /1,000)	Type A qty (≤A2)	Type B ety (>A ₂)	Highway Route centrelled quantit (3,000 × A ₂ or 30
 52 _{Mn}	Mongenese (25)	≤0.005	≤5 ———	>5	≥ 15K —
54 _{Mn}	Manganasa (25) ———	≤0.02	≤20	>20	±30K
56 _{Mn}	Managenese (25)	≤0.005 ———	≤5	>5	≥15K
99 _{Mo}	Melybdenum (42)	≤0.02	≤20 ———	>20	≥30K
13 _N	Nitrogen (7)	≤0.01	≤10 ————	>10	≥30K —
22 _{Ne}	Sedum (11)	≤0.006 —	≤8	>8	≥24K —
24 _{Na}	Sedium (11)	≤0.005	x5	>5	≥15K ———
93m ₁₄₀	Nichism (41)	\$0.2	≤200	>200	≥30K
95 _{Nb}	1	r -	£200 ———	>20-	≥30K
•	Nichium (41)	≤0.02	1		
97 _{Nb}	Misbium (41)	≤0.02	≤20 ———	>20	≥30K
147 _{Nd}	Needymium (60) ———	≤0.02	≤20	>20	≥30K
149 _{Nd}	Needymium (80)	≤0.02	≤20 ———	>20	≥30K
59 _{Ni}	Nickel (28)	≤0.9	≤900	>900 ———	≥30K
63 _{Ni}	Nickel (28) ———	≤0.1 ———	≤100	>100	≥30K
65 ₉₈	Nickei (28)	≤0.01	≤10 ———	>10	≥30K
237 _{Np}	Neptunium (93)	≤0.005 mCi	≤0.005	>0.006	≥ 15
239 _{No}	Neptanium (93)	≤0.025	≤25	>25	±30K ———
185 _{Os}	Oemium (76)	≤0.02	≤20 ———	>20	±30K ———
191 _{Oe}	Oemium (76)	≤0.2 ———	≤200	>200	≥30K —
191m _{Os}	Oemium (76)	s0.2	≤200	>200	≥30K
1930-	Osmken (76)	≤0.02	520	>200	≥30K —
32,					
1 '	Phospherus (15) ———	≤0.03	≤30 ———	>30	≥30K
230pa	Pretectinium (91)	≤0.0008	≤0.8	>0.8	≥2,400
231pa	Protectinium (\$1)	≤0.002 m Ci ———	≤0.002 ———	>0.002 ———	≥6 ———
233 _{Pa}	Protectinium (91)———	≤0.1 ———	≤100 ———	>100	≥30K
201 _{Pb}	Leed (62)	≤0.02	≤20 ———	>20	≥30K
210 _{Pb}	Lead (82)	≤0.9002	≤0.2 ———	>0.2 ———	≥000
212 _{Pb}	Lead (\$2)	≤0.006	≤6	×	±18K
103 pd	Palladium (48)	≤0.7 ———	≤700	>700 ———	≥30K
109 _{Pd}	Palladium (46)	≤0.02	≤20 ———	>20	≥30K
147 _{Pm}	Premethium (61)	≤0.025	≤25 ———	>25	≥30K ———
149 _{Pm}	Promethium (61)	≤0.02	£20 ———	>20	≥30K —
210po	Polenium (84)	≤0.0002	≤0.2	>0.2	≥600 ———
142pr	Presedymlum (59)	≤0.01	£10 ———	>10	±30K
143 _{Pr}	Present/mium (68)	≤0.02	≤20	>20	≥30K
191 _{Pt}	Pletinum (78)	≤0.1 ———	s100	>100 ———	≿30K
193mpt	Pletinum (78)	s0.2 —	≤200	>200	≥30K —
197mp;	Pletinum (78)	≤0.02	£20 ———	>20	≥30K
197 _{P1}	Pletinum (78)	£0.02	s20	>20	≥30K —
239-	Plutonium (94)	≤0.003 mCi	s0.003 —	>0.003	29
239 _{Pu}) · · · ·	±0.002 mCi —	±0.002 ———	>0.002	
240 _{PU}	Plutonium (94)				≥6
	Photonium (84) ———	≤0.002 mCi ——	≤0.002	>0.002	≥6
241pu	Plutonium (94)	≤0.0001	≤0.1 ———	>0.1	≥300
242 _{Pu}	Plutenium (94)	≤0.003 mCl	≤0.003 ———	>0.003	≥9
223 _{Re}	Redum (88)	≤0.0002	≤0.2	>0.2	≥900
224 _{Ré}	Redium (88)	≤0.005	≤0.5 ————	>0.5	≥1,500
226 _{Re}	Radium (88)	≤0.05 mCi	≤0.05	>0.05	≥150
228 _{Re}	Redium (88)	≤0.05 mCl ———	≤0.05	>0.05	≥ 150
81 _{Rb}	Rubidium (37) ———	≤0.025	£25 ———	>25	≥30K —
96 _{Rb}	Nubidium (37)	≤0.03	s30 ———	>30	≥30K
87 _{Rb}	Rubidium (37)	ULIII —	ULff ———	UL11	≥30K
Rb (Net)	Rubidium (37)	UL11	UL# —	UL++	≥30K
186 _{Re}	Rhenium (75)	≤0.02	≤20	>20	≥30K
187 _{Re}	Phonium (75)	UL#	UL++	UL++	≥30K
188 _{Re}	Rhenium (75)	≰0.01	≤10 ———	>10	≥30K
Re (Nat)	Rhenium (75)	UL++	UL##	UL++	≥30K
103mgh	Rhodium (45)	≤1.0 ———	s1.000	>1,000	≥30K —
105 _{Rh}	Rhodium (45)	≤0.025	≤25 ———	>25	≥30K
222 _{Rn}	Radon (86)	≤0.025	52	>2	≥6K
97 _{Ru}	Ruthenium (44)	≤0.08	≤80	>80	≥30K —
I PAGE	1 114 (AMERICAN 1444)				

^{*}Values given for solids and gases only, for liquids divide value given by 10 or divide the A_2 value by 10,000. *For shipments solely within the United States the A_2 value is 20 Ci for americium and plutonium contained in Am-Be or Pu-Be neutron sources or in nuclear-powered pacemakers. ††Unlimited.

477

O

C

RADIOACTIVE MATERIAL CHARACTERIZATION

Manual Section Page Effective Date WHC-CM-2-14 Appendix C C-23 of C-34 March 20, 1989

TABLE APP C-4 (Continued)

Normal Form Only Activity Limits for Radionuclides in Normal Form. (All values in curies (CI) unless otherwise stated.) (Continued)

Redienusiide symbol	Element & atomic number	Limited qty* (≤A ₂ /1,000)	Type A qty (≤A ₂)	Type # qty (>A ₂)	centrolled quantit (3,000 × A ₂ or 3)
1030	Ruthenium (44)	≤0.025 —	≤25	>25	≥30K
05		≤0.02	≤20 —	>20	≥30K
066	Ruchenium (44)	≤0.007	17	>7	≥21K —
·· ·	Rusherium (44)		l = -	>00	≥30K
6g	Suiter (16)	≤0.06	≤60	>30	≥30K
223	Antimony (51)	≤0.03	≤30 ———	>5	≥15K
2434	Andmany (51)	≤0.006	s\$	1	
25%	Antimony (51)———	s0.026	≤25 ———	>25	≥30K
434	Scendium (21)	≤0.00€	≤8	>8	≥24K
7 _{5e}	Seandlen (21)	±0.02	≤20 ———	>20	≥30K ———
4 ₅₄	Soundhum (21)	≤0.005	≤5	×5	≥ 15K
7530	Selenium (34)	≤0.04	≤40 ———	>40	≥30K
1153	Silicon (14)	±0.02	≤20 ———	>20	≥30K
47 _{5m}	Samarium (62) ———	ULH	UL11	ULIT	≥30K
51 _{5m}	Samerken (62) ———	≤0.09	≾90 ———	>90	≥30K
153 _{5m}	Samertum (62)	≤0.02	≤20	>20	≥30K
1350	The (50)	≤0.06	≤60 ———	>60	≥30K
19mga	Tin (50)	≤0.1 ———	≤100	>100	≥30K
2550	Tin (50)	±0.01	±10 ———	>10	≥30K
5mg,	Strondum (383	±0.0€	≤80 ———	>80	≥30K
169.	Strondum (38)	≤0.03	s30 ———	>30	≥30K
17mg,	Strondum (38)	≤0.05	≤50 ———	>50	≥30K ———
194	Strenden (38)	±0.01	≤10	>10	≥30K —
C ₂ ,		≤0.0004	≤0.4	>0.4	≥1,200
1134	Stronthum (38)	≤0.004	±10 —	>10	≥30K —
128.	Strendam (36)	±0.01	±10	>10	230K
(Uncomp)	Tricken (1)	±20	±1.000 —	>1,000	≥30K —
• • • • • • • • • • • • • • • • • • • •	Trickion (1)	≤20 ———	s1.000	>1.000	≥30K
(Compl			£1,000 ———	>1.000	230K
(Activated luminous paint)	Tridum (1)	±20 ———		>1,000	230K -
(Absorbed on solid) ——	Trithan (1)	≤20 ———	≤1,000		≥30K —
[Tritleted water]———	Trithan (1)	<0.1 Cl/liter	≤1.008	>1.000	23000
	Į.	0,1-1.6 Cl/Ster			1
		>1.0 Cl/liter			
[(other forms)	Tritium (1) ———	±0.02	≤20 ———	>20	≥30K
182 _{Te}	Tantalum (73)	≤0.02	≾20 —	>20	≥30K
160-ть	Terblum (65)	≤0.02	≤20	>20	≥30K ——
Many G.	Technetium (43)	≤1.0 ————	±1,000	>1,000 ———	≥30K
P\$TG	Technosium (43)	≤0.006	≤€	>6	≥18K
37m _{TC}	Technetium (43)	≤1.0 ———	≤1,000	>1,000	≥30K
37 _{Tq}	Technetium (43)	≤1.0 ————	≤1,000	>1.000 ———	≥30%
3m 7g	Technotium (43)	≤0.1 ————	≤100	>100	≥36K
19 _{Ta}	Technotium (43)	≤0.025	≤25 ———	>25	≥30K
125 m;	Telksium (52)	≤0.1 ———	≤100	>100	≥30K ———
127mg	Tellurium (52)	≤0.02	≤20 ———	>20	≥30K
27₹●	Tellurium (52)	≤0.02	≤20 ———	>20	≥30K
129m _{Te}	Tellurium (52)	≤0.01	±10 ———	>10	≥30K
129 _{Te}	Tellurium (52)	≤0.02	≤20 ———	>20	≥30K
131mTe	Tellurium (52)	≤0.01	≤10 ———	>10	≥30K ———
132 _{Te}	Teikurkern (52)	≤0.007	±7 ————	>7	≥21K
227 _{Th}	Therium (90)	≤0.0002	≤0.2 ———	>0.2	≥600
228 _{Th}	Therium (90)	≤0.008 mCi	≤0.008	>0.008	≥24
230 _{Th}	Therium (90)	≤0.003 mCl	≤0.003 ————	>0.003	29
231 _{7h}	Therium (90)	≤0.025	≤25 ————	>25	≥30K
23210	Thorium (90)	ULtt ———	ULH	UL:+	≥30K
234 _{Th}	Thorium (90)	≤0.01	≤10 ———	>10	≥30K ———
Th (Net)	Therium (90)	ULIT —	ULH —	UL##	≥30K
Th (Irrad)	Therium (90)	3	t	±	≥30K
2001	Theilium (81)	≤0.02	≤20 ———	>20	≥30K —
20171	Thellium (81)	≤0.2	≤200	>200	≥30K
2021	1 ' '	≤0.2	540	>40	≥30K
20417	Theilium (81)		1	1	≥30K —
	Theilium (51)	≤0.01 ———	i ≤ 10	>10	- COUR

[&]quot;Values given for solids and gases only, for liquids divide value given by 10 or divide the A_2 value by 10,000. $\rat{1}$ Unlimited

 $^{^{+}}$ The values of A_1 and A_2 must be calculated in accordance with the procedure specified in 49CFR173.433, taking into account the activity of the fission products and of the wanium-233 in addition to that of the thorium.

RADIOACTIVE MATERIAL CHARACTERIZATION

Manual Section Page

Effective Date

WHC-CM-2-14 Appendix C C-24 of C-34 March 20, 1989

TABLE APP C-4 (Continued)

Normal Form Only Activity Limits for Redionuclides in Normal Form. (All values in curies [Ci] unless otherwise stated.) (Continued)

Radionuciide symbol	Element & atemic number	Limited qty* {≤A ₂ /1,900}	Type A qty (≤A ₂)	Type B qty (>A ₂)	Highway Rour controlled quen (3.000 × A ₂ or
170 _{7m}	Thelium (69)	≠0.01	±10	>10	≥30K
171 _{Ten}	Thullum (09)	≤0.01	≤10	- >10	≥30K
2300	Unanium (92)	≤0.0001	≤0.1	- >0.1	≥300 —
2320	Uranium (92)	≤0.03 mCi	≤0.03		≥90
233 _U	Uranium (\$2) ———	≤0.0001	≤0.1	- >0.1	≥300
2340	Uranium (\$2) ———	≤0.0001	£0.1 ————	- >0.1 ————	≥300
235 _U	Uranium (\$2)	≤ 0.0002	s0.2	- >0.2	≥600
236U	Uranium (\$2)	≤C.0002	≤0.2	- >0.2	≥600
238 _U	Uranium (92)	UL##	UL#	- UL++	≥30K
U (Nat)	Uranium (92)	UL#1	ULH -	- DL++	≥30K
U (Enr<20%)	Uranium (92)	UL#	UL##	- UL++	≥30K
U (Enr>20%)	Uranium (82)	≤0.0001	≤0.1	- >0.1	≥300
U (Depl)	Uranium (92)	UL#	UL#	UL#	≥30K
U (irred)	##	#	#	- 81	≥30K
48 _V	Vanadium (23)	≤0.006	≤6	>6	≥18K
181w	Tungsten (74)	≤0.2 ———	≤200 ————	>200	≥30K
185 _W	Tungeten (74)	≤0.025	≤25	>25	≥30K
187 _W	Tungeten (74)	≤0.02	≤20	>20	≥30K
127Xe (Uncomp)	Xenon (54)	≤0.07	≤70	>70	≥30K ——
127Xe (Comp)	Xenon (54)	≤0.005	≤5	- >5	≥15K
131m _{Xe} (Comp)	Xenen (54)	≤0.01	≤10	>10	≥30K ——
131mxe (Uncomp)	Xenon (54)	≤0.1	≤ 100	>100	≥30K
133Xe (Uncomp) ————	Xener: (54)	s1.0	x1,000	>1,000 ———	≥30K
133Xe (Comp)	Xenen (84)	±0.005 ———	≤5	>5	≥15K
135 _{Xe} (Uncomp)	Xenon (54)	≤0.07	≤70		≥30K
135Xe (Comp) ————	Xenen (54)	≤0.002	≤2	>2	≥6K
87 _Y	Ytteken (35)	≤0.02	£20 ————	>20	≥30K
90y	Yttrium (39)	≤0.01	≤10 —	- >10	≥30K
91my	Yttelum (39) ———	≤0.03	≤30 ———	>30	≥30K
91y	Yttrium (39)	≤0.03	≤30 ————	>30	≥30K
92 _Y	Yttrium (39)	≤ 0.01	≤10 —	>10	≥30K ———
93 _Y	Yttrium (39)	≤0.01	£10	>10	≥30K
169 _{Yb}	Yssebium (70) ———	≤0.08	≤80 ———	- > 8 0	≥30K ———
175 _{Yb}	Yttebium (70)	≤0.025	≤25	>25	≥30K
66 _{Zn}	Zinc (30)	≤0.03 ———	≤30 ———	>30	≥30K
69mZn	Zinc (30)	≤0.02	≤20 ———	>20	≥30K ———
67 _{Zn}	Zinc (30)	±0.02	≤20	7	≥30K
93 _{Zr}	Ziroenken (40)———	≤0.2 ———	≤200	>200	≥30K
95 _{Zr}	Ziroonium (40)	≤0.02	≤20	>20	≥30K
97 _Z ,	Zirosnium (40)	<0.02	≤20	>20	>30K

^{*}Values given for solids and gases only, for liquids divide value given by 10 or divide the A2 value by 10,000.

15

P\$8408-129

⁺⁺ Unlimited

^{**}The values of A₁ and A₂ must be calculated in accordance with the procedure specified in 49CFR173.433, taking into account the activity of the fission products and of the plutonium isotopes in addition to that of the uranium.

HAZARDOUS MATERIAL PACKAGING AND SHIPPING RADIOACTIVE MATERIAL CHARACTERIZATION

50

Q

O

C

Manual Section Page Effective Date WHC-CM-2-14 Appendix C C-25 of C-34 March 20, 1989

TABLE APP C-5

SPECIFIC ACTIVITY VALUES FOR RADIONUCLIDES

HAZARDOUS MATERIAL PACKAGING AND SHIPPING	Manual Section	WHC-CM-2-14 Appendix C
RADIOACTIVE MATERIAL CHARACTERIZATION	Page Effective Date	C-26 of C-34 March 20, 1989

TABLE -APP C-5 SPECIFIC ACTIVITY VALUES FOR RADIONUCLIDES

Element & Atomic No.	Radio- nuclide	Specific Activity* (Ci/g)	Element & Atomic No.	Radio- nuclide	Specific Activity (Ci/g)
Actinium (89)	227 _{Ac}	7.2 E+1	Beryllium (4)	7 _{Be}	3.5 E+5
Actinium	²²⁸ Ac	2.2 E+6	Bismuth (85)	206 _{Bi}	9.9 E+4
Americium (95)	241 _{Am}	3.2	Bismuth	207 _{Bi}	2.2 E+2
Americium	243 _{Am}	1.9 E-1	Bismuth	210 _{Bi}	1.2 E+5
Antimony (51)	122 _{Sb}	3.9 E-5	Bismuth	212 _{Bi}	1.5 E+7
Antimony	¹²⁴ Sb	1.8 E+4	Bromine (35)	77 _{Br}	7.1 E+5
Antimony	125 _{Sb}	1.4 E+3	Bromine	82 _{Br}	1.1 E+6
Argon (18)	37 _{Ar}	1.0 E+5	Cadmium (48)	. ¹⁰⁹ Cd	2.6 E+3
Argon	41 _{Ar**}	4.3 E+7	Cadmium	115m _{Cd}	2.6 E+4
Arsenic (33)	73 _{As}	2.4 E+4	Cadmium	115 _{Cd}	5.1 E+5
Arsenic	⁷⁴ As	1.0 E+5	Calcium (20)	⁴⁵ Ca	1.9 E+4
Arsenic	76 _{As}	1.6 E+6	Calcium	47 _{Ca}	5.9 E+5
Arsenic	77 _{As}	1.1 E+6	Californium (98)	249 _{Cf}	3.1
Astatine (85)	211 _{At}	2.1 E+6	Californium	250 _{Cf}	1.3 E+2
Barium (56)	131 _{Ba}	8.7 E+4	Californium	252 _{Cf}	6.5 E+2
Barium	133 _{Ba}	4.0 E+2	Carbon (6)	11 _C	8.4 E+8
Barium	140 _{Ba}	7.3 E+4	Carbon	¹⁴ c	4.6
Berkelium (97)	249 _{Bk}	1.8 E+3	Cerium (58)	139 _{Ce}	6.5 E+3

^{*}The notation E+4 means \times 10⁴; E-4 means \times 10⁻⁴. **Uncompressed gas only.

estima Past

HAZARDOUS	MATERIAL	PACKAGING
AND SHIPP	ING	

Manual Section Page WHC-CM-2-14 Appendix C C-27 of C-34 March 20, 1989

RADIOACTIVE MATERIAL CHARACTERIZATION

Page Effective Date

	Element & Atomic No.	Radio- nuclide	Specific Activity (Ci/g)	Element & Atomic No.	Radio- nuclide	Specific Activity (Ci/g)
	Cerium	141 _{Ce}	2.8 E+4	Curium	243 _{Cm}	4.2 E+1
	Cerium	143 _{Ce}	6.6 E+5	Curium	244 _{Cm}	8.2 E+1
çv	Cerium	¹⁴⁴ Ce	3.2 E+3	Curium	245 _{Cm}	1.0 E-1
00000 A	Cesium (55)	¹²⁹ Cs	7.6 E+5	Curium	246 _{Cm}	3.6 E-1
\$	Cesium	131 _{Cs}	1.0 E+5	Dysprosium (66)	165 _{Dy}	8.2 E+6
0	Cesium	134m _{Cs}	7.4 E+6	Dysprosium	166 _{Dy}	2.3 E+5
	Cesium	¹³⁴ Cs	1.2 E+3	Erbium (68)	169 _{Er}	8.2 E+4
3000	Cesium	135 _{Cs}	8.8 E-4	Erbium	171 _{Er}	2.4 E+6
chianes	Cesium	¹³⁶ Cs	7.4 E+4	Europium (63)	152m _{Eu}	2.2 E+6
#807778	Cesium	¹³⁷ Cs	9.8 E+1	Europium	152 _{Eu}	1.9 E+2
O	Chlorine (17)	³⁶ c1	3.2 E-2	Europium	154 _{Eu}	1.5 E+2
***	Chlorine	³⁸ c1	1.3 E+8	Europium	155 _{Eu}	1.4 E+3
	Chromium (24)	⁵¹ cr	9.2 E+4	Fluorine (9)	¹⁸ F	9.3 E+7
	Cobalt (27)	⁵⁶ Co	3.0 E+4	Gadolinium (64)	153 _{Gd}	3.6 E+3
	Cobalt	57 _{Co}	8.5 E+3	Gadolinium	159 _{Gd}	1.1 E+6
	Cobalt	^{58m} Co	5.9 E+6	Gallium (31)	67 Ga	6.0 E+5
	Cobalt	⁵⁸ Co	3.1 E+4	Gallium	68 _{Ga}	4.0 E+7
	Cobalt	60 _{Co}	1.1 E+3	Gallium	72 Ga	3.1 E+6
2 2 4		<u>64</u>	; *		68,	

C

()

 \Box

つ ネ

Manual Section Page Effective Date

WHC-CM-2-14 Appendix C C-28 of C-34 March 20, 1989

RADIOACTIVE MATERIAL CHARACTERIZATION

Element & Atomic No.	Radio- nuclide	Specific Activity (Ci/g)	Element & Radi Atomic No. nucl	
Gold	196 _{Au}	1.2 E+5	Iron (26) 52	Fe 7.3 E+6
Gold	198 _{Au}	2.5 E+5	Iron 55	Fe 2.2 E+3
Gold	199 _{Au}	2.1 E+5	Iron 59	Fe 4.9 E+4
Hafnium (72)	181 _{Hf}	1.6 E+4	Krypton (36) 85m	¹ Kr 8.4 E+6
Holmium (67)	166 _{Ho}	6.9 E+5	Krypton 85	Kr 4.0 E+2
Iodine (53)	123 _I	1.9 E+6	Krypton 87	Kr 2.8 E+7
Iodine	125 _I	1.7 E+4	Lanthanum (57) ¹⁴⁰	La 5.6 E+5
Iodine	126 _I	7.8 E+4	Lead (82) 210	Pb 8.8 E+1
Iodine	129 _I	1.6 E-4	Lead 212	Pb 1.4 E+6
Iodine	131 _I	1.2 E+5	Lutetium (71) 177	Lu 1.1 E+5
Iodine	132 _I	1.1 E+7	Magnesium (12) 28	Mg 5.2 E+6
Iodine	133 _I	1.1 E+6	Manganese (25) 52	Mn 4.4 E+5
Iodine	134 _I	2.7 E+7	Manganese 54	Mn 8.3 E+3
Iodine	135 _I	3.5 E+6	Manganese 56	Mn 2.2 E+7
Indium (49)	111 _{In}	4.2 E+5	Mercury (80) 197m	
Indium	113m _{In}	1.6 E+7	Mercury 197	Hg 2.5 E+5
Indium	114m _{In}	2.3 E+4	Mercury 203	Hg 1.4 E+4
Indium	115m _{In}	6.1 E+6	Molybdenum (42)	Mo 4.7 E+5
Iridium (77)	190 _{Ir}	6.2 E+4	Neodymium (60) 147	Nd 8.0 E+4
Iridium	192 _{Ir}	9.1 E+3	Neodymium 149	Nd 1.1 E+7
Iridium	194 _{Ir}	8.5 E+5	Neptunium (93) 237	Np 6.9 E-4

RADIOACTIVE MATERIAL CHARACTERIZATION

€.

\$1.7°

О

Manual Section Page Effective Date WHC-CM-2-14 Appendix C C-29 of C-34 March 20, 1989

	Element & Atomic No.	Radio- nuclide	Specific Activity (Ci/g)	Element & Atomic No.	Radio- nuclide	Specific Activity (Ci/g)
	Neptunium	239 _{Np}	2.3 E+5	Plutonium	239 _{Pu}	6.2 E-2
	Nickel (28)	59 _{Ni}	8.1 E-2	Plutonium	240 _{Pu}	2.3 E-1
	Nickel	63 _{Ni}	4.6 E+2	Plutonium	241 _{Pu}	1.1 E+2
<u>†</u>	Nickel	65 _{Ni}	1.9 E+7	Plutonium	242 _{Pu}	3.9 E-3
•	Niobium (41)	93m _{Nb}	1.1. E+3	Polonium (84).	210 _{Po}	4.5 E+3
<u>.</u>	Niobium	95 _{Nb}	3.9 E+4	Potassium (19)	42 _K	6.0 E+6
	Niobium	97 _{Nb}	2.6 E+7	Potassium	43 _K	3.3 E+6
ı	Nitrogen (7)	13 _N	1.5 E+9	Praseodymium (59)	142 _{Pr}	1.2 E+6
	Osmium (76)	¹⁸⁵ 0s	7.3 E+3	Praseodymium	143 _{Pr}	6.6 E+4
•	Osmium	¹⁹¹ 0s	4.6 E+4	Promethium (61)	147 _{Pd}	9.4 E+2
	Osmium	^{191m} 0s	1.2 E+6	Promethium	149 _{Pd}	4.2 E+5
	Osmium	193 _{0s}	5.3 E+5	Protactinium (91)	230 _{Pa}	3.2 E+4
	Palladium (46)	103 _{Pd}	7.5 E+4	Protactinium	231 _{Pa}	4.5 E-2
	Palladium	109 _{Pd}	2.1 E+6	Protactinium	233 _{Pa}	2.1 E+4
	Phosphorus (15)	32 _p	2.9 E+5	Radium (88)	223 _{Ra}	5.0 E+4
	Platinum (78)	191 _{Pt}	2.3 E+5	Radium	224 _{Ra}	1.6 E+5
	Platinum	193m _{Pt}	2.0 E+5	Radium	226 _{Ra}	1.0
	Platinum	197m _{Pt}	1.2 E+7	Radium	228 _{Ra}	2.3 E+2
	Platinum	197 _{Pt}	8.8 E+5	Radon (86)	222 _{Rn}	1.5 E+5
	Plutonium (94)	238 _{Pu}	1.7 E+1	Rhenium (75)	186 _{Re}	1.9 E+5

HAZARDOUS MATERIAL PACKAGING AND SHIPPING	Manual Section	WHC-CM-2-14 Appendix C
RADIOACTIVE MATERIAL CHARACTERIZATION	Page Effective Date	C-30 of C-34 March 20, 1989

TABLE APP C-5 (Continued)

Element & Atomic No.	Radio- nuclide	Specific Activity (Ci/g)	Element & Atomic No.	Radio- nuclide	Specific Activity (Ci/g)
Rhenium	187 _{Re}	3.8 E-8	Silicon (14)	31 _{Si}	3.9 E+7
Rhenium	188 _{Re}	1.0 E+6	Silver (47)	105 _{Ag}	3.1 E+4
Rhenium	Re (natural)	2.4 E-8	Silver	110m _{Ag}	4.7 E+3
Rhodium (45)	103m _{Rh}	3.2 E+7	Silver	111 _{Ag}	1.6 E+5
Rhodium	105 _{Rh}	8.2 E+5	Sodium (11)	22 _{Na}	6.3 E+3
Rubidium (37)	81 _{Rb}	8.2 E+6	Sodium.	24 _{Na}	8.7 E+6
Rubidium	86 _{Rb}	8.1 E+4	Strontium (38)	85mSr ·	3.2 E+7
Rubidium	87 _{Rb}	6.6 E-8	Strontium [*]	⁸⁵ Sr	2.4 E+4
Rubidium	Rb (natural)	1.8 E-8	Strontium	87m _{Sr}	1.2 E+7
Puthonium (44)	97 _{Ru}	5.5 E+5	Strontium	⁸⁹ sr	2.9 E+4
Ruthenium (44)	103 _{Ru}		Strontium	90 _{Sr}	1.5 E+2
Ruthenium	105 _{Ru}	3.2 E+4	Strontium	⁹¹ Sr	3.6 E+6
Ruthenium	106 _{Ru}	6.6 E+6	Strontium	92 _{Sr}	1.3 E+7
Ruthenium	147 Sm	3.4 E+3	Sulphur (16)	³⁵ s	4.3 E+4
Samarium (62)	151 _{Sm}	2.0 E-8	Tantalum (73)	182 _{Ta}	6.2 E+3
Samarium	153 _{Sm}	2.6 E+1	Technetium (43)	96m _{Tc}	3.8 E+7
Samarium	46 Sc	4.4 E+5	Technetium	⁹⁶ Tc	3.2 E+5
Scandium (21)	47 Sc	3.4 E+4	Technetium	97m _{Tc}	1.5 E+4
Scandium		8.2 E+5	Technetium	97 _{Tc}	1.4 E-3
Scandium	^{.48} Sc ⁷⁵ Se	1.5 E+6	Technetium	99m _{Tc}	5.2 E+6
Selenium (34)	′ Se	1.4 E+4	Technetium	⁹⁹ Tc	1.7 E-2

Q

/**<u>`</u>

Manual Section Page WHC-CM-2-14 Appendix C C-31 of C-34 March 20, 1989

RADIOACTIVE MATERIAL CHARACTERIZATION

Effective Date

	Element & Atomic No.	Radio- nuclide	Specific Activity (Ci/g)	Element & Atomic No.	Radio- nuclide	Specific Activity (Ci/g)
	Tellurium (52)	125m _{Te}	1.8 E+4	Thulium	171 _{Tm}	1.1 E+3
	Tellurium	127m _{Te}	4.0 E+4	Tin (50)	113 _{Sn}	1.0 E+4
	Tellurium	¹²⁷ Te	2.6 E+6	Tin	¹²⁵ Sn	1.1 E+5
C !	Tellurium	129m _{Te}	2.5 E+4	Tritium (1)	3 _H	9.7 E+3
O)	Tellurium .	129 _{Te}	2.0 E+7	Tungsten (74)	181 _W	5.0 E+3
9	Tellurium	131m _{Te}	8.0 E+5	Tungsten	185 _W	9.7 E-3
O	Tellurium	132 _{Te}	3.1 E+5	Tungsten	187 _W	7.0 E+5
	Terbium (65)	160 _{Tb}	1.1 E+4	Uranium (92)	230 _U	2.7 E+4
~	Thallium (81)	200 _{T1}	5.8 E+5	Uranium	231 _U	2.1 E+1
1840/Ab	Thallium	²⁰¹ T1	2.2 E+5	Uranium	233 _U	9.5 E-3
*****	Thallium	²⁰² T1	5.4 E+4	Uranium	234 _U	6.2 E-3
O .	Thallium	²⁰⁴ T1	4.3 E+2	Uranium	235 _U	2.1 E-6
ium " ,	Thorium (90)	227 _{Th}	3.2 E+4	Uranium .	236 _U	6.3 E-5
	Thorium	228 _{Th}	8.3 E+2	Uranium	238 _U	3.3 E-7
	Thorium	230 _{Th}	1.9 E-2	Uranium (enr)		Table A-4
	Thorium	231 _{Th}	5.3 E+5	Vanadium (23)	⁴⁸ v	1.7 E+5
	Thorium	232 _{Th}	1.1 E-7	Xenon (54)	¹²⁷ Xe	2.8 E+4
	Thorium	234 _{Th}	2.3 E+4	Xenon	131m _{Xe}	1.0 E+5
	Thorium	Th (natural)	2.2 E-7	Xenon	133 _{Xe}	1.9 E+5
)	Thulium (69).	170 _{Tm}	6.0 E+3	Xenon	135 _{Xe} .	2.5 E+5

Manual Section Page WHC-CM-2-14 Appendix C C-32 of C-34 March 20, 1989

RADIOACTIVE MATERIAL CHARACTERIZATION

Page Effective Date

TABLE APP C-5 (Continued)

Element & Atomic No.	Radio- nuclide	Specific Activity (Ci/g)
Ytterbium (70)	169 _{Yb}	2.3 E+5
Ytterbium	175 _{Yb}	1.8 E+5
Yttrium (39)	87 _Y	4.5 E+1
Yttrium	90 _Y ·	2.5 E+5
Yttrium	91m _Y	4.1 E+7
Yttrium	91 _Y	2.5 E+4
Yttrium	92 _Y	9.5 E+6
Yttrium	93 _Y	3.2 E+6
Zinc (30)	65 _{Zn}	8.0 E+3
Zinc	69m _{Zn}	3.3 E+6
Zinc	69 _{Zn}	5.3 E+7
Zirconium (40)	93 _{Zr}	3.5 E-3
Zirconium	⁹⁵ Zr	2.1 E+4
Zirconium	97 _{Zr}	2.0 E+6

C.

• •

: "

9

 \Box

୍

Manual Section Page Effective Date WHC-CM-2-14 Appendix C C-33 of C-34 March 20, 1989

RADIOACTIVE MATERIAL CHARACTERIZATION

TABLE APP C-6

ACTIVITY-MASS RELATIONSHIPS FOR URANIUM (DEPLETED, NATURAL AND ENRICHED)

HAZARDOUS	MATERIAL	PACKAGING
AND SHIPP	ING	

117

 \bigcirc

.

()

RADIOACTIVE MATERIAL CHARACTERIZATION

Manual Section Page Effective Date WHC-CM-2-14 Appendix C C-34 of C-34 March 20, 1989

TABLE APP C-6

ACTIVITY-MASS RELATIONSHIPS FOR URANIUM

235 _{U*} Enrichment (wt% Present)	Specific Activity** (Ci/g)	(g/Ci)
0.0	3.3 E-7	3.0 E+6
0.45	5.0 E-7	2.0 E+6
0.72 (natural)	7.06 E-7	1.42 E+6
1.0	7.6 E-7	1.3 E+6
1.5	1.0 E-6	1.0 E+6
5.0	2.7 E-6	3.7 E+5
10.0	4.8 E-6	2.1 E+5
20.0	1.0 E-5	1.0 E+5
35.0	2.0 E-5	5.0 E+4
50.0	2.5 E-5	4.0 E+4
90.0	5.8 E-5	1.7 E+4
93.0	7.0 E-5	1.4 E+4
95.0	9.1 E-5	1.1 E+4

^{*}Figures for uranium include the activity of uranium-234, which is concentrated during the enrichment process. **The notation E-7 means \times 10⁻⁷; E+5 means \times 10⁵.

WESTINGHOUSE HANFORD COMPANY

Manual Section WHC-CM-2-14 Appendix D1, REV 0

Page

D1-1 of D1-5 August 1, 1988

Effective Date Organization

Procurement and

HAZARDOUS MATERIAL PACKAGING AND SHIPPING

on Mad

Materials Management

TITLE:

Approved by

PRENOTIFICATION REQUIREMENTS FOR OFFSITE SHIPMENTS OF SPENT FUEL AND HIGH LEVEL RADIOACTIVE WASTE

D. K. Quigley, Manager,

Procurement and Materials Mgmt

1.0 PURPOSE

The purpose of this procedure is to provide guidance for the rules to be followed in making prenotification of unclassified spent fuel and high level waste shipments offsite per the Department of Energy (DOE) directive and dated August 1, 1987.

[™] 2.0 SCOPE

1

This procedure establishes requirements to be followed by each facility originating unclassified spent fuel or high level radioactive waste shipments which are destined for transport and delivery outside the Hanford Site boundaries.

3.0 GUIDANCE AND REQUIREMENTS

- 3.1 The manager of a facility or his delegate, who intends to ship either unclassified spent fuel or high level radioactive waste outside the Hanford Site must, in cooperation with Traffic, make the following notifications:

3.1.1 For Unclassified Spent Fuel:

3.1.1.1 <u>Prenotification</u>: At least two weeks prior to the scheduled shipment departure date, the following information must be submitted to Traffic for concurrence and subsequent transmittal to DOE-Richland (DOE-RL).

NOTE: Traffic will provide items c. and e., and all carrier data.

- a. The name, address, and telephone number of the shipper and receiver.
- b. A description of the shipment as specified by the Department of Transportation in 49 CFR 172.202 and 172.203(d).
- c. A listing of the routes to be used within each State.
- d. The estimated date and time of departure from the point of origin of the shipment.

PRENOTIFICATION REQUIREMENTS FOR OFFSITE SHIPMENTS OF SPENT FUEL AND HIGH LEVEL RADIOACTIVE WASTE

Manual Section Page Effective Date

WHC-CM-2-14 Appendix D1, REV 0 D1-2 of D1-5 August 1, 1988

e. The estimated date and time of entry into each Governor's State.

f. A request that the information be protected against disclosure.

A form for data submittal (Attachment A) can be obtained from Traffic.

- 3.1.1.2 <u>Schedule Change Notice</u>: Any schedule change which differs by more than six hours from the scheduled information previously furnished must be reported by telephone or other means using the same communication channels.
- 3.1.1.3 <u>Cancellation Notice</u>: Any cancellation must be reported by telephone or other means using established communication channels. A record of how the cancellation was transmitted shall be retained for one year.
- 3.1.2 For Unclassified High Level Radioactive Waste:
- 3.1.2.1 <u>Prenotification</u>: At least two weeks prior to the scheduled shipment departure date, the following information must be submitted to Traffic for concurrence and subsequent transmittal to DOE-RL.

NOTE: Traffic will provide items d. and f. and all carrier data.

- a. The name, address, and telephone number of the shipper receiver.
- b. The address of the point of origin of the shipment and a 7-day period during which departure of the shipment is estimated to occur.
- c. A description of the waste shipment as specified by the Department of Transportation in 49 CFR 172.202 and 172.203(d).
- d. A 7-day period during which arrival of the shipment at each State boundary is estimated to occur.
- e. The destination of the shipment and the 7-day period during which arrival of the shipment is estimated to occur.
- f. A point of contact with a telephone number for current shipment information.
- g. A request that the information be protected against disclosure.

A form for submittal of this information (Attachment B) can be obtained from Traffic.

3.1.2.2 <u>Schedule Change Notice</u>: Any scheduled change which would result in a departure from the originally submitted plan would require notification by telephone or other means using the same communication channels.

0627

TOTAL STATE OF THE

 \bigcirc

¢. .

 \bigcirc

()

Manual Section Page Effective Date WHC-CM-2-14 Appendix D1, REV 0 D1-3 of D1-5

PRENOTIFICATION REQUIREMENTS FOR OFFSITE SHIPMENTS OF SPENT FUEL AND HIGH LEVEL RADIOACTIVE WASTE

August 1, 1988

- 3.1.2.3 <u>Cancellation Notice</u>: Any cancellation must be reported by telephone or other means using established communication channels. A record of how the cancellation was transmitted shall be retained for one year.
- 3.2 Traffic will review the submittal form for accuracy, completeness, regulatory compliance and provide a concurring signature. Traffic will also complete routing information and identify estimated time of arrival into each State enroute. Each submittal will be logged in and transmitted to the identified DOE-RL contact on or before the next normally scheduled work day.
- 3.3 Traffic will transmit all schedule changes and cancellations via telephone to the identified DOE-RL contacts. A logged record of the telephone communication will be retained for one year.
- 3.4 Traffic will schedule carriers and equipment for each shipment and will establish carrier procedures for notification if delays are incurred during transport.

UNIAUTIORIZED

PROTECTO AGAINST

뭂

MIST

HEN IN

THIS INFORMATION

()

C\!

...

 \bigcirc

PRENOTIFICATION REQUIREMENTS FOR OFFSITE SHIPMENTS OF SPENT FUEL AND HIGH LEVEL RADIOACTIVE WASTE

Manua 1 Section Page Effective Date

WHC-CM-2-14 Appendix D1, REV 0 D1-4 of D1-5 August 1, 1988

SHIPMENT

MUMBER

ATTACHMENT A

UNCLASSIFIED SPENT FUEL SHIPMENT

PRENOTIFICATION STATEMENT DOE CARRIER (Completed by Traffic) RECEIVER (Destination) SHIPPER (Origin Point) Name : Name:_ Сопрапу Company: Сопрану: Address: Address: Address:_ Phone: Phone:_ Phone: SHIPMENT DESCRIPTION DOT Proper Shipping Name: Hazard Class: ID# & Secondary Hazards: Quantity (MT):_ Radionuclides: Physical Form: Chemical Form: Activity (Ci):_ Labels (W-I,Y-II,Y-III):_ T.I.: Fissile Class (I,II,III): Container ID (COC #): Miscellaneous: SCHEDULED DEPARTURE Date:___ _Time:_ ROUTING INFORMATION (Completed by Traffic) State A Name: Route: Time:_ ETA Date: State B Name: Route: Time:_ ETA Date: State C Name: Time: ETA Date:_ State D Name: ETA Date: **APPROVALS** Originator Approval Signature: Date: Print Name: Traffic Department Concurrence Signature: Print Name:_ POINT OF CONTACT Department of Energy Date: Signature: Phone: Print Name:

PRENOTIFICATION REQUIREMENTS FOR OFFSITE SHIPMENTS OF SPENT FUEL AND HIGH LEVEL RADIOACTIVE WASTE

Manual
Section A
Page
Effective Date

WHC-CM-2-14 Appendix D1, REV 0 D1-5 of D1-5 August 1, 1988

SHIPMENT

ATTACHMENT B

UNCLASSIFIED HIGH LEVEL RADIOACTIVE WASTE SHIPMENT

	PREMUTIFICATION STATEMENT		NUMBER DOE
SHIPPER (Origin Point)	CARRIER (Completed by Traffic)		(Destination
Company	Kane:	Name: Company	
Company:Address:	Company:	Address:	
Add 633.	Address:		
Phone:	Phone:	Phone:	
SHIPMENT DESCRIPTION			
DOT Proper Shipping Name:			
Hazard Class:			
ID# & Secondary Hazards:_	· · · · · · · · · · · · · · · · · · ·		
Quantity (WT):			
Radionuclides:			
Physical Form:			
Chemical Form:			
Activity (C1):			
Labels (W-I,Y-II,Y-III):_			<u></u>
I.I.:			
Fissile Class (I,II,III):			
COMESTINES IN (COC 4):			
Miscellaneous:			
SCHEDULED DEPARTURE	Dates:To:	Time:	
ROUTING INFORMATION (Comp	leted by Traffic)		
Pouts:			
FTA Dates:	To:	Time:	
State B Name:	<u> </u>		
Route:	1		
ETA Dates:	To:	Time:	
	<u> </u>		
State C Name:			
Route:			
ETA Dates:	To:	Time:	
			
State D Name:			
Route:			
ETA Dates:	To:	Time:	
APPROYALS			
Originator Approval	•		
Signature:		Date:	
Print Name:			
			
Traffic Department Concur	Tence		
		Date:	
Print Name:			
POINT OF CONTACT			
Department of Energy			
Signature:		Date:	
2131404141		~~·	

7 20630

O

THIS PAGE INTENTIONALLY LEFT BLANK

WESTINGHOUSE HANFORD COMPANY

Manual Section WHC-CM-2-14

Page

Appendix D2, REV 0 D2-1 of D2-2

Effective Date Organization

August 1, 1988 Procurement and

Materials Management

HAZARDOUS MATERIAL PACKAGING AND SHIPPING

TITLE:

PRENOTIFICATION REQUIREMENTS FOR OFFSITE SHIPMENTS OF HIGHWAY ROUTE CONTROLLED QUANTITIES OF RADIOACTIVE MATERIALS ...

Approved by

D. K. Quigley, Manager

Procurement and Materials Mgmt

1.0 PURPOSE

The purpose of this procedure is to provide guidance in the U.S. Department of Energy (DOE) prenotification requirements related to the offsite shipments of Highway Route Controlled Quantities of radioactive materials. The requirements stated here are a result of a DOE directive dated May 8, 1985.

M

Printer.

◆ 2.0 SCOPE

 \mathbb{C} This procedure establishes requirements to be followed by each facility originating Highway Route Controlled Quantities of radioactive material shipments to offsite destinations.

> 3.0 GUIDANCE AND REQUIREMENTS

- 3.1 The manager or designate of a facility who arranges for the offsite shipment of a Highway Route Controlled Quantity of radioactive materials must provide to Traffic, 60 days prior to first shipment. the following \bigcirc data which will be forwarded to the DOE in a timely manner:
 - Materials to be shipped
 - o Expected dates for the first and last shipment
 - o Estimated number of shipments
 - o Package or cask to be used
 - o Destination of receiving facility
 - Security arrangements (when required).
 - 3.2 Traffic will provide the following additional information:
 - o Mode of transport
 - o Probable carriers
 - o Probable route to destination

THIS PAGE INTENTIONALLY LEFT BLANK

WESTINGHOUSE HANFORD COMPANY

Manua 1 Section WHC-CM-2-14

Page

Appendix D2, REV 0 D2-1 of D2-2

Effective Date Organization

August 1, 1988 Procurement and

Materials Management

HAZARDOUS MATERIAL PACKAGING AND SHIPPING

PRENOTIFICATION REQUIREMENTS FOR OFFSITE

SHIPMENTS OF HIGHWAY ROUTE CONTROLLED

QUANTITIES OF RADIOACTIVE MATERIALS

TITLE:

Approved by

D. K. Quigley, Manager

Procurement and Materials Mgmt

1.0 PURPOSE

The purpose of this procedure is to provide guidance in the U.S. Department of Energy (DOE) prenotification requirements related to the offsite shipments of Highway Route Controlled Quantities of radioactive materials. The requirements stated here are a result of a DOE directive dated May 8, 1985.

2.0 SCOPE

700

This procedure establishes requirements to be followed by each facility Originating Highway Route Controlled Quantities of radioactive material shipments to offsite destinations.

3.0 GUIDANCE AND REQUIREMENTS

- The manager or designate of a facility who arranges for the offsite -3.1 shipment of a Highway Route Controlled Quantity of radioactive materials must provide to Traffic, 60 days prior to first shipment, the following data which will be forwarded to the DOE in a timely manner: \bigcirc
 - o Materials to be shipped
 - o Expected dates for the first and last shipment
 - o Estimated number of shipments
 - o Package or cask to be used
 - o Destination of receiving facility
 - Security arrangements (when required).
- 3.2 Traffic will provide the following additional information:
 - o Mode of transport
 - o Probable carriers
 - o Probable route to destination

Manual Section Page

Effective Date

WHC-CM-2-14 Appendix D2, REV 0

PRENOTIFICATION REQUIREMENTS FOR OFFISTE SHIPMENTS OF HIGHWAY ROUTE CONTROLLED QUANTITIES OF RADIOACTIVE MATERIALS

D2-2 of D2-2 August 1, 1988

3.3 Should any of the above data be classified, then submission of data must be in complete compliance with applicable Safeguards and Security Directives and Orders.

NOTE:

M

17

Notification concerning continuing campaigns, such as the Westinghouse continuing movements of irradiated materials to Idaho and New Mexico, are not required. Notifications concerning the shipments made via the Albuquerque Operations Office Transportation Safeguards Division are also exempt from this requirement.

3.4 Guidance regarding prenotification requirements for spent fuel and other radioactive waste is provided in Appendix I-1, "Prenotification Requirements for Spent Fuel and High Level Radioactive Waste Shipments."

Manual Section Page

Effective Date

WHC-CM-2-14 Appendix E, REV O E-1 of E-19

RADIOACTIVE MATERIALS PACKAGING QUALITY
ASSURANCE PROGRAM PLAN

July 15, 1989

1.0 PURPOSE

This plan implements the elements of the Quality Assurance (QA) Program for all activities associated with the design, procurement, fabrication, and inspection verification of reusable radioactive materials packaging. This program conforms to the eighteen Quality Assurance Requirements of the Consensus Standard ANSI/ASME NQA-1-1986 as endorsed by the U.S. Department of Energy (DOE) in Orders.

2.0 SCOPE

M

O

O

7. 7

.

<u>()</u>

.....

The scope of this plan extends to operations performed on and off the Hanford Site under the jurisdictional authority of the Westinghouse Hanford Company (WHC).

3.0 GENERAL REQUIREMENTS

Existing packaging that has been approved for use shall continue to be acceptable for use under this plan provided they are subjected to the inspections, modification control, and handling requirements specified by this plan.

This plan addresses the requirements of WHC-CM-4-2, Quality Assurance Manual, the 18 elements of 10CFR71, Subpart H, and the QA requirements of DOE Order 5480.3 as they pertain to WHC activities. The following paragraphs identify the requirements for Radioactive Material Packaging (RAMPAK) and implement the QA requirements of 49CFR173 and 178. A standards and procedures matrix (QA Program Index) for RAMPAK is shown in Table 1 for ready reference to the requirements and implementing procedures.

1. ORGANIZATION

The WHC Quality Assurance Function is responsible for establishing an appropriate QA program and for assessing the effectiveness of the program to provide product and service quality. WHC-CM-1-3, Management Requirements and Procedures, MRP 5.2, "Quality Assurance," establishes policies, organizational requirements, responsibilities, and authority for the QA program, the QA function, and other WHC organizations participating in the RAMPAK program.

The Manager of the QA function reports to the Safety, Quality Assurance and Security Department Manager, who reports directly and independently to the Vice President and President of WHC. The responsibilities of the QA Manager include ensuring that WHC manuals and procedures provide complete and adequate instructions for the implementation of quality assurance requirements, and for ensuring sufficient reviews, inspections and audits are conducted by QA personnel to verify compliance to the procedures.

Manual Section Page Effective Date WHC-CM-2-14
Appendix E, REV 0
E-2 of E-19

RADIOACTIVE MATERIALS PACKAGING QUALITY
ASSURANCE PROGRAM PLAN

July 15, 1989

The Procurement and Materials Management (PMM) of the Resources Allocation and Management (RAM) Department, Traffic group provides overall coordination of the WHC hazardous material packaging and shipping program via the WHC-CM-2-14, <u>Hazardous Materials Packaging and Shipping Manual</u>.

Packaging Development under Advanced Reactor Engineering Division is responsible for the onsite packaging designs and the Safety Analysis Reports for Packaging (SARP) which support the use of the packaging at Hanford.

The safe and efficient use of the RAMPAK is the responsibility of the packaging user.

- o The packaging owner's responsibilities include ensuring that packaging has valid inspection tags and for notifying QA and Non Destructive Examination (NDE) when an inspection is needed.
- o The cognizant engineer is responsible for the design of, and any design changes to, the RAMPAK.
- o The user is responsible for the proper use of the RAMPAK.

2. QUALITY ASSURANCE PROGRAM

This Quality Assurance Program Plan (QAPP) specifies the appropriate requirements from the WHC-CM-4-2 for the RAMPAK program, and the attached QA Program Index (QAPI) identifies the procedures or documents which implement the specific QA requirements. Impact Levels are determined in accordance with MRP 5.43, "Impact Levels." All WHC organizations who participate in the RAMPAK program shall comply with this program as specified.

3. DESIGN CONTROL

 \bigcirc

 \mathbb{C}^{3}

. 7. 19

Engineering design activities for RAMPAK shall be accomplished in accordance with WHC-CM-6-1, <u>Standard Engineering Practices</u> and 49CFR173. The responsible design organization shall prepare specifications, instructions, and drawings as applicable to describe the associated activities. Packaging Development shall prepare the SARP.

Design reviews at WHC shall be in accordance with WHC-CM-6-1, <u>Standard Engineering Practices</u>, EP 4.1, "Design Verification Requirements." Supplier designs shall be approved by the responsible WHC design group prior to DOE review.

, Ci

5

S

O

,

 \bigcirc

∵}•

Manual Section Page Effective Date WHC-CM-2-14 Appendix E, REV 0 E-3 of E-19 July 15, 1989

RADIOACTIVE MATERIALS PACKAGING QUALITY ASSURANCE PROGRAM PLAN

A SARP shall be prepared and provide the analytical evaluation of the RAMPAK system in accordance with the DOE Order 1540.2 to demonstrate full compliance with the applicable regulations governing safe transport and/or storage or compliance through the use of appropriate administrative controls. If the container has an approved Certificate of Compliance (C of C) and all requirements and limitations of that C of C are met for Westinghouse's intended use of the container, then the SARP is acceptable without further comment. Waivers or exemptions to design requirements may be granted by the DOE in accordance with DOE Order 5480.3, provided the departure offers an equivalent degree of safety.

Interfaces shall be defined and controlled.

Changes to design documents shall be initiated, approved, and controlled through the use of the Engineering Change Notice (ECN) in accordance with WHC-CM-6-1, EP 2.2, "Engineering Document Change Control." The ECN is the approved method for making proposed changes to technical documents controlling the RAMPAK. Changes to the supplier design documents shall be transmitted via the ECN through the WHC review system for approval.

Software shall be developed and controlled in accordance with the design control section 3 of the Quality Assurance Manual. Additionally at WHC, the WHC Standard Engineering Practices, WHC-CM-6-1, EP 2.1, "Computer Software Configuration Management," shall be used to document software control. When testing is used for software design verification, the test plan and results shall be documented and included in the final documentation package.

4. PROCUREMENT DOCUMENT CONTROL

The procurement of packaging or associated packaging system components and services shall be controlled to assure conformance with specified RAMPAK requirements. The design basis and related requirements necessary to ensure adequate quality shall be included or referenced in documents for the procurement of items and services. Procurement documents shall require the supplier to have a QA program. The WHC technical and QA organizations shall verify the adequacy of the supplier QA program.

The design organization and QA shall review and approve manufacturing plans and indicate where independent source verifications are necessary.

Requirements for the contents of procurement documents, procurement planning, supplier selection, bid evaluation, supplier performance evaluation, control of supplier generated documents, control of changes in items or services, acceptance of items or services, and QA requirements are contained in WHC-CM-2-1, <u>Procurement Manual and Procedures</u>, and WHC-CM-2-2, <u>Materials Management Manual</u> while QA requirements for procurement are specified in paragraph 4 of WHC-CM-4-2.

Manual
Section
Page
Effective Date

WHC-CM-2-14 Appendix E, REV 0 E-4 of E-19

RADIOACTIVE MATERIALS PACKAGING QUALITY
ASSURANCE PROGRAM PLAN

July 15, 1989

The procurement of Nuclear Regulatory Commission (NRC) licensed shipping containers shall be reviewed by the Procurement Review Board and approved by the responsible DOE-RL organization, prior to the award of the contract. Although other organizations may be represented, the Procurement Review Board shall consist of representatives from at least the following WHC organizations:

- o Engineering
- o Safety
- o QA
- o Radiological Assessment, Packaging and Shipping
- o Independent Technical Reviewer
- o Packaging and Shipping Subcouncil (Optional)
- o DOE-RL (Optional)

Changes to supplier design documents shall be processed in accordance with the methods specified in the supplier's QA program and approved by WHC.

5. INSTRUCTIONS, PROCEDURES, AND DRAWINGS

Packaging and shipping activities associated with RAMPAK shall be performed in accordance with methods prescribed by the WHC-CM-2-14, <u>Hazardous Materials Packaging and Shipping Manual</u>.

Westinghouse Hanford Company designs shall be translated into engineering drawings per WHC-CM-6-1, EP 1.3, "Preparation of Engineering Drawings." Supplier designs shall be prepared in accordance with methods specified in applicable standards and approved by WHC.

All fabrication of RAMPAK shall be in accordance with approved procedures as specified in the QA program.

All records prepared for the RAMPAK program which identify design criteria or fabrication methods shall be legible. Record retention shall comply with the requirements for records specified in paragraph 17 of this plan.

6.0 DOCUMENT CONTROL

 \bigcirc

, , ,

Documents specifying quality requirements or prescribing activities affecting quality shall be controlled through procedures which provide the administrative directions for the preparation, issue, approval, and control of design documentation, including changes thereof.

Preparation and change of design documents at WHC shall be performed in accordance with WHC-CM-6-1.

Manual Section Page Effective Date WHC-CM-2-14 Appendix E, REV 0 E-5 of E-19 July 15, 1989

RADIOACTIVE MATERIALS PACKAGING QUALITY ASSURANCE PROGRAM PLAN

Documents affecting quality shall be approved based on Impact Level definitions described by MRP 5.43. Impact of changes shall be evaluated by the cognizant design engineer against the original design base. Any change to an NRC or DOE licensed package shall be an impact level I change. Suppliers shall demonstrate that their internal document control system is in compliance with their approved QA program.

7. CONTROL OF PURCHASED ITEMS AND SERVICES

The procurement of items and services associated with the RAMPAK program shall be controlled through the issue of purchase orders in accordance with the requirements of the WHC-CM-2-1 and WHC-CM-2-2. The design, design base and other supporting requirements, necessary to assure adequate quality shall be included or referenced in the procurement package prepared for the purchase or containers or associated components.

The supplier shall be required to have a QA program consistent with the applicable requirements of the NQA-1. The supplier shall be responsible for all work conducted by sub-tier suppliers under their contract. The WHC cognizant engineer, or delegate, and supporting QA shall evaluate the supplier's QA program prior to purchase order placement.

Suppliers that are designated for design and/or fabrication services shall demonstrate their systems to be satisfactory for complying with the assigned specifications. Once approved, all changes in the design, including those resulting from anomalies or changes in the fabrication methods, shall be documented and approved by the WHC technical staff and QA organization through use of the ECN.

WHC QA shall provide independent inspection for all procured packaging.

8. IDENTIFICATION AND CONTROL OF ITEMS

The identification of materials or items ordered to specifications, standards, or codes must be maintained throughout fabrication, assembly, storage, and installation.

When traceability of material is required, identification shall be fixed to the resulting parts prior to subdivision of the material. Traceability must be maintained during fabrication. For Government Furnished Material (GFM), appropriate identification markings shall be applied to material and the supplier must demonstrate an independent method for tracking the documentation accompanying the material.

All RAMPAK shall be identified and controlled by the packaging owner to prevent incorrect use or the use of containers whose inspection tags have expired.

 \Box

أستية

9

(***)

Manual Section Page Effective Date

WHC-CM-2-14 Appendix E, REV 0 E-6 of E-19

RADIOACTIVE MATERIALS PACKAGING QUALITY ASSURANCE PROGRAM PLAN

July 15, 1989

Identification and control of items at WHC shall be in accordance with Section 8 of WHC-CM-4-2, <u>Quality Assurance Manual</u>. Identification and control of items by the suppliers shall be in accordance with their approved QA program.

9. CONTROL OF PROCESSES

Processes affecting the quality of items or services relating to RAMPAK shall be controlled. Special processes that control or verify quality, such as those used in impact tests, heat tests, welding, heat treating, NDE, submersion and puncture tests, must be performed by qualified personnel using qualified procedures in accordance with specified requirements.

Process control procedures shall be in compliance with design specifications, codes, or standards. Special processes at WHC shall be controlled by approved procedures in accordance with section 9 of WHC-CM-4-2, Quality Assurance Manual. Control procedures shall specify the preparatory steps, processing details, conditions to be maintained during each step, and the requirements for records.

Special processes performed by the supplier shall be in accordance with their approved internal procedures demonstrating appropriate documented control of personnel, equipment, and method.

The supplier's internal QA program shall assure that personnel, processes, and equipment are qualified in accordance with the purchase order documents prior to initiation of the fabrication. Objective evidence shall be provided by the supplier.

Welding at WHC shall be performed in accordance with drawings, WHC-CM-6-10, Welding Manual, and WHC-CM-6-26, Welding Procedures Specifications Manual. Non Destructive Examination shall be performed in accordance with WHC-CM-4-38, Nondestructive Examination Procedures.

Supplier welding requirements and performing procedures shall be prepared in accordance with methods specified in Requirements 5 and 9 of NQA-1 and approved by WHC prior to use.

10. INSPECTION

Inspections are examinations or measurements to verify whether an item or activity conforms to specified requirements. Inspections of RAMPAK shall be conducted by qualified QA personnel unless otherwise documented with the concurrence of QA. Inspections shall be performed in accordance with Inspection Plans. Inspection hold points and inspection criteria shall be included in fabrication travelers or work instruction.

Manual Section Page Effective Date WHC-CM-2-14 Appendix E, REV O E-7 of E-19

RADIOACTIVE MATERIALS PACKAGING QUALITY ASSURANCE PROGRAM PLAN

July 15, 1989

Westinghouse Hanford Company inspection personnel shall be qualified prior to the inspection in accordance with WHC-CM-4-2, QI 2-4, "Qualification of Quality Assurance Inspection and Test Personnel." The personnel providing the inspections for suppliers shall have demonstrated sufficient evidence that they are qualified for the inspections they are performing. Inspections shall be planned per documented methods and the results documented and provided to WHC.

Inspections at WHC shall be done in accordance with WHC-CM-4-2, QR 10. Inspections performed by the suppliers shall be done in accordance with their approved internal procedures.

All inspection results shall be documented and include the acceptance criteria. Records provided to WHC shall be legible and include:

- o Item inspected
- o Date of inspection
- o Inspector

ڏڻ)

A.L.

Q.

(...

•

(~~)

1.7

- o Type of observation
- o Results or acceptability
- o Reference to information on action taken in connection with nonconformances

Quality Assurance has the responsibility for preparing and maintaining the inspection plans for each reusable Type A and Type B RAMPAK. Inspections shall be performed in accordance with WHC-CM-4-2, QI 13.2. When RAMPAK are out of use for periods exceeding 2 years, they will be put into a suspended category and inspected prior to use. The results of the inspection shall be documented and evaluated for acceptability and the proper tag attached to the RAMPAK.

11. TEST CONTROL

Tests required to verify conformance of an item or activity to specified requirements and to demonstrate satisfactory performance shall be planned and executed in accordance with WHC-CM-4-2, Section 11. Testing will meet the requirements of all applicable regulations.

Characteristics to be inspected and tested shall be specified in a test plan, as well as the methods to be used. The test plan must be approved by appropriate level of management and independent groups, including Safety and QA, to assure all requirements are fully met.

Test results shall be documented. The conformance of test results with acceptance criteria shall be evaluated. QA shall review and approve the test report to verify that the requirements for the test plan are fully addressed. The test results and report shall verify that the acceptance criteria specified in the test plan is met. Inspections for acceptance shall be performed by persons other than those who performed or directly supervised the work being inspected.

Manual Section Page Effective Date WHC-CM-2-14 Appendix E, REV 0 E-8 of E-19

RADIOACTIVE MATERIALS PACKAGING QUALITY
ASSURANCE PROGRAM PLAN

July 15, 1989

Tests conducted by supplier shall be conducted in accordance with approved test plans and procedures. WHC shall approve test plans and verify that all requirements are addressed in the plan. Test reports shall reflect that the criteria are being met and must be approved by the supplier's QA.

Test records, test plans, and test reports containing results shall be maintained in accordance with paragraph 17 of this QAPP and include as a minimum:

o Item tested

Z.

N)

C

ţ ``.

(_,)

- o Date of test
- o Name of tester or data recorder
- o Type of observation
- o Results and acceptability

The test reports shall be included in the final data package.

12. CONTROL OF MEASURING AND TEST EQUIPMENT

Westinghouse Hanford Company control shall be in accordance with WHC-CM-4-2, QR 12, "Measuring and Test Equipment Control" and ANSI/IEEE 498. All measuring and test equipment (M&TE) used for accepting material or equipment, controlling special processes, or obtaining test data shall be calibrated and be traceable to nationally recognized standards. Calibrations shall be performed at planned intervals to provide confidence in the reliability of the M&TE. Records of the M&TE calibrations shall be maintained in accordance with WHC-CM-4-2, QI 12-2, "Measuring and Test Equipment Calibration Documentation" and paragraph 17 of this QAPP.

The supplier shall maintain control of M&TE in accordance with their approved internal procedures which have been verified by WHC QA as meeting NQA-1, BR 12.

13. HANDLING, STORAGE, AND SHIPPING

Packaging, handling, shipping and storage of packaging which are purchased, fabricated, shipped or stored by WHC shall be controlled to prevent damage or loss and to provide adequate safety of personnel involved. This shall be done in accordance with:

WHC-CM-1-3, <u>Management Requirements and Procedures</u>, MRP 5.20, "Packaging and Transportation of Hazardous Materials."

WHC-CM-2-14, Hazardous Material Packaging and Shipping.

WHC-CM-3-5. Records Management.

Manual Section Page

WHC-CM-2-14 Appendix E, REV 0

Effective Date

E-9 of E-19 July 15, 1989

RADIOACTIVE MATERIALS PACKAGING QUALITY ASSURANCE PROGRAM PLAN

> WHC-CM-4-2, Quality Assurance Manual, QR 13.0, "Handling, Storage and Shipping."

WHC-CM-6-4, Hanford Hoisting and Rigging Manual.

INSPECTION, TEST. AND OPERATING STATUS 14.

Quality Assurance shall:

- Maintain and publish the Radioactive Shipping Container Status Report, indicating the status for reusable WHC RAMPAKs.
- b. Affix tags to RAMPAKs to indicate the individual status of each serially numbered container.
- Inspect non-WHC-owned RAMPAK prior to use by WHC personnel per owner's inspection plan or per WHC generated inspection plans and appropriately tag or otherwise indicate the status of the packaging.

The owner of the RAMPAK shall:

- Not use any container with an expired inspection tag.
- b. Notify QA for inspection of the cask.
- Provide input to QA for the Radioactive Shipping Container Status c. Report.
- Insure that the RAMPAK is authorized and in suitable condition for use.
- Examine RAMPAK per 49 CFR 173.475.

CONTROL OF NONCONFORMING ITEMS

Nonconformance reporting, control, and dispositioning shall be in accordance with WHC-CM-4-2, section 15, "Control of Nonconforming Items."

RAMPAKs that do not conform to specified requirements, or whose conformance is indeterminate, shall be controlled by the RAMPAK owner to Controls shall provide for identification, prevent inadvertent use. documentation, evaluation, segregation where practical, disposition of the nonconforming items, and notification to affected organizations.

٧Ţ.

2

0 * , * 3

C

3 T-12

Manual Section Page Effective Date WHC-CM-2-14 Appendix E, REV 0 E-10 of E-19

RADIOACTIVE MATERIALS PACKAGING QUALITY ASSURANCE PROGRAM PLAN

July 15, 1989

Identification of nonconforming packaging shall include hold tags placed in a conspicuous location appropriate to the RAMPAK size and weight. The hold tags are to be attached by WHC QA personnel, and detached by WHC QA personnel when the quality issue has been resolved and dispositioned. All dispositions shall be in accordance to WHC-CM-4-2, QI 15-1. DOE and NRC concurrence shall be obtained for dispositions which affect NRC license requirements.

16. CORRECTIVE ACTION

Conditions adverse to quality or significant conditions adverse to quality may be revealed by an audit, an unusual occurrence, a random observation during inspection, or from trend analysis of other reports (Nonconformance Report, etc.). The identification of unsatisfactory conditions, the cause of the condition, and the corrective action taken must be documented and appropriately reported. The reports must be verified by QA and appropriate levels of management for completeness.

Corrective action shall be in accordance with WHC-CM-4-2, QR 16, "Corrective Action", commensurate with the seriousness of the condition being corrected. Corrective action may also be identified in an unusual event report in accordance with MRP 5.14, "Event, Critique, and Unusual Occurrence Reporting." The effectiveness of corrective action must be demonstrated before a condition shall be considered corrected.

17. RECORDS

Records which furnish documentary evidence of quality for RAMPAKs shall be maintained in a manner consistent with the requirements and instructions of section 17 of WHC-CM-4-2. Records for the RAMPAK shall include a completed inspection plan and NDE Report for all RAMPAKs on which inspections are performed. The completed inspection report and NDE Reports shall be maintained by WHC QA with a copy submitted to the RAMPAK owner. Completed inspection reports and NDE reports shall be maintained for a minimum of six years as non-permanent records, except for the NRC and DOE licensed casks whose records are maintained for the life of the packaging. No further indexing or distribution shall be performed.

A copy of the specific license, C of C, or other approval of the packaging, drawings and other documents referenced in the approval relating to the use and maintenance of the packaging and to the actions to be taken prior to shipment shall be sent to Traffic per MRP 5.20, "Packaging and Transportation of Hazardous Materials."

Manual
Section
Page
Effective Date

WHC-CM-2-14 Appendix E, REV 0 E-11 of E-19 July 15, 1989

RADIOACTIVE MATERIALS PACKAGING QUALITY
ASSURANCE PROGRAM PLAN

Testing records required by NRC and DOE requirements shall be identified and preserved for the life of the packaging and a record plan shall be established for all new NRC and DOE licenced packaging. These records will be maintained by the owner of the RAMPAK and all records will be transferred with any change of owners. These responsibilities lie with the organization responsible for the RAMPAK, with assistance of appropriate support organizations including Safety and QA.

Quality records may be either the originals or copies. Microform is acceptable, except for radiographs. Records must be legible, written in ink or typed, identifiable, and retrievable. Records must be protected from damage, deterioration, or loss. Lost or damaged records must be replaced, restored, or substituted promptly to the extent possible.

Records shall be readily retrievable. The time required for retrieval shall be commensurate with the urgency with which the record would be needed.

Correction to quality records shall be performed in accordance with WHC-CM-4-2, QR 17.0, paragraph 8.

The cognizant design organization is responsible for the preparation and retention of records and records plan until the responsible WHC owner becomes identified and accepts the records and responsibility for the records.

18. AUDITS

-

T.

S

(")

\$1 mg

,

1

 \Box

.

Quality audits are conducted on both WHC project activities (internal audits) and suppliers (external audits) in accordance with WHC-CM-4-2, QR 18. Annual internal audits covering control of the RAMPAK and the shipping of radioactive material shall be performed by WHC QA.

Quality Assurance is responsible for conducting and scheduling quality audits. Audits are scheduled and performed to a prepared checklist and the results documented in a report to management. Follow up corrective actions are verified by the appropriate QA personnel.

4.0 REFERENCES

- DOE Order 1540.2, "Hazardous Material Packaging for Transportation-Administrative Procedures."
- 2. DOE Order 5480.3, "Safety Requirements for the Packaging and Transportation of Hazardous Materials, Hazardous Substances, and Hazardous Wastes," establishes the safety standards for hazardous materials packaging and transportation.
- 3. DOE-RL Order 5700.1A, "Quality Assurance," establishes quality assurance standards for Hanford operations.

10

A.

Effective Date

RADIOACTIVE MATERIALS PACKAGING QUALITY ASSURANCE PROGRAM PLAN

July 15, 1989

- 4. DOE Order 5700.6B, "Quality Assurance," establishes the quality assurance standards for DOE operations.
- ANSI/ASME NOA-1. Quality Assurance Program Requirements for Nuclear Facilities, American National Standard Institute/American Society of Mechanical Engineers Consensus Standard. This standard is endorsed for the Hanford Site.
- 6. ANSI/IEEE 498-1985, "Standard Requirements for the Calibration and Control of Measuring and Test Equipment Used in Nuclear Facilities."
- 7. 49 CFR 173, "Shippers General Requirements for Shipments and Packaging."
- WHC-CM-1-2, Organization Charts and Charters. CH CC-5, "Safety and Environmental Advisory Council."
- 9. WHC-CM-1-3, Management Requirements and Procedures. MRP 5.2, "Quality Assurance."
 MRP 5.14, "Event, Critique, and Unusual Occurrence Reporting."
 MRP 5.20, "Packaging and Transportation of Hazardous Materials." MRP 5.43, "Impact Levels."
- 10. WHC-CM-2-1, Procurement Manual.
- 11. WHC-CM-2-2, Materials Management Manual.
- WHC-CM-2-14, Hazardous Material Packaging and Shipping, has been established as the WHC authority for the packaging and shipment of radioactive and hazardous materials. This manual incorporates the requirements and controls specified in the following:

10 CFR 71, "Packaging and Transportation of Radioactive

Materials"

49 CFR 178, "Shipping Container Specifications" 49 CFR 171 - 49 CFR 173

- 13. WHC-CM-3-5. Records Management.
- WHC-CM-4-2, Quality Assurance Manual, provides structure for the eighteen criteria contained in the NQA-1 consensus standard and supplements.
- WHC-CM-4-38, Nondestructive Examination Procedures. 15.
- Standard Engineering Practices, WHC-CM-6-1. defines preparing and controlling requirements for engineering documentation.

O

<u>ල</u>

Manual Section Page Effective Date WHC-CM-2-14 Appendix E, REV 0 E-13 of E-19 July 15, 1989

RADIOACTIVE MATERIALS PACKAGING QUALITY ASSURANCE PROGRAM PLAN

17. WHC-CM-6-4, Hanford Hoisting and Rigging Manual.

- 18. WHC-CM-6-10, Welding Manual.
- 19. WHC-CM-6-26, Welding Procedures Manual.

О О

Manual Section Page Effective Date WHC-CM-2-14 Appendix E, REV 0 E-14 of E-19 July 15, 1989

RADIOACTIVE MATERIALS PACKAGING QUALITY ASSURANCE PROGRAM PLAN

Table 1. Quality Assurance Program Index. (Sheet 1 of 6)

NQA-1		Implementing Procedure(s)			
Criteria		WHC-CM-4-2 QR/QI	WHC-CM-1-3 MRP	Other WHC Manuals	0ther
BR-1	ORGANIZATION	1.0	5.2		
15-1	Multiple Organizations	,			
15-1	Organizational Responsibilities				
BR-2	QUALITY ASSURANCE PROGRAM	2.0			DOE 5480.3 10CFR71
	QA Program Planning/Project Type Activities	2.1			
	QA Program Planning	2.2			
25-4	QA Indoctrina- tion and Training	2.3			
2S-1	Qualification of QA Inspection and Test Personnel	2.4			
25-3	Qualification of Audit Personnel	2.5			
25-2	Management Assessments	2.7			

Manual Section Page WHC-CM-2-14 Appendix E, REV 0 E-15 of E-19 July 15, 1989

RADIOACTIVE MATERIALS PACKAGING QUALITY ASSURANCE PROGRAM PLAN

Page Effective Date

Table 1. Quality Assurance Program Index. (Sheet 2 of 6)

NQA-1		Implementing Procedure(s)				
Criteria	Title	WHC-CM-4-2 QR/QI	WHC-CM-1-3 MRP	Other WHC Manuals	Other	
BR-3	DESIGN CONTROL	3.0	5.20	CM-6-1	49CFR17 3	
3S-1	QA Verification and Evaluation of Design Activities	3.1		CM-6-1, EP 2.1 and 4.1	DOE 1540.2 DOE 5480.3	
3S-1	Change Control			EP 2.2		
	Changes to Non-WHC Design Documents			EP 2.2		
BR-4	PROCUREMENT DOCUMENT CONTROL	4.0	5.20	CM-2-1, CM-2-2		
45-1	Procurement Document Control	4.1				
	External Services Control	4.2				
BR-5	INSTRUCTIONS, PROCEDURES, AND DRAWINGS	5.0		CM-2-14 CM-6-1, EP 1.3		
	Preparation, Revision, and Control of QRs and QIs	5.1				
BR-6	DOCUMENT CONTROL	6.0	5.43	CM-6-1		
	QA Document Control	6.1				

 \Box

Manual Section Page Effective WHC-CM-2-14 Appendix E, REV 0 E-16 of E-19 July 15, 1989

RADIOACTIVE MATERIALS PACKAGING QUALITY Effective Date ASSURANCE PROGRAM PLAN

Table 1. Quality Assurance Program Index. (Sheet 3 of 6)

NQA-1 Criteria	_. Title	Implementing Procedure(s)				
		WHC-CM-4-2 QR/QI	WHC-CM-1-3 MRP	Other WHC Manuals	0ther	
BR-1	CONTROL OF PURCHASED ITEMS AND SERVICES	7.0		CM-2-1, CM-2-2		
7S-1	Procurement Planning and Control	7.1				
7S-1	Supplier Qualification	7.2	·			
75-1	Source Inspection	7.3				
7S-1	Receiving Inspection	7.4				
BR-8	IDENTIFICATION AND CONTROL OF ITEMS	8.0				
8S-1	Material Identification and Control	8.1				
BR-9	CONTROL OF PROCESSES	9.0				
	Control of Nondestructive Examinations	9.1		CM-4-38		
95-1	Control of Welding and Brazing	9.2		CM-6-10, CM-6-26		

Manual Section Page WHC-CM-2-14 Appendix E, REV 0 E-17 of E-19 July 15, 1989

RADIOACTIVE MATERIALS PACKAGING QUALITY ASSURANCE PROGRAM PLAN

Page Effective Date

Table 1. Quality Assurance Program Index. (Sheet 4 of 6)

NQA-1		Implement	ing Procedure(s)	
Criteria	Title	WHC-CM-4-2 QR/QI	WHC-CM-1-3 MRP	Other WHC Manuals	0ther
BR-10 10S-1	INSPECTION	10.0			
	Inspection Instruction for Operations, Maintenance, and Modifications	10.1			
	Inspection Instruction for Manufacturing and Fabrication	10.2			
	Surveillance	10.4			
	Selection and Interpretation of Readings form Variable- Reading Gages and Instruments	10.5			
BR-11	TEST CONTROL	11.0			
	Test Verifi- cation	11.1			
BR-12 12S-1	CONTROL OF MEASURING AND TEST EQUIPMENT	12.0			
	Acquisition and Calibration of Measuring and Test Equipment	12.1			ANSI/IEEE 498
	M&TE Calibration by Users				

LO

Q

 \bigcirc

 \bigcirc

Manual Section Page Effective Date

WHC-CM-2-14 Appendix E, REV 0 E-18 of E-19 July 15, 1989

RADIOACTIVE MATERIALS PACKAGING QUALITY ASSURANCE PROGRAM PLAN

Table 1. Quality Assurance Program Index. (Sheet 5 of 6)

NQA-1 Criteria	Title	Implementing Procedure(s)				
		WHC-CM-4-2 QR/QI	WHC-CM-1-3 MRP	Other WHC Manuals	0ther	
BR-13	HANDLING, STORAGE, AND SHIPPING	13.0				
	Lifting	13.1		CM-6-4		
	Radioactive Materials Packaging	13.2	,	·		
BR-14	INSPECTION, TEST, AND OPERATING STATUS	14.0				
	Inspection and Test Status	14.1				
BR-15 15S-1	CONTROL OF NONCONFORMING ITEMS	15.0				
	Nonconforming Item Reporting	15.1	5.14			
	Nonconforming Item Control	15.2			; ! !	
BR-16	CORRECTIVE ACTION	16.0		<u>.</u>		
	Analysis and Trending	16.1				
	Corrective Action Reporting	16.2				
BR-17	QUALITY ASSURANCE RECORDS	17.0	5.20			
	Records Contról	17.1				

HAZARDOUS MATERIAL PACKAGING AMD SHIPPING

Manual Section Page Effective Date

WHC-CM-2-14 Appendix E, REV 0 E-19 of E-19 July 15, 1989

RADIOACTIVE MATERIALS PACKAGING QUALITY ASSURANCE PROGRAM PLAN

 \bigcirc

Quality Assurance Program Index. (Sheet 6 of 6) Table 1.

	NQA-1 Criteria		Implementing Procedure(s)			
			WHC-CM-4-2 QR/QI	WHC-CM-1-3 MRP	Other WHC Manuals	0ther
	BR-18	AUDITS	18.0		,	DOE 5480.3
c:	185-1	Audit Programming and Schedule	18.1			
9 0 n >	185-1	Planning, Conducting, Reporting, and Follow-up of Quality Audits	18.2			

THIS PAGE INTENTIONALLY LEFT BLANK

HAZARDOUS MATERIAL PACKAGING AND SHIPPING	Manual Section Page	WHC-CM-2-14 Glossary, REV 1 1 of 11
GLOSSARY AND ACRONYMS	Effective Date	July 15, 1989

The following abbreviations, acronyms, and definitions are provided to clarify material contained in this manual, and apply to the use of this manual only.

- "A1". Means the maximum activity of special form radioactive material permitted in a Type A package (49 CFR 173.403(a)).
- "A2". Means the maximum activity of radioactive material, other than special form of low specific activity radioactive material, permitted in a Type A package (49 CFR 173.403(b)).
- $\underline{A_1A_2}$ System. A method for determining radioactive material quantity categories and proper packaging for each category.
- Activity. The total amount of radioactivity in a shipment expressed in the traditional units of curies, e.g., Ci, mCi, uCi, etc., or the International System (SI) units of becquerels (Bq).
 - ALAP. Acronym for As Low As Practicable.

5.00

S S

 \bigcirc

7.7

 \bigcirc

~

- ALARA. Acronym for As Low As Reasonably Achievable.
- ALO-TSD. Acronym for Albuquerque Operations Office Transportation Safeguards Division.
- Alpha Particle (α) . A particle identical to the helium atom nucleus emitted by some radionuclides called alpha emitters. Each alpha particle consists of two protons and two neutrons and has two positive charges.
- Beta Particle (B). A particle with same mass and size of an electron with either a negative (electron) or a positive (positron) charge emitted from an atomic nucleus in the disintegration process.
- <u>Bill of Lading</u>. A non-negotiable document by which a carrier acknowledges receipt of freight and contracts for its movement.
- <u>Carrier</u>. An individual or corporation engaged in the business of transporting goods or passengers by land, sea or air.
- <u>Categories I, II, III.</u> Special Nuclear Materials (SNM) are divided by weight (grams) into three major categories with specific physical protection requirements for each. See DOE Order 5632.2A, "Physical Protection of Special Nuclear Materials and Vital Equipment." Category IV is an accountability categorization for source and other nuclear materials.
- <u>CFR</u>. Acronym for Code of Regulations; contains a codification of documents of general applicability and future effect. Published by the Office of the Federal Register as a special edition of the <u>Federal Register</u>.

WHC-CM-2-14 Glossary, REV 1 2 of 11 July 15, 1989

GLOSSARY AND ACRONYMS

4

LO

Ç

()

 \bigcirc

5.0

<u>COC</u>. Acronym for Certificate of Compliance. A permit to use a specific container issued by DOE or NRC.

Combustible Liquid. Any liquid with a <u>flash point</u> from 100 to 200 F or as measured by the tests specified in 49 CFR 173.115, except any mixture having one or more components with a flash point of 200 F or higher, that makes up at least 99% of the total volume of the mixture (49 CFR 173.115(b)).

Compressed Gas. Any material or mixture having in the container a pressure exceeding 40 psia at 70 F, or a pressure exceeding 104 psia at 130 F, or any liquid flammable material having a vapor pressure exceeding 40 psia at 100 F (49 CFR 173.300(a)).

Consignee. One to whom a shipment is addressed; the receiver

Consignor. One initiating a shipment; the shipper

<u>Consumer Commodity</u>. A material that is packaged or distributed in a form intended and suitable for sale through retail sales agencies or for consumption by individuals for purposes of personal care or household use. This term also includes drugs and medicines (49 CFR 171.8).

<u>Controlled Vehicle</u>. A vehicle having fixed radioactive contamination and a low potential for personnel contamination.

<u>Convoy.</u> Personnel and equipment designated to accompany a shipment while in transit.

<u>Corrosive Material</u>. Any liquid or solid that causes destruction of human skin tissue, or a liquid that has a severe corrosion rate on steel. (See 49 CFR 173.240(a) and (b) for details.)

CPS. Acronym for Criticality Prevention Specification.

CSAR. Acronym for Criticality Safety Analysis Report.

CSS. Acronym for Criticality Safety Specification.

<u>Curie (Ci)</u>. The international curie is a unit of radioactivity equal to 3.7×10^{10} disintegrations per second; also equal to 3.7×10^{10} becquerels (Bq).

<u>DOE</u>. Acronym for U.S. Department of Energy. A regulatory agency of the Federal Government that has jurisdiction over certain energy and defense waste programs and that establishes packaging requirements for radioactive materials in support of these programs.

 $\underline{\text{DOE-RL}}$. Acronym for U.S. Department of Energy. Richland Operations Office

WHC-CM-2-14 Glossary, REV 1 3 of 11 July 15, 1989

GLOSSARY AND ACRONYMS

<u>DOT</u>. Acronym for U.S. Department of Transportation. A regulatory agency of the Federal Government that has jurisdiction over the safe transport of materials moving in interstate commerce. The regulations covering the transportation of hazardous materials are found in 49 CFR Parts 171-179.

Emergency. Any serious event that causes a delay in transporting a package to its destination (e.g., vehicle breakdown, collision, highway obstruction, etc.).

EPA. Acronym for U.S. Environmental Protection Agency.

<u>Etiologic Agent</u>. A viable micro-organism or its toxin which causes or may cause human disease (49 CFR 173.386). Refer to the U.S. Department of Health, Education and Welfare Regulations, 42 CFR 72.25(c), for list of agents.

<u>Exclusive Use</u>. A shipment where the consignor reserves a vehicle exclusively for his use and where all initial, intermediate, and final loading and unloading is carried out under the direction of the consignor, consignee, or a designated agent.

<u>Explosive</u>. Any chemical compound, mixture, or device, the primary purpose of which is to function by explosion with substantial instantaneous release of gas and heat (49 CFR 173.50).

Fissile Class I. Shipments of fissile material in packages that may be transported in unlimited numbers, in any arrangement, and without any nuclear criticality safety array controls during transportation. A transport index is not assigned to Fissile Class I packages for purposes of nuclear safety control (49 CFR 173.455). However, the external radiation levels may require assignment of a transport index (49 CFR 173.403(bb)).

Fissile Class II. Shipments of fissile material in packages that may be transported together in any arrangement but in numbers that do not exceed an aggregate transport index of 50. For purposes of nuclear safety control, the transport index of an individual package shall not be less than 0.1, nor more than 10, and shall be the higher of the two values required by either external radiation levels or criticality prevention. Such shipment requires no nuclear safety control by the shipper during transportation (49 CFR 173.455).

<u>Fissile Class III</u>. Shipments of fissile material in packages that do not qualify as Fissile Class I or Fissile Class II packages. Nuclear safety control and radiation control during transportation are provided by special arrangement (e.g., exclusive use) between the shipper and the carrier (49 CFR 173.455).

<u>Fissile Exempt</u>. The quantity or concentration of fissile material exempt from DOT fissile material packaging requirements (49 CFR 173.453).

ru Iu

(C)

S

1

/T-14

WHC-CM-2-14 Glossary, REV 1 4 of 11 July 15, 1989

GLOSSARY AND ACRONYMS

Fissile Material. Any material containing $238p_u$, $239p_u$, $241p_u$, 233U, or 235U (49 CFR 173.403(j)). Neither natural nor depleted uranium are fissile material.

Flammable Gas. Any compressed gas meeting requirements for lower flammability limit, flammability limit range, flame projection, or flame propagation criteria as specified in 49 CFR 173.300(b).

Flammable Liquid. Any liquid with a flash point less than 100° F as measured by the tests specified in 49 CFR 173.115, with the following exceptions: (1) a flammable liquid with a vapor pressure greater than 40 psia at 100 F, as defined in 49 CFR 173.300; (2) any mixture having one component or more with a flash point of 100 F or higher that makes up at least 99% of the total volume of the mixture; and (3) a water-alcohol solution containing 24% or less alcohol by volume if the remainder of the solution does not meet the definition of a hazardous material contained in 49 CFR.

Flash Point. The minimum temperature at which a substance gives off flammable vapors which in the presence of air and in contact with spark or flame, will ignite (49 CFR 173.115).

<u>Forbidden</u>. Hazardous material that may not be offered or accepted for transportation (49 CFR 172.101(d)).

<u>Gamma Ray (\emptyset)</u>. An electromagnetic radiation emitted by the nuclei of certain radioactive substances during decay, similar in nature to X-Rays.

 $\underline{\mathsf{HM}}$. Acronym for Hazardous Material. A substance or material that has been determined to be capable of posing an unreasonable risk to health, safety, and property when transported and that has been so designated by the DOT (49 CFR 171.8).

HMSR. Acronym for Hazardous Material Shipment Record. A form recording data and documenting the shipment of (non-radioactive) hazardous material. This record when signed by an authorized individual certifies that the material has been properly prepared for shipment.

HRCQ. Acronym for Highway Route Controlled Quantity. A packaged quantity of radioactive material which when shipped offsite requires special routing, labeling, and placarding, in addition to other special requirements (49 CFR 173.403(1)).

<u>Hazardous Substance</u>. A quantity of a material offered for transportation that equals or exceeds the reportable quantity (RQ) specified for the material in EPA regulations (see 49 CFR 171.8 for specific criteria).

HW. Acronym for Hazardous Waste. A material subject to the hazardous waste manifest requirements of the EPA (see 49 CFR 171.8).

6 5

 \Box

, .

HAZARDOUS MATERIAL PACKAGING AND SHIPPING	Manual Section Page	WHC-CM-2-14 Glossary, REV 1 5 of 11
GLOSSARY AND ACRONYMS	Effective Date	July 15, 1989

IAEA. Acronym for International Atomic Energy Agency. An agency of the United Nations that provides regulations covering the shipment of fissile and other radioactive materials between countries. The Agency regulations are contained in IAEA pamphlet Safety Series Number 6, "Regulations for the Safe Transport of Radioactive Materials"; and Safety Series Number 37, "Advisory Materials for the Application of IAEA Transport Regulations".

International System (SI) of Units. An extended and improved form of the metric system being increasingly incorporated into general usage. A comparison of the appropriate traditional and SI units for radioactivity is given here.

Relationship

Quantity	Traditional Unit	SI <u>Unit</u>	of Traditional and SI Units
Activity	Curie (Ci)	becquerel (Bq)	$1 \text{ Bq} = 2.7 \times 10^{-11} \text{ Ci}$
	$2.2 \times 10^{12} \text{ dpm}$	1 dps	1 curie = 3.7 x 10 ¹⁰ Bq 37 GBq, 0.037 TBq
Absorbed Dose	rad	gray (Gy)	1 Gy = 100 rad 1 rad = 10 ⁻² Gy
Dose Equiva- lent	rem	sievert (Sv)	1 Sv = 100 rem 1 rem = 10 ⁻² Sv
Since a Bq	is extremely small, u	se: Kilobecquerel Megabecquerel Gigabecquerel Terabecquerel	

10

0

© C⊃

<u>Irritating Material</u>. A liquid or solid substance which upon contact with fire or exposure to air gives off dangerous or intensely irritating fumes, but not including any poisonous material, Class A (see 49 CFR 173.381).

<u>Limited Quantity</u>. The maximum amount of hazardous material, as specified in those sections of 49 CFR Part 173 applicable to the particular hazard class, for which there are <u>specific exceptions</u> from the requirements of the subchapter.

LSA. Acronym for Low Specific Activity Radioactive Material. see 49 CFR 173.403(n).

MFP. Acronym for Mixed Fission Products for which there is no specific definition. Generally includes mixtures of isotopes ranging in mass numbers from 70 to 162 depending on their half lives and time since formation in the fission process.

WHC-CM-2-14 Glossary, REV 1 6 of 11 July 15, 1989

Nonflammable Gas. Any compressed gas other than a flammable compressed gas (49 CFR 173.300).

Normal Formal Radioactive Material. See 49 CFR 173.403(s).

N.O.S.. Acronym for not otherwise specified.

NRC. Acronym in this manual, for U.S. Nuclear Regulatory Commission. A regulatory agency of the U.S. Government. It has, among other matters, jurisdiction over licensee packaging requirements for radioactive materials, some of which are adopted by DOE. This acronym is also used by the DOT in 49 CFR to mean non reuseable container.

<u>Nuclear Safety and Criticality Prevention</u>. Are used synonymously; the terms refer to the limits established to prevent nuclear chain reactions in a nonreactor environment.

Offsite Shipment. The movement of material from the packaging facility of any of the following onsite contractors to any offsite receiver:

Battelle Pacific Northwest Laboratory

Westinghouse Hanford Company

Kaiser Engineers Hanford Company

OHP. Acronym for Operational Health Physics.

Onsite Radioactive Shipment Record. A form recording data and documenting the onsite shipment of radioactive materials. This record when signed by an authorized individual certifies that the material has been properly prepared for shipment. The acronym for Onsite Radioactive Shipment Record is RSR.

Onsite Shipment. A movement of material within the confines of the Hanford Site between DOE-RL contractor facilities or between or within security areas. (See also Shipment)

Organic Peroxide. An organic compound containing the bivalent -0-0-structure and which may be considered a derivative of hydrogen peroxide where one or more of the hydrogen atoms have been replaced by organic radicals (see 49 CFR 173.151a for exceptions and details).

ORM. Acronym for Other Regulated Materials. Any material that does not meet the definition of another hazard class, but may pose an unreasonable risk to health and safety when transported and is specified in 49 CFR 172.101 as an ORM material or that possesses one or more of the characteristics described in ORM-A through E (see 49 CFR 173.500).

ល ហ

C)

4.,3

ممرا مهروا

 \mathbb{C}

Ğ.ν

Section Page Effective Date

Manual

WHC-CM-2-14 Glossary, REV 1 7 of 11 July 15, 1989

GLOSSARY AND ACRONYMS

O

LO

 \mathbb{C}

110 mg

ORSR. Acronym for Offsite Radioactive Shipment Record. A form recording data and documenting the offsite shipment of radioactive material. This form when signed by an authorized individual certifies that the material has been properly prepared for shipment.

Oxidizer. A substance such as chlorate, permanganate, inorganic peroxide, nitro carbo nitrate, or a nitrate that yields oxygen readily to stimulate the combustion of organic matter (49 CFR 173.151).

Package. The packaging and its contents as presented for transport.

<u>Packager</u>. The contractor responsible for the preparation of a package of hazardous material for shipment, including radioactive material.

<u>Packaging</u>. The assembly of containers, insulation, shielding, and other components as described in the package specification or COC.

<u>Placard</u>. A square-on-point sign measuring 10 3/4 in. per side; e.g., a radioactive placard has "Radioactive" in black letters on a yellow and white background (see 49 CFR Part 172, Subpart F, for details). This placard is displayed on the front, back, and sides of each dedicated onsite vehicle carrying radioactive material and each offsite vehicle carrying radioactive material which requires a Yellow III label or LSA full load. A recent change in the regulations governing offsite movement of an HRCQ of radioactive materials requires the radioactive warning placard be placed on a square background as described in 49 CFR 172.527. Placards are carried in store stock under the following identification:

- o Truck 37-6775-390
- o Rail 37-6775-300

<u>Poison A. Extremely Dangerous Poisons, Class A.</u> Poisonous gases or liquids of such nature that a very small amount of the gas or vapor of the liquid, mixed with air is dangerous to life (49 CFR 173.326).

Poison B. Less Dangerous Poisons. Substances, liquids, or solids (including pastes and semi-solids), other than Class A or irritating materials, which are known to be so toxic to man as to afford a hazard to health during transportation or are presumed to be toxic to man (49 CFR 173.343).

<u>Procedure</u>. Written instructions that specify or describe how an activity is to be performed. It may include methods to be employed, equipment or materials to be used, and sequence of operations.

Proper Shipping Name. Name of the hazardous material as shown in Roman print (not italics) in 49 CFR 172.101, Hazardous Materials Table.

PSAA. Acronym for Packaging and Shipping Approval Authority.

WHC-CM-2-14 Glossary, REV 1 8 of 11 July 15, 1989

GLOSSARY AND ACRONYMS

\Q

S

*****.54

....

PSSC. Acronym for Packaging and Shipping Sub Council.

Pyrophoric, Liquid. Any liquid that ignites spontaneously in dry or moist air at or below 130° F (49 CFR 173.115).

- OA. Acronym for Quality Assurance.
- OC. Acronym for Quality Control.

Rad. A unit of absorbed radiation dose, which approximates 0.01 grays (Gy) or 0.01 joule/kilogram (J/kg).

Radioactive Material. For offsite shipments, any material or combination of materials that spontaneously emits ionizing radiation and has a specific activity greater than 0.002 microcurie per gram (Ci/g) or 74 Bq/g (49 CFR 173.403(y)).

For onsite shipments items, materials, or equipment which meet any of the following criteria:

Specific activity exceeds 2 nCi/g,

Alpha activity exceeds 60 pCi/g,

Fixed or smearable radioactive contamination that is detectable with standard portable survey instruments,

Activity exceeds that for exempt quantities (listed in Appendix F, WHC-CM-4-10), or

The item is classified as a radioactive source.

RAM. Acronym for Resource, Allocation & Management Department. RAM shall not be used in this manual to denote radioactive material.

Regulated Vehicle. See Controlled Vehicle.

 $\underline{\text{REM}}$. Stands for "roentgen equivalent man"; it is the quantity of any type radiation having the same effect on the body as one rad of x or gamma radiation. One REM approximates 0.01 sievert (Sv) or 0.01 J/kg.

Removable Radioactive Contamination. Radioactive contamination that can be readily removed in measurable quantities by wiping the contaminated surface with an absorbent material. (See 49 CFR 173.443).

- RM. Acronym for Radiation Monitoring.
- RPT. Acronym for Radiation Protection Technologist.
- RQ. Acronym for Reportable Quantity.

RSR. Acronym for Onsite Radioactive Shipment Record.

RWP. Acronym for Radiation Work Procedure.

SARP. Acronym for Safety Analysis Report for Packaging.

<u>Seal (Type E)</u>. A numbered tamper-indicating seal, that is destroyed in disassembly.

Shipment. One or more packages of hazardous material to be transported to a consignee at one time, and may be in one or more vehicles. Onsite Shipments are classified as interarea (between areas) and intra area (within an area) movements. These shipments are movements that cause the material to change areas or building residences or custodianship. (See also User Movement)

Shipment, International. A shipment consigned to any foreign country.

Shipment, Large. A shipment weighing 5,000 lb or more.

Shipment, Small. A shipment weighing less than 5,000 lb.

Shipper. WHC is the shipper for DOE-RL of all hazardous and radioactive materials moved offsite by DOE-RL contractors in connection with contract-related work, including materials moved by DOE courier. (See RL 5480.1A, Chapter III).

SNM. Acronym for Special Nuclear Material.

Q

S

 \bigcirc

2.0

1

1

(N

Solid, flammable. Any solid material, other than an explosive, that is liable to cause fires through friction, absorption of moisture, spontaneous chemical changes, retained heat from manufacturing or processing, or that can be ignited readily and when ignited burns so vigorously and persistently as to create a serious transportation hazard (49 CFR 173.150).

Special Form Radioactive Material. See 49 CFR 173.403(z) and 173.469.

Special Nuclear Material. Any quantity of plutonium, ²³³U, or uranium-enriched in the ²³⁵U isotope. For more details, see DOE Order 5632.2.

<u>Spontaneously Combustible Material (solid)</u>. Any solid substance (including sludges and pastes) that may undergo spontaneous heating or self-ignition under conditions normally incident to transportation of that may upon contact with the atmosphere undergo an increase in temperature and ignite (49 CFR 171.8 and 173.150).

SST. Acronym for Safe Secure Trailer operated by ALO-TSD.

Section Page Effective

Manual

WHC-CM-2-14 Glossary, REV 1 10 of 11 July 15, 1989

GLOSSARY AND ACRONYMS

·.

4)

C)

•

 \Box

٠,٠

Effective Date

Transport Index (TI). The dimensionless number (rounded up to the first decimal place) placed on the label of a RAM package to designate the degree of control to be exercised by the carrier during transportation (See 49 CFR 173.403(bb)). The TI is used as a guide to control placement of radioactive material in a vehicle or in segregated batches for storage to reduce radiation exposure to people and/or to prevent the initiation of a criticality.

The shipper determines the TI as follows: For radioactive material packages of non-fissile material, i.e., those containing <15 g fissile material and/or any amount of other radionuclides the TI is simply the maximum radiation dose rate in m rem/hr measured at one meter (3.3 ft) from the surface of the package. For packages of fissile material the minimum TI is determined by a criticality safety analysis. This analysis evaluates the container with various fissile material loadings and determines the number of containers that may be shipped together on a single vehicle without causing a criticality. Since any one vehicle may transport no more than 50 transport index units at a time, the number 50 is divided by the maximum number of containers allowed per vehicle to determine the minimum TI assigned to each container. For example, criticality safety analysis for the Model 60 shipping container allows 125 Model 60s for a loading of 120 FFTF fuel pins each, to be shipped together at one time. The minimum TI per container then is 50/125 = 0.4 TI units. Note, this is the minimum TI for this specific As is often the case, however, we find the radiation dose rate from combined and neutrons for one of these containers with this loading exceeds 0.4 m rem/hr at one meter. In this case, the higher number, the measured dose rate, will become the TI. Do not add the 0.4 from criticality analysis and the dose rate reading to obtain the TI. The TI is only the higher value of the two.

TSDF. Acronym for Treatment Storage Disposal Facility.

Type A Packaging. See 49 CFR 173.403(gg).

Type A Quantity. See 49 CFR 173.431(a).

Type B Packaging. See 49 CFR 173.403(hh).

Type B Quantity. See 49 CFR 173.431(b).

<u>User Movement</u>. The transport of hazardous or radioactive material by an employee who will retain direct custody and use the material in performance of his onsite duties. As examples a painter moving a 5 gallon bucket of flammable paint from the storeroom or warehouse to job site where the paint is consumed; or a Radiation Protection Technician moving a radioactive source from building to building to check or calibrate radiation detection equipment.

HAZARDOUS MATERIAL PACKAGING AND SHIPPING	Manual Section	WHC-CM-2-14 Glossary, REV 1
GLOSSARY AND ACRONYMS	Page Effective Date	11 of 11 July 15, 1989

<u>Water Reactive Material (solid)</u>. Any solid substance (including sludges and pastes) which, by interaction with water, is likely to become spontaneously flammable or to give off flammable or toxic gases in dangerous quantities (49 CFR 171.8 and 713.150).

V

6 6

 \bigcirc

0

THIS PAGE INTENTIONALLY LEFT BLANK